



AUTOGUARD STARTING FLUID

Warren Oil Company

Product Data Sheet

MAXIMUM STARTING

Autoguard Starting Fluid has been formulated to deliver maximum starting strength. Ether and petroleum distillates are blended together to produce a starting fluid which has a low freezing point (does not freeze in extremely cold temperatures), high vapor pressure (produces vapor at low temperatures which passes through air intake systems and air filters), low flash point (ignition), high BTU content (starting power) and an upper cylinder lubricant for protection.

- Starts engines quickly
- Reduces drain on batteries
- Starts diesel or gasoline engines
- Contains an upper cylinder lubricant
- Fits diesel injector systems
- Gives smooth starts in all kinds of weather
- Easy to use



ETHER CONTENT

Extensive testing using a diesel engine in sub-zero temperatures has shown an optimum ether content range exists. Starting fluids containing too much ether, as well as not enough, failed to start a diesel engine at cold temperatures. Autoguard Starting Fluid gives maximum starting strength by carefully controlling ether content. Optimizing ether content gives consumers the best value and performance.

APPLICATIONS

For fast, easy starting, spray Autoguard Starting Fluid into the air intake for 2-3 seconds (no more than 3 seconds), then start the engine. Besides cars and trucks, Autoguard Starting Fluid works great on lawn mowers, trimmers, chain saws, motorcycles, etc. (not necessary to remove air filter.)

Warren Oil Company, Inc.

*Dunn, NC 28334: Benton, AL 36758: San Antonio, TX 78210:
Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72301*