



Coastal® HD Fleet Engine Oils

COASTAL HD FLEET ENGINE OILS combine high quality base oils with high performance additives to provide superb performance in the areas of detergency and dispersancy and protection against wear, rust, corrosion and high temperature thickening.

COASTAL HD FLEET ENGINE OILS are premium HD engine oils meeting API CF (10WT) and CF, CF-2 (30WT, 40WT, 50WT) for use in both turbo-charged and naturally aspired diesel engines. They meet the requirements of 2-cycle diesel engines made before 2007. They are also suitable for use in transmission applications calling for Allison C-4 specification. The SAE 10WT and 30WT are suitable for use in applications calling for Caterpillar TO-2, or Allison C4.

Benefits

- Resists breakdown under high temperatures
- Maintains oil pressure under heavy load conditions
- Helps prevent rust and corrosion

Typical Characteristics

SAE GRADE	10	30	40	50
API CF-2	N	Y	Y	Y
API CF	Y	Y	Y	Y
API Gravity @ 60 °F	31.6	28.5	28.2	26.5
spg @ 60 °F	0.676	0.8833	0.8853	0.8956
Flash,COC °F	430	460	470	470
Pour Pt ° F	-30	-20	-15	10
Viscosity, cSt @40 °C	40.4	95.5	142	205
Viscosity, cSt @100 °C	6.9	11.5	15.0	19.0
Viscosity Index	130	108	106	104
Sulfated Ash, Wt. %	0.9	0.9	0.9	0.9
TBN	7.3	7.3	7.3	7.3



Warren Oil Company, Inc