



**DRIRITE**  
*Absorbents for Industry*

## MSDS

### Dri-Rite Premium all purpose absorbent

Dri-Rite Premium all purpose absorbent is made with **Calcined Montmorillonite Clay** and **Dolomite**. These materials are mined domestically, are non toxic and non hazardous.

The Material Safety Data Sheets of these two naturally occurring minerals are attached for your convenience and filing.

Thank you,

The Dri-Rite Company

## 1. PRODUCT IDENTIFICATION

MSDS Number: 1003000  
Identity: Granular Absorbent  
Issued: July 11, 2008  
Chemical Name: Fullers Earth (attapulgite type) or montmorillonite or amorphous opaline silica

## 2. COMPOSITION

Component	CAS Number	Amount
Silica Hydrated (Amorphous Opaline Silica)	7631-86-9	90-100%
Fullers Earth	8031-18-3	80-90%
Montmorillonite	1302-78-9	90-93%
Quartz (crystalline silica)	14808-60-7	0-20% bulk

## 3. HAZARDS IDENTIFICATION

### EMERGENCY OVERVIEW

This product is a non-combustible, chemically inert mineral. This mineral sample contains a small amount of naturally-occurring crystalline silica as quartz. Prolonged overexposure to respirable crystalline silica may cause lung disease (silicosis). IARC, in Monograph 68, has concluded that crystalline silica inhaled in the form of quartz from occupational sources is carcinogenic to humans (Group 1); however, carcinogenicity was not detected in all industrial circumstances studied. Because applications and exposure data indicate that exposure to respirable quartz in this product with normal use is well below the OSHA Permissible Exposure Limit (PEL) and ACGIH Threshold Limit Value (TLV); and because the company is not aware of any scientific or medical data available indicating that exposure to dust from this product under conditions of normal use will cause silicosis or cancer; adverse effects would not be expected from normal use of this product.

### HEALTH HAZARDS

**INGESTION:** No adverse effects expected with unused material.  
**INHALATION:** Inhalation of excessive concentrations of dust may cause irritation of mucous membranes and upper respiratory tract.  
**EYE:** Contact may cause mechanical irritation and possible injury.  
**SKIN:** No adverse effects expected.  
**SENSITIZATION:** No adverse effects expected.

### CHRONIC/CARCINOGENICITY:

Inhalation of excessive concentrations of any dust, including this material, may lead to lung injury. This product contains crystalline silica. Excessive inhalation of respirable crystalline silica may cause silicosis, a progressive, disabling and fatal disease of the lung. Symptoms may include cough, shortness of breath, wheezing and reduced pulmonary function. The International Agency for Research on Cancer (IARC), in Monograph 68 has concluded that crystalline silica inhaled in the form of quartz or cristobalite, from occupational sources is carcinogenic to humans (Group 1).

However, in making the overall evaluation, the Working Group noted that carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs. The National Toxicology Program (NTP) classifies crystalline silica as a known carcinogen. Because applications and exposure data indicate that exposure to respirable quartz in this product with normal use is well below the OSHA Permissible Exposure Limit (PEL) and ACGIH Threshold Limit Value (TLV); and because the company is not aware of any scientific or medical data available indicating that exposure to dust from this product under conditions of normal use will cause silicosis or cancer; adverse effects would not be expected from normal use of this product.

**MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE:**

None currently known.

**4. FIRST AID MEASURES**

**EYE:** Immediately flush eyes with cool running water, lifting upper and lower lids. If irritation persists or for foreign body in the eye, get immediate medical attention.

**SKIN:** None needed for normal use.

**INGESTION:** If used material is ingested, get medical attention due to possibility of chemical contamination. If large amount of unused material is swallowed, get immediate medical attention.

**INHALATION:** Remove to fresh air.

**5. FIREFIGHTING MEASURES**

**FLASH POINT:** This product is not combustible.

**FLAMMABLE LIMITS** Not applicable

**EXTINGUISHING MEDIA:**  
Use media that is appropriate for surrounding fire.

**UNUSUAL FIRE OR EXPLOSION HAZARDS:**  
None

**SPECIAL FIREFIGHTING INSTRUCTIONS**  
None required.

**HAZARDOUS COMBUSTION PRODUCTS:**  
None

**6. ACCIDENTAL RELEASE MEASURES**

Sweep up and collect for re-use or disposal

**7. HANDLING AND STORAGE**

**HANDLING:** Avoid breathing dust. If clothing becomes dusty, launder before re-use.

**STORAGE:** Store in a dry area.



**CORPORATION OF AMERICA**  
 410 North Michigan Avenue  
 Chicago, IL 60611

# Material Safety Data Sheet

Granular Absorbent (#1003000)

(312)321-1515, Information (800)424-9300, Emergency

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### EXPOSURE GUIDELINES:

Component	Exposure Limit
Silica Hydrated (Amorphous Opaline Silica)	PEL - 5mg/m <sup>3</sup> TWA (respirable dust) TLV - 3mg/m <sup>3</sup> TWA (respirable fraction) TLV - 10mg/m <sup>3</sup> TWA (inhalable dust)
Fullers Earth	PEL - 5 mg/m <sup>3</sup> TWA (respirable fraction) TLV - 3 mg/m <sup>3</sup> TWA (respirable fraction) TLV - 10 mg/m <sup>3</sup> TWA (inhalable dust)
Montmorillonite	PEL - 5 mg/m <sup>3</sup> TWA (respirable fraction) TLV - 3 mg/m <sup>3</sup> TWA (respirable fraction) TLV - 10 mg/m <sup>3</sup> TWA (inhalable dust)
Quartz (crystalline silica)	PEL - 10 mg/m <sup>3</sup> /%SiO <sub>2</sub> +2 TWA TLV - 0.025 mg/m <sup>3</sup> TWA

*PEL- OSHA Permissible Exposure Limit. TLV- American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Value. TWA- 8 hour Weighted Average. STEL-Short Term Exposure Limit.*

### ENGINEERING CONTROLS:

For operations where the exposure limit may be exceeded, local exhaust ventilation is recommended.

### RESPIRATORY PROTECTION:

For operations where the exposure limit may be exceeded, a NIOSH/MSHA approved high efficiency particulate respirator is recommended.

**SKIN PROTECTION:** None required for normal use.

**EYE PROTECTION:** Safety glasses or goggles recommended.

**OTHER:** None required for normal use.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

### APPEARANCE AND ODOR:

Gray to tan (or red) granules, no odor

**PHYSICAL STATE:** Solid

**BOILING POINT:** Not applicable

**VAPOR PRESSURE:** Not applicable

**VAPOR DENSITY:** Not applicable

**SOLUBILITY IN WATER:**

Insoluble

**SPECIFIC GRAVITY:** 2.2

**pH:** Not applicable

**MELTING POINT:** Not applicable

**OCTANOL/WATER COEFFICIENT:**

Not available

**10. STABILITY AND REACTIVITY**

**STABILITY:** Stable

**INCOMPATIBILITY:** Physical contact between this material and turpentine, hydrofluoric acid, vegetable oil or other unsaturated organic compounds (such as fish oil) may generate heat and/or fire. Do not use this material with these compounds.

**HAZARDOUS DECOMPOSITION PRODUCTS**

None

**HAZARDOUS POLYMERIZATION:**

Will not occur.

**11. TOXICOLOGICAL INFORMATION**

No data available.

**12. ECOLOGICAL INFORMATION**

No data available.

**13. DISPOSAL CONSIDERATIONS**

Dispose in accordance with local, state and federal environmental regulations. Unused material is suitable for disposal in sanitary landfill. Used material may be subject to regulation, depending on the nature of the material absorbed. Check with appropriate regulatory authority for used material containing hazardous waste.

**14. TRANSPORT INFORMATION**

**PROPER SHIPPING NAME:**

Not regulated

**UN NUMBER:** Not applicable

**HAZARD CLASS/PACKING GROUP:**

Not applicable

**LABELS REQUIRED:** None

**15. REGULATORY INFORMATION**

**CERCLA/SUPERFUND** None

**SARA HAZARD CATEGORY (311/312):**

Chronic Health

**SARA 313:** None

**TSCA:** All of the components of this product are listed on the EPA TSCA Inventory or exempt from notification requirements.

**EINECS:** All of the components of this product are listed on the EINECS Inventory or exempt from notification requirements

**EEC R&S Phrases:** Not Classified as Dangerous under EEC Labeling Regulations

**JAPAN MITI:** All of the components of this product are existing chemical substances as defined in the Chemical Substances Control Law.

**AICS:** All of the components of this product are listed on the AICS Inventory or exempt from notification requirements

**CANADIAN DSL:** All of the components of this product are listed on the Canadian Domestic Substance List or exempt from notification requirements.

**CA PROPOSITION 65:** This product contains respirable crystalline silica which is known to the State of California to cause cancer.

## 16. OTHER INFORMATION

**NFPA RATING:** Health=1 Fire=0 Reactivity=0

**HMIS RATING:** Health=1 \* Fire=0 Reactivity=0

The information in this data sheet is believed to be accurate. However, each purchaser should make its own test to determine the suitability of the product for its purposes. OIL-DRI CORPORATION OF AMERICA MAKES NO WARRANTY, EXPRESSED OR IMPLIED, WITH RESPECT TO THE PRODUCT and assumes no responsibility for any risk or liability arising from the use of the information or the product. Statements about the product should not be construed as recommendations to use the product in infringement of any patent.

## APPENDIX. ASSOCIATED PRODUCTS

This MSDS applies to the following products:

Absorbs It	Oil Dri Regular Absorbent Plain
All Purpose 18/40	Oil Dri U.S. Special
All Purpose 18/40 2426#	Oil Zorb
Associates Premium	Oil Zorb Premium Abs
Calcine 5/18 Red	Oil-Dri Automotive Premium 4/10
Concentrate	Oil-Dri Premium Poly Abs
Concept Absorbent	Pvl Heavy Duty Generic
DOC Private	Quick Sorb Pail
Dryden Generic	SND Standard GB
Exclusiva	Super Clean A.P. 18/40
Flor Dri GA Generic	White Absorbent
GA A.P. Private Label	White Absorbent-Pvl
Ga Generic	
Grey Calcined 5/30	
Ground Clay 4/20 GW	
Ground Clay 6/30 GB	
Industrial Quick Sorb	
Instant Dri Blue	
Instant Dri Red	
Japanese Floor Abs.	
OD Premium Absorb	
OD Premium Absorbent	
O-D Sams Premium Poly	
Off Shore Generic	
Oil Dri 12/24 LVM	
Oil Dri Allpurpose	
Oil Dri Allpurpose 33 1/3	
Oil Dri Industrial	
Oil Dri Industrial Absorbent	
Oil Dri Premium Poly Abs	

## MATERIAL SAFETY DATA SHEET

### I. Material Identification And Use

Product Name: Dolomite, Indiana Ag Lime CAS#: 16389-88-1  
 Common Names: Carbonate of Calcium and Magnesium, Dolomitic Limestone  
 Chemical Name:  $\text{CaCO}_3\text{MgCO}_3$   
 Product Use: Used in the aggregate, metallurgical and agricultural industries  
 Product may contain respirable silica particles. CAS#: 14808-60-7

### II. Ingredients And Recommended Occupational Exposure Limits

Composition	Typical % Weight	Exposure Limits	
		OSHA PEL	ACGIH TLV
Mixture of Magnesium and Calcium Carbonate	97-99	15mg/m <sup>3</sup> Total Dust 5mg/m <sup>3</sup> Respirable Dust	10mg/m <sup>3</sup> Total Dust 5mg/m <sup>3</sup> Respirable Dust
Silica (Quartz)	0.1-2.0	0.1mg/m <sup>3</sup> TWA for Respirable Dust	0.1mg/m <sup>3</sup> TWA for Respirable Dust
Other Carbonate Minerals	<1.0		

### III. Physical Data

Boiling Point: 1652°F Specific Gravity: 2.7-2.95  
 Vapor Pressure: N/A Melting Point: N/A  
 Vapor Density: N/A Evaporation Rate: N/A  
 Stability: Stable Solubility in water: Negligible  
 Appearance: White to light gray – odorless solid

### IV. Fire And Explosion Hazard Data

Flashpoint: N/A Flammable Limits: N/A  
 Extinguishing Media: N/A LEL: N/A UEL: N/A  
 Unusual Fire and Explosion Hazards: Limestone is neither a fire nor explosion hazard.

### V. Reactivity Data

Stability: Stable Conditions to Avoid: None  
 Hazardous Decomposition: None Hazardous Polymerization: None  
 Incompatibles: Strong Acids



## **VI. Health Hazard Information**

Dolomite is essentially a non-toxic material. The refined form of magnesium carbonate is added to foods as a mild alkali. It is also used in pharmaceuticals and cosmetics. Extremely high concentrations of dolomite dust are self-limiting due to the nuisance conditions it may create, causing coughing, sneezing and nasal irritation. Dolomite may contain small amounts of respirable silica particles. Silica is capable of causing silicosis if inhaled in high enough concentrations over an extended period of time. Exposure to excessive concentrations may aggravate pre-existing respiratory conditions.

Carcinogenicity: None Identified

Routes of Entry:        Inhalation? YES        Skin? NO        Ingestion? YES

Emergency and First Aid Procedures:

Eyes – Not anticipated to pose an acute or significant hazard. If irritation occurs, flush eye with large amounts water.

Inhalation – Not anticipated to pose an acute or significant inhalation hazard. If irritation occurs, remove to an area of fresh air.

Ingestion – Not considered and ingestion hazard.

Skin Contact – Not anticipated to pose an acute or significant hazard. If skin is previously irritated wash area with plenty of soap and water for at least 15 minutes.

## **VII. Precautions For Safe Handling And Use**

Respirable dust may be generated during processing, handling, and storage.

Spillage, where dust may be generated, may overexpose cleanup personnel to respirable dust.

Wetting of the material and/or use of respiratory protective equipment may be necessary. Avoid dry sweeping.

Waste Disposal Method: Dispose of material in accordance with Federal, State, and Local regulations.

## **VIII. Control Measures**

Ventilation: Local exhaust or general ventilation adequate to maintain exposures below appropriate exposure limits.

Eye and Skin Protection: Wear long sleeve shirt and pants, Safety goggles and proper gloves.

Respiratory Protection: A respirator with dust/mist filter is recommended. If airborne concentration exceeds TLV, a self-contained breathing apparatus is advised.

UPDATED: August 28, 2002

Material Service Corporation  
Safety Department

The information contained in this Material Safety Data Sheet (MSDS) was obtained from sources, which we believe are reliable. However, the information is provided without any representation of warranty, expressed or implied, regarding the accuracy or correctness.

The conditions or methods of handling, storing, use and disposal of this product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of, or in any way connected with handling, storage, use or disposal of the products.