



CHAIN SAW BAR LUBRICANT

Warren Oil Company

Product Data Sheet

ITASCA CHAIN SAW BAR LUBRICANT is a premium lubricant designed especially for the lubrication of bar and chains on chain saws, and all types of link chains that require lubrication, including motorcycles and bicycles, as well as farm and industrial uses.

ITASCA CHAIN SAW BAR LUBRICANT is formulated with highly refined base stocks and an additive package to assure excellent performance as a chain saw bar and chain lubricant. A special tackifier is added to the oil, which promotes good adhesion to moving parts and minimizes oil throw off.

ITASCA CHAIN SAW BAR LUBRICANT is designed to prevent rusting and reduce wear and link breakage thus extending bar and chain life. Penetration into rivet holes and the bat channel is assured. Down-time and cutting interruptions are minimized.

Benefits

- Extends bar, chain and sprocket life
- Reduced throw off
- Reduces heat build-up
- Excellent rust and corrosion protection
- Different viscosity weights for various ambient temperatures

Warren Oil Company, Inc.

*Dunn, NC 28334 : Benton, AL 36758: San Antonio, TX 78210:
Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72303*



***CHAIN SAW BAR
LUBRICANT***

Typical Characteristics

	10W	20W	30W	40W
Gravity, API	32.8	30.8	29.5	28.9
Density,	0.8602	0.8708	0.8777	0.8808
Viscosity				
@ 40 Deg. C, cSt	22.49	51.29	85.97	118.56
@ 100 Deg. C, cSt	4.79	8.21	10.99	13.47
Viscosity Index	138	132	114	109
Pour Point Deg. F	-48	-36	-15	3

Warren Oil Company, Inc.

*Dunn, NC 28334 : Benton, AL 36758: San Antonio, TX 78210:
Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72303*