PENNZOIL® PREMIUM WHEEL BEARING 707L RED GREASE



MSDS Number: 592

Version Date: 6/1/01

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name: PENNZOIL® PREMIUM WHEEL BEARING 707L RED GREASE

Product Use: No information available

Synonyms: PENNZOIL® PREMIUM WHEEL BEARING GREASE 707L

Manufacturer

Pennzoil-Quaker State Company P.O. Box 2967 Houston, TX 77252-2967 USA **Phone Numbers**

Medical Emergency: 1-800-546-6040

Transportation Emergency (USA): 1-800-535-5053

 ${\bf Transportation\ Emergency\ (International):}$

1-352-323-3500 (Call Collect)

MSDS Assistance: 1-800-546-6227 Fax On Demand: 1-800-546-6227 Technical Assistance: 1-800-458-4998 Customer Service: 1-800-468-8397 Fax Number: 713-217-3181

Internet Address: www.MSDS.PZLQS.com

2. COMPONENT INFORMATION

Component	CAS No.	Weight Percent	Hazardous
		Range	in Blend
BASE LUBRICATING OILS	MIXTURE	80 - 90	No
LITHIUM SOAP	MIXTURE	5 - 15	No
EXTREME PRESSURE AGENT	MIXTURE	1 - 5	No
CORROSION INHIBITOR	MIXTURE	1 - 5	No
ANTIWEAR AGENT	MIXTURE	< 1	No
TACKIFIER	MIXTURE	< 0.5	No

This product is **NOT HAZARDOUS** according to OSHA 29 CFR 1910.1200.

Other: Greases consist of solid or semisolid dispersion of metallic soaps and other thickeners in a mineral oil base.

3. HAZARDS IDENTIFICATION

Emergency and Hazards Overview

CAUTION: Contains Petroleum Oil (Grease). Repeated skin contact can cause skin disorders.

ATTENTION: Repeated exposure to oil mist in excess of the OSHA limit (5mg/m3) can result in accumulation of oil droplets in pulmonary tissue.

NFPA Ratings:	Health	1 FI	amm	ability	1	Reactivity	0
Primary Route of	Exposure:	Skin	X	Inhala	tion	Eye	

Health Effect Information

Eye Contact: This product is minimally irritating to the eyes upon direct contact. Based on testing of similar products and/or components.

Skin Contact: Avoid skin contact. This product is minimally irritating to the skin upon direct contact. Prolonged or repeated contact may result in contact dermatitis which is characterized by dryness, chapping, and reddening. Prolonged or repeated contact may result in oil acne which is characterized by blackheads with possible secondary infection. A high pressure grease gun injection injury can cause serious, delayed soft tissue damage. See Section 4, First Aid Information.

MSDS Number: 592

PENNZOIL® PREMIUM WHEEL BEARING 707L RED GREASE

Inhalation: This product has a low vapor pressure and is not expected to present an inhalation hazard at ambient conditions. Caution should be taken to prevent aerosolization or misting of this product. On rare occasions, prolonged and repeated exposure to oil mist poses a risk of pulmonary disease such as chronic lung inflammation. Shortness of breath and cough are the most common symptoms. These are low-grade, chronic localized tissue reactions.

Ingestion: Do not ingest. This product is relatively non-toxic by ingestion. This product has laxative properties and may result in abdominal cramps and diarrhea. Exposure to a large single dose, or repeated smaller doses, may lead to lung aspiration, which can lead to lipid pneumonia or chronic lung inflammation. These are low-grade, chronic localized tissue reactions.

Medical Conditions Aggravated by Exposure: Drying and chapping may make the skin more susceptible to other irritants, sensitizers and disease.

Other: No information available

4. FIRST AID INFORMATION

Eye Contact: Immediately flush eyes with large amounts of water and continue flushing until irritation subsides. If material is hot, treat for thermal burns and seek immediate medical attention.

Skin Contact: No treatment is necessary under ordinary circumstances. Remove contaminated clothing. Wash contaminated area thoroughly with soap and water. If redness or irritation occurs and persists, seek medical attention. If material is hot, submerge injured area in cold water. If victim is severely burned, remove to a hospital immediately. If injected under skin, contact a physician immediately. High pressure grease gun injection injury, can cause serious, delayed soft tissue injury.

Inhalation: This material has a low vapor pressure and is not expected to present an inhalation exposure at ambient conditions.

Ingestion: No treatment is necessary under ordinary circumstances.

Notes to Physician: No information available

Other: No information available

5. FIRE AND EXPLOSION INFORMATION

Flammable Properties

Flash Point: 525 F, 273.9 C Test Method: ASTM D-92 (C.O.C.)

Flammable Limits in Air

Upper Percent: No data available **Lower Percent:** No data available

Autoignition Temperature: No data available Test Method: No information available

NFPA Classification: No information available

Extinguishing Media: Use dry chemical, foam, or carbon dioxide.

Fire Fighting Measures

Special Fire Fighting Procedures and Equipment: Water may be ineffective but can be used to cool containers exposed to heat or flame to prevent vapor pressure buildup and possible container rupture. Caution should be exercised when using water or foam as frothing may occur, especially if sprayed into containers of hot, burning liquid.

PENNZOIL® PREMIUM WHEEL BEARING 707L RED GREASE

Unusual Fire and Explosion Conditions: Dense smoke may be generated while burning. Carbon monoxide, carbon dioxide, and other oxides may be generated as products of combustion.

Hazardous Combustion By-Products: None

Other: No information available

MSDS Number: 592

6. ACCIDENTAL RELEASE MEASURES

Personnel Safeguards: Consult Health Effect Information in Section 3, Personal Protection Information in Section 8, Fire and Explosion Information in Section 5, and Stability and Reactivity Information in Section 10. Remove all sources of ignition.

Regulatory Notifications: No notification required

Containment and Clean up: Absorb with appropriate inert material such as sand, clay, etc. Large spills may be picked up using vacuum pumps, shovels, buckets, or other means and placed in drums or other suitable containers.

Other: No information available

7. HANDLING AND STORAGE INFORMATION

Handling: Fire extinguishers should be kept readily available. See NFPA 30 and OSHA 1910.106-Flammable and Combustible Liquids.

Storage: Do not transfer to unmarked containers. Store in closed containers away from heat, sparks, open flame, or oxidizing materials.

Empty Container Warnings

Drums: Empty drums should be completely drained, properly bunged and promptly returned to a drum reconditioner, or properly disposed.

Plastic: Empty container may retain product residues.

Other: No information available

8. EXPOSURE CONTROLS / PERSONAL PROTECTION INFORMATION

Exposure Limits and Guidelines

This product does not contain any components with OSHA or ACGIH exposure limits.

Personal Protective Equipment

Eye/Face Protection: Eye protection is not required under conditions of normal use. If material is handled such that it could be sprayed into eyes, wear plastic face shield or splash-proof safety goggles.

Skin Protection: No skin protection is required for single, short duration exposures. For prolonged or repeated exposures, use impervious clothing (boots, gloves, aprons, etc.) over parts of the body subject to exposure. If handling hot material, use insulated protective clothing (boots, gloves, aprons, etc.). Launder soiled clothes. Properly dispose of contaminated leather articles including shoes, which cannot be decontaminated.

Respiratory Protection: Respiratory protection is not required under conditions of normal use. If vapor or mist is generated when the material is heated or handled, use an organic vapor respirator with a dust and mist filter. All respirators must be NIOSH certified. Do not use compressed oxygen in hydrocarbon atmospheres.

Page 3 of 7

PENNZOIL® PREMIUM WHEEL BEARING 707L RED GREASE

Personal Hygiene: Consumption of food and beverage should be avoided in work areas where hydrocarbons are present. Always wash hands and face with soap and water before eating, drinking, or smoking.

Engineering Controls / Work Practices

MSDS Number: 592

Ventilation: General room ventilation is normally sufficient. If vapor or mist is generated when the material is heated or handled, adequate ventilation must be provided.

Other: As a precaution, all exposure to mists and vapors of petroleum products should be minimized. The OSHA permissible exposure limit (PEL) and ACGIH threshold limit value (TLV) for oil mist is 5 mg/m3. Chronic exposures below 5 mg/m3 are without significant health risks.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Amber colored grease			
Odor: Sweet	Vapor Pressure: No data available		
Physical state: No information available	Vapor Density (air=1): No data available		
pH: No data available	Percent Volatile by Volume: No data available		
Boiling Point: > 600 F, 315.6 C	Volatile Organic Content: No data available		
Melting Point: 475 - 500 F, 246.1 - 260 C	Molecular Weight: No data available		
Specific Gravity: 0.89	Average Carbon Number: No data available		
Pour Point: No data available	Viscosity @ 100 F: No data available		
	Viscosity @ 40 C: No data available		
Solubility in Water: Soluble in hydrocarbons, insoluble in water			
Octanol / Water Coefficient: Log K_{ow} = No data available			

10. STABILITY AND REACTIVITY INFORMATION

Chemical Stability: Stable

Conditions to Avoid: None

Incompatible Materials to Avoid: May react with strong oxidizing agents.

Other: No information available

11. TOXICOLOGICAL INFORMATION

Primary Eye Irritation: No information available

Primary Skin Irritation: No information available

Acute Dermal Toxicity: No information available

Subacute Dermal Toxicity: No information available

Dermal Sensitization: No information available

Inhalation Toxicity: No information available

Inhalation Sensitization: No information available

Oral Toxicity: No information available

Mutagenicity: No information available

Page 4 of 7

PENNZOIL® PREMIUM WHEEL BEARING 707L RED GREASE

MSDS Number: 592 Page 5 of 7

Carcinogenicity: The International Agency for Research on Cancer (IARC) has concluded that there is inadequate data to evaluate the carcinogenicity to experimental animals of formulated products.

Reproductive and Developmental Toxicity: No information available

Teratogenicity: No information available

Immunotoxicity: No information available

Neurotoxicity: No information available

Other: No information available

12. ECOLOGICAL INFORMATION

Aquatic Toxicity: No information available

Terrestrial Toxicity: No information available

Chemical Fate and Transport: No information available

Other: No information available

13. DISPOSAL INFORMATION

Regulatory Information: Dispose of residual products and empty containers responsibly. Caution! If regulated solvents are used to clean up spilled material, the resulting waste mixture may be regulated. Department of Transportation (DOT) regulations may apply for transporting this material when spilled. Refer to state and local regulations.

Waste Disposal Methods: Waste material may be landfilled or incinerated at an approved facility. Materials should be recycled if possible.

Other: No information available

14. TRANSPORTATION INFORMATION

U.S. Department of Transportation (DOT)

Highway / Rail (Bulk): Not Regulated Highway / Rail (Non-Bulk): Not Regulated

The DOT description is provided to assist in the proper shipping classification of this product and may not be suitable for all shipping descriptions.

Page 6 of 7

MSDS Number: 592

PENNZOIL® PREMIUM WHEEL BEARING 707L RED GREASE

International Information Vessel: IMDG Regulated: IMDG Not Regulated: X Air: ICAO Regulated: ICAO Not Regulated: X
Other: No information available
15. Regulatory Information
<u>Regulatory Lists Searched</u> : The components listed in Section 2 of this MSDS were compared to substances that appear on the following regulatory lists. Each list is numerically identified. See Regulatory Search Results below.
Health & Safety: 10 - IARC carcinogen, 11 - NTP carcinogen, 12 - OSHA carcinogen, 15 - ACGIH TLV, 16 - OSHA PEL, 17 - NIOSH exposure limit, 20 - US DOT Appendix A, Hazardous substances, 21 - USDOT Appendix B, Marine pollutants, 22 - FDA 21 CFR Total food additives, 23 - NFPA 49 or 325
Environmental: 30 - CAA 1990 Hazardous air pollutants, 31 - CAA Ozone depletors, 33 - CAA HON rule, 34 - CAA Toxic substance for accidental release prevention, 35 - CAA Volatile organic compounds (VOC's) in SOCMI, 41 - CERCLA / SARA Section 302 extremely hazardous substances, 42 - CERCLA / SARA Section 313 emissions reporting, 43 - CWA Hazardous substances, 44 - CWA Priority pollutants, 45 - CWA Toxic pollutants, 46 - EPA Proposed test rule for hazardous air pollutants, 47 - RCRA Basis for listing - Appendix VII, 48 - RCRA waste, 49 - SDWA - (S)MCLs
International: 50 - Canada - WHMIS Classification of substance, 54 - Mexico - Drinking water - ecological criteria, 55 - Mexico - Wastewater discharges, 56 - US -TSCA Section (12)(b) - export notification
State Lists: 60 - CA - Proposition 65, 61 - FL - Substances, 62 - MI - Critical materials, 63 - MA - RTK, 64 - MA - Extraordinarily hazardous substances, 65 - MN - Hazardous substances, 66 - PA - RTK, 67 - NJ - RTK, 68 - NJ - Environmental hazardous substances, 69 - NJ - Special hazardous substances
Inventories: 80 - Canada - Domestic substances , 81 - European - EINECS, 82 - Japan - ENCS, 83 - Korea - Existing and evaluated chemical substances, 84 - US - TSCA
Regulatory Search Results: No components appear on any of the regulatory lists searched.
U.S. TSCA Inventory: All components of this material are on the US TSCA Inventory.
SARA Section 313: This product is not known to contain any SARA, Title III, Section 313 Reportable Chemicals at or greater than 1.0% (0.1% for carcinogens).
IARC: No information available
SARA 311/312 Categories Acute: Chronic: Fire: Pressure: Reactive: Not Regulated:X
Canadian WHMIS Classification Not a controlled substance under WHMIS
European Union Classification Hazard Symbols: No classification recommended Risk Phrases: No classification recommended

PENNZOIL® PREMIUM WHEEL BEARING 707L RED GREASE

MSDS Number: 592

Safety Phrases:No classification recommended

Other: No information available

16. OTHER INFORMATION

Health and Environmental Label Language

CAUTION: Contains Petroleum Oil (Grease). Repeated skin contact can cause skin disorders.

ATTENTION: Repeated exposure to oil mist in excess of the OSHA limit (5mg/m3) can result in accumulation of oil droplets in pulmonary tissue.

PRECAUTIONARY MEASURES: Avoid excessive & prolonged skin contact. Wash thoroughly after handling. Avoid generation and inhalation of oil mists.

INSTRUCTIONS IN CASE OF FIRE OR SPILL: In case of fire, use water spray, foam, dry chemical or carbon dioxide. Water spray may be ineffective, but can be used to cool containers. In case of spill, do not use water, soak up with absorbent material.

MSDS Revisions

Previous Version Date: 4/3/97

Previous Version Information: Revised all sections, new 16 section MSDS format.

Other: No information available

Prepared By:

Pennzoil-Quaker State Company Environmental, Safety, Health, & DOT Compliance P.O. Box 2967 Houston, TX 77252-2967 USA

Disclaimer of Warranty: The information contained herein is based upon data and information available to us, and reflects our best professional judgement. This product may be formulated in part with components purchased from other companies. In many instances, especially when proprietary or trade secret materials are used, Pennzoil-Quaker State Company must rely upon the hazard evaluation of such components submitted by that product's manufacturer or importer. No warranty of merchantability, fitness for any use, or any other warranty is expressed or implied regarding the accuracy of such data or information. The results to be obtained from the use thereof, or that any such use does not infringe any patent. Since the information contained herein may be applied under conditions of use beyond our control and with which we may be unfamiliar, we do not assume responsibility for the results of such application. This information is furnished upon the condition that the person receiving it shall make his own determination of the suitability of the material for his particular use.

Page 7 of 7