



Previous Name: Shell Corena P

Shell Corena S2 P 100

- *Reliable Protection*
- *Standard Life Applications*

Reciprocating (Piston) Air Compressor Oil

Shell Corena S2 P is high quality air compressor oil designed to deliver the lubrication performance for high pressure reciprocating compressors. It is suitable for most reciprocating air compressors running at up to 220°C discharge temperatures at elevated pressures.

DESIGNED TO MEET CHALLENGES

Performance, Features & Benefits

■ Long oil life – Maintenance saving

Shell Corena S2 P allows the interval between valve and piston maintenance to be extended under certain applications.

Compressors can be kept in service for much longer periods, operating at a consistently high level of efficiency.

Extended maintenance capability is supported by resistance to formation of carbon deposits and lacquer on valves and piston crowns at high working temperatures and pressures.

■ Outstanding wear protection

Shell Corena S2 P helps provide effective protection of internal metal surfaces from corrosion and wear to help prolong the life of critical parts such as bearings and pistons.

■ Maintaining system efficiency

Shell Corena S2 P helps prevent the formation of carbon deposits and lacquer on valves and piston crowns at high working temperatures and pressures. These can cause serious damage, lower compressor efficiency and increase maintenance costs. In addition, Shell Corena S2 P has good water separation to help prevent accelerated corrosion, facilitating easy condensate draining.

■ Enhanced air line safety

In discharge air-lines, the combination of rust particles, dispersed in carbonaceous deposits, coupled with heat from recently compressed air, can cause a reaction leading to the possibility of fires and explosion. Shell Corena S2 P helps to minimize the likelihood of this danger.

Main Applications



■ Reciprocating air compressors

Shell Corena S2 P is suitable for use in industrial reciprocating air compressors operating with air discharge temperatures of up to 220°C.

■ Breathing air compressors

Shell Corena S2 P may be used in breathing air compressors, provided subsidiary clean-up apparatus is used to ensure that the air produced is fit for breathing.

Specifications, Approvals & Recommendations

- DIN 51506 VBL
- ISO 6743-3A-L DAA Normal Duty
- For additional questions regarding equipment approvals and recommendations, please consult your local Shell Technical Helpdesk, or the OEM Approvals website.

Compatibility & Miscibility

■ Seal Compatibility

Shell Corena S2 P oils are compatible with all sealing materials commonly used in air compressors.



Typical physical characteristics

Properties			Method	Shell Corena Oils S2 P
ISO Viscosity Grade			ISO 3448	100
Kinematic Viscosity	@40°C	mm ² /s	ASTM D 445	100
Kinematic Viscosity	@100°C	mm ² /s	ASTM D 445	9.2
density	@15°C	kg/m ³	ASTM D 1298	899
Flash Point			°C	ASTM D 92 (COC)
Pour Point			°C	ASTM D 97
Neutralization Value			mg KOH/g	ASTM D 974
Sulfated Ash			% m	DIN 51575
Rust Prevention - Synthetic Sea Water			degree	ASTM D 665B
Water Separability	@54°C	min	ASTM D 1401	-
Water Spherability	@82°C	min	ASTM D 1401	20

- These Characteristics are typical of current production. While future production will conform to Shell's specification, variations in These Characteristics may occur.

Health, Safety & Environment

Health and Safety

Shell Corena S2 P is unlikely to present any significant health or safety hazard when properly used in the recommended Application and good standards of personal hygiene are maintained.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water.

Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet, which can be obtained from <http://www.epc.shell.com/>

Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

Additional Information

Advice

Product recommendations for applications not covered here may be obtained from your Shell representative.

Viscosity - Temperature Diagram for Shell Corena S2 P

