

Safety Data Sheet



Stock Number: 3063020
Revision Date: 07-07-2021
Replaces: 09-09-2020

TECTYL® 185GW BLACK 3.4

1. Identification

Product identifier used on the label: TECTYL® 185GW BLACK 3.4
Stock Number: 3063020

Other means of identification:
Synonyms: None
Chemical family: Mixture

Recommended use of the chemical and restrictions on use:
Recommended use: Corrosion Preventative Compound
Restrictions on use: Uses other than those described above

Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party: Daubert Chemical Company
4700 S. Central Avenue
Chicago, IL 60638

Telephone number: 1-708-496-7350
E-mail address: SDS@Daubert.com
Emergency phone number: Chemtrec: 1-800-424-9300 (International)

2. Hazard(s) identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200:

GHS Hazard Symbols:



GHS Classification: Skin Corrosion/Irritation Category 2; Flammable Liquid Category 3; Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category 3

Signal Word: Warning

Hazard Statements: Flammable liquid and vapor
Causes skin irritation
May cause drowsiness or dizziness

Unclassified Hazards (HNOC): None Identified

Precautionary Statements:
Prevention: Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting equipment.
Use only non-sparking tools.

Safety Data Sheet

Product identifier used on the label: TECTYL® 185GW BLACK 3.4

Stock Number: 3063020

Revision Date: 07-07-2021

Replaces: 09-09-2020

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/ vapors/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

Response:

If on skin: Wash with plenty of water.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If inhaled: Remove person to fresh air and keep comfortable for breathing.

Call a poison center/doctor if you feel unwell.

Specific treatment: see Section 4 on this SDS.

If skin irritation occurs: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

In case of fire: Use appropriate media to extinguish.

Storage:

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Disposal:

Dispose of contents/container to a suitable disposal site in accordance with local/national/international regulations.

Hazards not otherwise classified:

Carbon black, when present in paint, grease or a liquid coating is not known to present a carcinogen hazard as it is bound within a matrix. Risks associated with this chemical is attributable to dust (inhalation) exposures, and not to exposures from formulated products, like paint, grease, or a liquid coating, where the dust is embedded in the mixture and not available for exposure. Particles released from sanding and sawing mixtures, including paints, lacquers, and epoxy solids containing carbon black, have been characterized. Pure chemical particles are not released during these uses, but rather the particles remain embedded in the coating matrices.

Safety Data Sheet

Product identifier used on the label: TECTYL® 185GW BLACK 3.4

Stock Number: 3063020

Revision Date: 07-07-2021

Replaces: 09-09-2020

3. Composition/information on ingredients

Chemical Name	Common name and synonyms	CAS #	%
Distillates (petroleum), hydrotreated light	None	64742-47-8	30 - 60
Carbon black	None	1333-86-4	0.5 - 1.5

Specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

4. First-aid measures

Description of necessary measures, subdivided according to the different routes of exposure, i.e., inhalation, skin and eye contact, and ingestion:

Inhalation:	If symptoms are experienced remove source of contamination or move victim to fresh air and obtain medical advice.
Eye Contact:	Flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention.
Skin Contact:	Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists.
Ingestion:	Do not induce vomiting and seek medical attention immediately. Provide medical care provider with this SDS. If vomiting occurs, lean victim forward to reduce risk of aspiration into lungs.
Most important symptoms/effects, acute and delayed:	Causes skin irritation. May cause drowsiness or dizziness
Indication of immediate medical attention and special treatment needed, if necessary:	Consult a physician. Treat symptomatically.

5. Fire-fighting measures

Suitable (and unsuitable) extinguishing media:

Suitable extinguishing media:	Use alcohol resistant foam, carbon dioxide, dry chemical, or water spray when fighting fires. Water or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the fire.
Unsuitable extinguishing media:	Do not use water jet as an extinguisher, as this will spread the fire.

Safety Data Sheet

Product identifier used on the label: TECTYL® 185GW BLACK 3.4

Stock Number: 3063020

Revision Date: 07-07-2021

Replaces: 09-09-2020

Specific hazards arising from the chemical:

Vapors may be ignited by sparks, flames or other sources of ignition if material is above the flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition and flash back. Empty containers that retain product residue (liquid, solid/sludge, or vapor) can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition. Any of these actions can potentially cause an explosion that may lead to injury or death.

Hazardous combustion products:

Carbon dioxide, Carbon monoxide, Sulfur compounds, Hydrocarbons

Special protective equipment and precautions for fire-fighters:

Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Use appropriate methods for the surrounding fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section 8 of this SDS. Additional precautions may be necessary based on special circumstances created by the spill including the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill.

Methods and materials for containment and cleaning up:

Absorb or cover with dry earth, sand or other non-combustible material and transfer to appropriate waste containers. Use clean, non-sparking tools to collect absorbed material. Collect and discard in accordance with local, state and national regulations.

7. Handling and storage

Precautions for safe handling:

Avoid contacting and avoid breathing the material. Use only in a well-ventilated area. Use with adequate ventilation "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. Ground and bond containers when transferring material. Do not get in eyes, on skin and clothing. Wash thoroughly after handling. As with all chemicals, good industrial hygiene practices should be followed when handling this material.

Safety Data Sheet

Product identifier used on the label: TECTYL® 185GW BLACK 3.4

Stock Number: 3063020

Revision Date: 07-07-2021

Replaces: 09-09-2020

Conditions for safe storage, including any incompatibilities:

Safe storage conditions:

Store in a cool dry place. Isolate from incompatible materials. Do not store in direct sunlight. Keep away from heat, sparks, and flame. Keep container closed when not in use.

Materials to Avoid/Chemical Incompatibility:

Strong oxidizing agents

8. Exposure controls/personal protection

OSHA permissible exposure limit (PEL), American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Value (TLV), and any other exposure limit used or recommended by the chemical manufacturer, importer, or employer preparing the safety data sheet, where available:

Chemical component	OSHA PEL	ACGIH TLV	ACGIH STEL	IDLH
Distillates (petroleum), hydrotreated light		200 mg/m ³		No data available
Carbon black	3.5 mg/m ³ (inhalable)	3.5 mg/m ³ (inhalable)		No data available

Appropriate engineering controls:

Local exhaust ventilation or other engineering controls are normally required when handling or using this product to avoid overexposure.

Engineering controls must be designed to meet the OSHA chemical specific standard in 29 CFR 1910.

Individual protection measures, such as personal protective equipment:

Respiratory Protection:

Proper ventilation (at a minimum) will be required when handling this product. Use respirators (NIOSH approved) only if ventilation cannot be used to eliminate symptoms or reduce the exposure to below acceptable levels.

Respirator Type(s):

NIOSH approved air purifying respirator with organic vapor cartridge.

Eye protection:

Wear chemically resistant safety glasses with side shields when handling this product. Do not wear contact lenses.

Skin protection:

Wear protective gloves. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work.

Gloves:

Chemically resistant gloves

Other protective equipment:

Wear chemically resistant safety glasses with side shields when handling this product. Do not wear contact lenses.

Safety Data Sheet

Product identifier used on the label: TECTYL® 185GW BLACK 3.4

Stock Number: 3063020

Revision Date: 07-07-2021

Replaces: 09-09-2020

Wear protective gloves. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work.

General hygiene conditions:

Do not use pressure to empty container. Remove contaminated clothing and wash before reuse. Use spark-proof tools and explosion-proof equipment. Use with adequate ventilation "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. Ground and bond containers when transferring material. Do not get in eyes, on skin and clothing. Wash thoroughly after handling. As with all chemicals, good industrial hygiene practices should be followed when handling this material.

9. Physical and chemical properties

Appearance (physical state, color etc.):

Physical state: Liquid

Color: Black

Odor: Solvent Odor

Slight

Odor Threshold: No data available

pH: No data available

Melting point/freezing point (°C):

Melting Point (°C): No data available

Freezing point (°C): No data available

Initial boiling point and boiling range (°C): No data available

Flash Point: ≥ 105 °F (41 °C)

Evaporation Rate: No data available

Flammability (solid, gas): No data available

Upper/lower flammability or explosive limits:

Upper flammability or explosive limits: No data available

Lower flammability or explosive limits: No data available

Vapor pressure: 2 mmHg @ 20°C

Vapor density: >1 (Air=1)

Relative density: 0.97

Solubility(ies): Negligible; 0-1%

Partition coefficient: n-octanol/water: No data available

Safety Data Sheet

Product identifier used on the label: TECTYL® 185GW BLACK 3.4

Stock Number: 3063020

Revision Date: 07-07-2021

Replaces: 09-09-2020

Auto-ignition temperature (°C):	No data available
Decomposition Temperature (°C):	No data available
Viscosity:	12000 cP
Volatiles, % by weight:	40.39
VOC, Material, lb/gal	3.19
VOC, Material, grams/liter	382
VOC minus exempt solvents & water, g/L	386

10. Stability and reactivity

Reactivity:	Not expected to be reactive
Chemical stability:	Hazardous polymerization will not occur.
Possibility of hazardous reactions:	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid (e.g., static discharge, shock, or vibration):	Temperatures above flash point in combination with sparks, open flames, or other sources of ignition. High temperatures. Elevated temperatures. Contamination.
Incompatible materials:	Strong oxidizing agents
Hazardous decomposition products:	Under normal conditions of use & storage, decomposition and hazardous decomposition products are unlikely.

11. Toxicological information

Description of the various toxicological (health) effects and the available data used to identify those effects:

Information on the likely routes of exposure (inhalation, ingestion, skin and eye contact): Eye contact, Skin contact, Inhalation

Symptoms related to the physical, chemical and toxicological characteristics: Causes skin irritation. . May cause drowsiness or dizziness

Delayed and immediate effects and also chronic effects from short- and long-term exposure:

Ingestion Toxicity: Harmful if swallowed. Estimated to be > 5.0 g/kg; practically non-toxic

Skin Contact: Can cause moderate skin irritation, defatting, and dermatitis. Not likely to cause permanent damage.

Inhalation Toxicity: No data available

Eye Contact: Can cause moderate irritation, tearing and reddening, but not likely to permanently injure eye tissue.

Safety Data Sheet

Product identifier used on the label: TECTYL® 185GW BLACK 3.4

Stock Number: 3063020

Revision Date: 07-07-2021

Replaces: 09-09-2020

Sensitization:	None known
Mutagenicity:	No data
Reproductive and Developmental Toxicity:	No data available
Carcinogenicity:	Carbon black has been classified by IARC as a Category 2B (known animal carcinogen, possible human carcinogen) material. This was based on the results of rat inhalation studies of carbon black, despite the lack of parallel evidence on humans or other animal species. Carbon Black in a coating product, either in wet or dry form, is encapsulated and unlikely to be present in small enough particles to present an inhalation risk. Normal precautions should be taken if the dry coating is to be severely abraded by sanding or sandblasting.
STOT-single exposure:	Classification has been based on toxicological information of the components in Section 3.
STOT-repeated exposure:	Based on available data, the classification criteria are not met.
Aspiration hazard:	Based on available data, the classification criteria are not met.

Numerical measures of toxicity (such as acute toxicity estimates):

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Distillates (petroleum), hydrotreated light			Inhalation LC50 (4h) Rat > 20 mg/L
Carbon black	Oral LD50 Rat > 8000 mg/kg		

Is the hazardous chemical listed in the National Toxicology Program (NTP) Report on Carcinogens (latest edition) or has it been found to be a potential carcinogen in the International Agency for Research on Cancer (IARC) Monographs (latest edition), or by OSHA?:

Chemical Name	OSHA Carcinogen	IARC Carcinogen	NTP Carcinogen
Carbon black	N	Y	N

12. Ecological information

Ecotoxicity (aquatic and terrestrial, where available): No data available

Ecological Toxicity Data:

Chemical Name	CAS #	Aquatic EC50 Crustacea	Aquatic ERC50 Algae	Aquatic LC50 Fish
Carbon black	1333-86-4	EC50(24HR) WATER FLEA > 5600 mg/L	EC50(72HR) ALGAE > 10000 mg/L	LC50(96 HR) ZEBRA FISH > 1000 mg/L

Safety Data Sheet

Product identifier used on the label: TECTYL® 185GW BLACK 3.4

Stock Number: 3063020

Revision Date: 07-07-2021

Replaces: 09-09-2020

Persistence and degradability:	No data
Bioaccumulative potential:	No data available
Mobility in soil:	No data available
Other adverse effects (such as hazardous to the ozone layer):	No data available

13. Disposal considerations

Description of waste residues and information on their safe handling and methods of disposal, including the disposal of any contaminated packaging:	Spent or discarded material may be a hazardous waste. Dispose of by incineration following Federal, State, Local, or Provincial regulations.
Waste codes / waste designations:	D001

14. Transport information

Domestic Ground in containers <= 119 GL	Corrosion preventive/Non-Regulated
Domestic Ground in containers > 119 GL	UN1268, PETROLEUM DISTILLATES, N.O.S., (Naphtha Solvent), Combustible liquid, PG III
Shipping name for Export, Air (IATA)	UN1268, PETROLEUM DISTILLATES, N.O.S., (Naphtha Solvent),3, PG III
Shipping name for Export, Sea (IMDG)	UN1268, PETROLEUM DISTILLATES, N.O.S., (Naphtha Solvent),3, PG III
Marine Pollutant?	No

15. Regulatory information

International Inventory

Country(s) or region		On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)/Non-Domestic Substances List (NDSL)	Yes

Safety Data Sheet

Product identifier used on the label: TECTYL® 185GW BLACK 3.4

Stock Number: 3063020

Revision Date: 07-07-2021

Replaces: 09-09-2020

China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippines Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Inventory	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or are unknown from listing on the inventory administered by the governing country(s).

Chemical Name	CAS #	Regulation	Percent
Carbon black	1333-86-4	Prop. 65 - Cancer	0.5 - 1.5
Naphthalene	91-20-3	Prop. 65 - Cancer	TRACE
Cumene	98-82-8	Prop. 65 - Cancer	TRACE
Benzene	71-43-2	Prop. 65 - Cancer	TRACE
Ethylbenzene	100-41-4	Prop. 65 - Cancer	TRACE
Toluene	108-88-3	Prop. 65 - Developmental and/or Reproductive	TRACE

Safety Data Sheet

Product identifier used on the label: TECTYL® 185GW BLACK 3.4

Stock Number: 3063020

Revision Date: 07-07-2021

Replaces: 09-09-2020

Benzene	71-43-2	Prop. 65 - Developmental and/or Reproductive	TRACE
Toluene	108-88-3	CERCLA	TRACE RQ = 1000 lbs
Naphthalene	91-20-3	CERCLA	TRACE RQ = 100 lbs.
Cumene	98-82-8	CERCLA	TRACE RQ = 5000 lbs.
Benzene	71-43-2	CERCLA	TRACE RQ = 10 lbs.
Ethylbenzene	100-41-4	CERCLA	TRACE RQ = 1000 lbs.
Toluene	108-88-3	SARA 313	TRACE
Naphthalene	91-20-3	SARA 313	TRACE
Cumene	98-82-8	SARA 313	TRACE
Benzene	71-43-2	SARA 313	TRACE
Ethylbenzene	100-41-4	SARA 313	TRACE
No SARA 302 EHS-listed chemicals in this product.		SARA EHS	

Safety Data Sheet

Product identifier used on the label: TECTYL® 185GW BLACK 3.4

Stock Number: 3063020

Revision Date: 07-07-2021

Replaces: 09-09-2020

16. Other information, including date of preparation or last revision.

SDS Prepared by: DAUBERT\HALINSKI

Revision Date: 07-07-2021

Revision Number: 25

Reason for revision: Reviewed
Approved: M. Longo

Disclaimer: Although the information contained herein is believed to be reliable, it is furnished without warranty of any kind. This information is not intended to be all-inclusive as to the manner and conditions of use, handling, and storage.