

**Stock Number:** 3202120 **Revision Date:** 09-19-2023 **Replaces:** 06-30-2021

#### TECTYL® 8140

#### 1. Identification

Product identifier used on the label: TECTYL® 8140
Stock Number: 3202120

Other means of identification:

Synonyms: None Chemical family: Mixture

Recommended use of the chemical and restrictions on use:

**Recommended use:** Corrosion Preventative Coating

**Restrictions on use:** Uses other than those described above

Name, address, and telephone number

of the chemical manufacturer,

Daubert Chemical Company

importer, or other responsible party:

4700 S. Central Avenue

Chicago, IL 60638

**Telephone number:** 1-708-496-7350 **E-mail address:** SDS@Daubert.com

Emergency phone number: Chemtrec: (800) 424-9300 - in USA and Canada

+1-703-527-3887 - outside USA and Canada

#### 2. Hazard(s) identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200:

GHS Hazard Symbols:





GHS Classification: Flammable Liquid Category 3; Specific Target Organ Systemic Toxicity

(STOT) - Single Exposure Category 3; Hazardous to the aquatic

environment - Acute Category 3

Signal Word: Warning

Hazard Statements: Flammable liquid and vapor

May cause respiratory irritation

Harmful to aquatic life

Unclassified Hazards (HNOC): None Identified

**Precautionary Statements:** 

**Prevention:** Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting equipment.

Product identifier used on the label: TECTYL® 8140

**Stock Number:** 3202120 **Revision Date:** 09-19-2023 **Replaces:** 06-30-2021

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/ vapors/spray.

Use only outdoors or in a well-ventilated area.

Avoid release to the environment.

Wear protective gloves/protective clothing/eye protection/face

protection.

**Response:** If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower.

If inhaled: Remove person to fresh air and keep comfortable for

breathing.

Call a poison center/doctor if you feel unwell.

In case of fire: Use appropriate media to extinguish.

**Storage:** Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

**Disposal:** Dispose of contents/container to a suitable disposal site in accordance

with local/national/international regulations.

Hazards not otherwise classified: Crystalline silica, when present in paint, grease, or a liquid coating, is not

known to present a carcinogen hazard as it is bound within a matrix. Risks associated with this chemical is attributable to dust (inhalation) exposures, and not to exposures from formulated products, like paint, grease, or a liquid coating, where the dust is embedded in the mixture and not available for exposure. Particles released from sanding and sawing mixtures, including paints, lacquers, and epoxy solids containing crystalline silica, have been characterized. Pure chemical particles are not released during these uses, but rather the particles remain embedded in

the coating matrices.

#### 3. Composition/information on ingredients

Chemical Name	Common name and synonyms	CAS#	%
Distillates (petroleum), hydrotreated light	None	64742-47-8	30 - 60
n-Nonane	None	111-84-2	1-5
Crystalline Silica (Quartz)	None	14808-60-7	0.1 - 1

Specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

Product identifier used on the label: TECTYL® 8140

**Stock Number:** 3202120 **Revision Date:** 09-19-2023 **Replaces:** 06-30-2021

#### 4. First-aid measures

Description of necessary measures, subdivided according to the different routes of exposure, i.e., inhalation, skin and eye contact, and ingestion:

**Inhalation:** If symptoms are experienced remove source of contamination or move

victim to fresh air and obtain medical advice.

**Eye Contact:** Flush eyes with plenty of water for at least 20 minutes retracting eyelids

often. Tilt the head to prevent chemical from transferring to the

uncontaminated eye. Get immediate medical attention.

**Skin Contact:** Wash with soap and water. Get medical attention if irritation develops or

persists.

**Ingestion:** Do not induce vomiting and seek medical attention immediately. Provide

medical care provider with this SDS.

Most important symptoms/effects,

acute and delayed:

May cause respiratory irritation

Indication of immediate medical attention and special treatment

needed, if necessary:

Consult a physician. Treat symptomatically.

#### 5. Fire-fighting measures

Suitable (and unsuitable) extinguishing media:

Suitable extinguishing media: Use alcohol resistant foam, carbon dioxide, dry chemical, or water spray

when fighting fires. Water or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully applied to the

fire.

**Unsuitable extinguishing media:** Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the

chemical:

Vapors may be ignited by sparks, flames or other sources of ignition if material is above the flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition and flash back. Empty containers that retain product residue (liquid, solid/sludge, or vapor) can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or

other sources of ignition. Any of these actions can potentially cause an explosion that may lead to injury or death.

Hazardous combustion products: Carbon dioxide, Carbon monoxide

Product identifier used on the label: TECTYL® 8140

**Stock Number:** 3202120 **Revision Date:** 09-19-2023 **Replaces:** 06-30-2021

Special protective equipment and precautions for fire-fighters:

Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products.

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:

Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section 8 of this SDS. Additional precautions may be necessary based on special circumstances created by the spill including; the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill.

Methods and materials for containment and cleaning up:

Prevent the spread of any spill to minimize harm to the environment. Keep out of sewage systems and any water course. Absorb spill with liquid-binding material (sand, sawdust, etc.). Collect and discard in accordance with local, state and national regulations. Absorb or cover with dry earth, sand or other non-combustible material and transfer to appropriate waste containers. Use clean, non-sparking tools to collect absorbed material. Collect and discard in accordance with local, state and national regulations.

#### 7. Handling and storage

Precautions for safe handling:

Avoid contacting and avoid breathing the material. Use only in a well-ventilated area. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. Do not get in eyes, on skin and clothing. Wash thoroughly after handling. As with all chemicals, good industrial hygiene practices should be followed when handling this material.

Conditions for safe storage, including any incompatibilities:

Safe storage conditions:

Store in a cool dry place. Isolate from incompatible materials. Keep away from heat, sparks, and flame. Keep container closed when not in use.

Materials to Avoid/Chemical Incompatibility:

Strong oxidizing agents, Metals

Product identifier used on the label: TECTYL® 8140

**Stock Number:** 3202120 **Revision Date:** 09-19-2023 **Replaces:** 06-30-2021

#### 8. Exposure controls/personal protection

OSHA permissible exposure limit (PEL), American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Value (TLV), and any other exposure limit used or recommended by the chemical manufacturer, importer, or employer preparing the safety data sheet, where available:

Chemical component	OSHA PEL	ACGIH TLV	ACGIH STEL	IDLH
Distillates (petroleum), hydrotreated light		200 mg/m3		No data available
n-Nonane		200 ppm		No data available
Crystalline Silica (Quartz)	0.05 mg/m3 (respirable dust)	0.025 mg/m3 (respirable dust)		No data available

**Appropriate engineering controls:** Local exhaust ventilation or other engineering controls are normally

required when handling or using this product to avoid overexposure.

Engineering controls must be designed to meet the OSHA chemical

specific standard in 29 CFR 1910.

Individual protection measures, such as personal protective equipment:

**Respiratory Protection:** Proper ventilation (at a minimum) will be required when handling this

product. Use respirators (NIOSH approved) only if ventilation cannot be used to eliminate symptoms or reduce the exposure to below acceptable

levels.

**Respirator Type(s):** NIOSH approved air purifying respirator with organic vapor cartridge.

**Eye protection:** Wear chemically resistant safety glasses with side shields when handling

this product. Do not wear contact lenses.

**Skin protection:** Wear protective gloves. Inspect gloves for chemical break-through and

replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating,

drinking, and when leaving work.

**Gloves:** Chemically resistant gloves

Other protective equipment: Wear chemically resistant safety glasses with side shields when handling

this product. Do not wear contact lenses.

Wear protective gloves. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating,

drinking, and when leaving work.

Product identifier used on the label: TECTYL® 8140

**Stock Number:** 3202120 **Revision Date:** 09-19-2023 **Replaces:** 06-30-2021

**General hygiene conditions:** Ground and bond containers when transferring material. Use spark-

proof tools and explosion-proof equipment. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. Do not get in eyes, on skin and clothing. Wash thoroughly after handling. As with all chemicals, good industrial hygiene practices should be followed when

handling this material.

#### 9. Physical and chemical properties

Appearance (physical state, color etc.):

Physical state: Viscous Liquid

Color: Black

**Odor:** Solvent Odor

Odor Threshold: No data available pH: No data available

Melting point/freezing point (°C):

Melting Point (°C):

Freezing point (°C):

No data available

Flash Point:

Flash Point:

Flammability (solid, gas):

No data available

No data available

Upper/lower flammability or explosive

limits:

Upper flammability or explosive limits: No data available
Lower flammability or explosive limits: No data available
Vapor pressure: 0.62 mmHg @ 20°C
Vapor density: No data available

Relative density: 0.96

Solubility(ies): Insoluble Negligible; 0-1%

Partition coefficient: n-octanol/water:

Auto-ignition temperature (°C):

No data available

Decomposition Temperature (°C):

No data available

Viscosity: 28000 cP

Volatiles, % by weight: 36
VOC, Material, lb/gal 2.82

Product identifier used on the label: TECTYL® 8140

**Stock Number:** 3202120 **Revision Date:** 09-19-2023 **Replaces:** 06-30-2021

VOC, Material, grams/liter 337.65

VOC minus exempt solvents & water, g/L 340.04

10. Stability and reactivity

**Reactivity:** Not expected to be reactive

**Chemical stability:** Stable under normal conditions.

**Possibility of hazardous reactions:** Under normal conditions of storage and use, hazardous reactions will not

occur.

Conditions to avoid (e.g., static

discharge, shock, or vibration):

Temperatures above flash point in combination with sparks, open flames,

or other sources of ignition. Elevated temperatures. Contamination.

**Incompatible materials:** Strong oxidizing agents, Metals

Hazardous decomposition products: Under normal conditions of use & storage, decomposition and hazardous

decomposition products are unlikely.

11. Toxicological information

Description of the various toxicological (health) effects and the available data used to identify those effects:

Information on the likely routes of exposure (inhalation, ingestion, skin

and eye contact):

Eye contact, Skin contact, Inhalation

Symptoms related to the physical,

chemical and toxicological

characteristics:

May cause respiratory irritation

Delayed and immediate effects and also chronic effects from short- and long-term exposure:

**Ingestion Toxicity:** Harmful if swallowed.

**Skin Contact:** Can cause minor skin irritation, defatting, and dermatitis.

**Inhalation Toxicity:** May cause respiratory irritation

**Eye Contact:** Can cause moderate irritation, tearing and reddening, but not likely to

permanently injure eye tissue.

**Sensitization:** None known

Mutagenicity: No data

**Reproductive and Developmental** 

No data available

**Toxicity:** 

Product identifier used on the label: TECTYL® 8140

**Stock Number:** 3202120 **Revision Date:** 09-19-2023 **Replaces:** 06-30-2021

**Carcinogenicity:** Crystalline Silica: This product contains mined materials which generally

contain small amounts of crystalline silica (CAS# 14808-60-7, quartz sand) above 0.1% as a naturally occurring impurity. IARC Monograhs on the evaluations of the carcinogenic Risk of Chemicals to Humans (Volume 42, 1987) concludes that there is "limited evidence" of the carcinogenicity of crystalline silica to humans. IARC classification 2A. Crystalline silica in a coating product, either in wet or dry form, is encapsulated and unlikely to be present in small enough particles to present an inhalation risk. Normal dust precautions should be taken if the dry coating is to be severely

abraded by sanding or sandblasting.

STOT-single exposure: Classification has been based on toxicological information of the

components in Section 3.

**STOT-repeated exposure:** Based on available data, the classification criteria are not met.

**Aspiration hazard:** Based on available data, the classification criteria are not met.

Numerical measures of toxicity (such as acute toxicity estimates):

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Distillates (petroleum), hydrotreated light			Inhalation LC50 (4h) Rat > 20 mg/L
n-Nonane	Oral LD50 Rat > 5000 mg/kg		

Is the hazardous chemical listed in the National Toxicology Program (NTP) Report on Carcinogens (latest edition) or has it been found to be a potential carcinogen in the International Agency for Research on Cancer (IARC) Monographs (latest edition), or by OSHA?:

Chemical Name	OSHA Carcinogen	IARC Carcinogen	NTP Carcinogen
Quartz	N	Υ	Ν

#### 12. Ecological information

Ecotoxicity (aquatic and terrestrial,

No data available

where available):

**Ecological Toxicity Data:** 

Chemical Name	CAS #	Aquatic EC50	Aquatic ERC50	Aquatic LC50 Fish
		Crustacea	Algae	
n-Nonane	111-84-2	EC50(48 HR)	No data available	No data available
		WATER FLEA 0.2		
		mg/L		

Product identifier used on the label: TECTYL® 8140

Stock Number: 3202120 **Revision Date:** 09-19-2023 Replaces: 06-30-2021

Persistence and degradability:

No data

**Bioaccumulative potential:** 

No data available

Mobility in soil:

No data available

Other adverse effects (such as

hazardous to the ozone layer):

No data available

#### 13. Disposal considerations

Description of waste residues and information on their safe handling and methods of disposal, including the disposal of any contaminated

Spent or discarded material may be a hazardous waste.

Dispose of by incineration following Federal, State, Local, or Provincial

regulations.

packaging:

Waste codes / waste designations: D001

#### 14. Transport information

Domestic Ground in containers <= 119 GL	Corrosion preventive/Non-Regulated
Domestic Ground in containers > 119 GL	UN1268, PETROLEUM DISTILLATES, N.O.S., (Naphtha Solvent), Combustible liquid, PG III
Shipping name for Export, Air (IATA)	UN1268, PETROLEUM DISTILLATES, N.O.S., (Naphtha Solvent),3, PG III
Shipping name for Export, Sea (IMDG)	UN1268, PETROLEUM DISTILLATES, N.O.S., (Naphtha Solvent),3, PG III
Marine Pollutant?	No

Product identifier used on the label: TECTYL® 8140 Stock Number: 3202120 Revision Date: 09-19-2023

Replaces: 06-30-2021

#### 15. Regulatory information

#### **International Inventory**

Country(s) or region		On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	Yes
Philippines	Philippines Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Inventory	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or are unknown from listing on the inventory administered by the governing country(s).

Chemical Name	CAS#	Regulation	Percent
Palygorskite fibers (> 5mm in length)	12174-11-7	Prop. 65 - Cancer	7 - 13
Crystalline silica	14808-60-7	Prop. 65 - Cancer	0.1 - 1

Product identifier used on the label: TECTYL® 8140

Stock Number: 3202120 Revision Date: 09-19-2023 Replaces: 06-30-2021

Benzo[j]fluoranthene	205-82-3	Prop. 65 - Cancer	TRACE
Naphthalene	91-20-3	Prop. 65 - Cancer	TRACE
Cumene	98-82-8	Prop. 65 - Cancer	TRACE
Benzene	71-43-2	Prop. 65 - Cancer	TRACE
Ethylbenzene	100-41-4	Prop. 65 - Cancer	TRACE
Toluene	108-88-3	Prop. 65 - Developmental and/or Reproductive	TRACE
Benzene	71-43-2	Prop. 65 - Developmental and/or Reproductive	TRACE
Toluene	108-88-3	CERCLA	TRACE
			RQ = 1000 lbs
Naphthalene	91-20-3	CERCLA	TRACE
			RQ = 100 lbs.
Cumene	98-82-8	CERCLA	TRACE
			RQ = 5000 lbs.
Benzene	71-43-2	CERCLA	TRACE
			RQ = 10 lbs.
Ethylbenzene	100-41-4	CERCLA	TRACE
			RQ = 1000 lbs.
Toluene	108-88-3	SARA 313	TRACE
Benz(j)fluoranthene	205-82-3	SARA 313	TRACE
Naphthalene	91-20-3	SARA 313	TRACE
Cumene	98-82-8	SARA 313	TRACE

Product identifier used on the label: TECTYL® 8140

Stock Number: 3202120 Revision Date: 09-19-2023 Replaces: 06-30-2021

**Benzene** 71-43-2 SARA 313 TRACE

Ethylbenzene 100-41-4 SARA 313 TRACE

No SARA 302 EHS-listed chemicals SARA EHS

in this product.

#### 16. Other information, including date of preparation or last revision.

SDS Prepared by: DAUBERT\HALINSKI

Revision Date: 09-19-2023

Revision Number: 24

Reason for revision: Reviewed

Approved: K. Slegel

**Disclaimer:** Although the information contained herein is believed to be reliable, it is

furnished without warranty of any kind. This information is not intended to be all-inclusive as to the manner and conditions of use, handling, and

storage.