

TERRA MULTI-TRAC THF



GENERAL DESCRIPTION

TERRA MULTI-TRAC THF is an environmentally responsible, biodegradable universal lubricant for farm equipment, off-highway machinery, and industrial tractors. This multifunctional, bio-based fluid is designed for equipment requiring one lubricant for the transmission, final drive, wet brakes and hydraulic systems. It meets or exceeds the performance requirements of all major brands of farm tractors and other farm equipment that utilize a common fluid reservoir. TERRA MULTI-TRAC THF is formulated with special friction modifiers to ensure proper operation of wet brakes and transmission clutch packs. The vegetable based formulation provides superior oxidation resistance, excellent wear protection, protects against rust and corrosion, and has exceptional anti-foam characteristics. TERRA MULTI-TRAC THF is classified as ultimately biodegradable (Pw1) and non-toxic, It is ideal for equipment operating in environmentally sensitive areas.

APPLICATION

TERRA MULTI-TRAC THF meets or exceeds the requirements for ATD Allison C-4, Caterpillar TO-2 and is recommended for use where the equipment manufacturer specifies the following:

CASE INTERNATIONAL JIC-145/MS-1210, JIC-185/MS-1204MS-1205, MS-1127, MS1129-A, M1135, M1141
DEUTZ-ALLIS
FIAT-HESSTON
FORD M2C134-DM2C86-C, M2C86-B, M2C41-B, M2C48-B, M2C53-A, M2C134-A, M2C134-B, M2C134-C
JOHN DEERE J20C, J14AQuatrol, J20DHygard
KUBOTA
LANDINI
MASSEY-FERGUSON MS-1205, MS-1127, MS1129-A, M1135, M1141
STEIGER
VERSATILE
WHITE FARM Q-1826, Q-1705, Q-1766, Q-1802

PRODUCT DATA SHEET

August 22, 2012

375 Stewart Road, Hanover Twp., PA 18706 | P: (570)822-1151 | F: (570)823-1910



Petroleum Service Company
375 Stewart Road, Hanover Twp., PA 18706
Phone: (570)822-1151 - Fax: (570)823-1910

August 22, 2012

375 Stewart Road, Hanover Twp., PA 18706 | P: (570)822-1151 | F: (570)823-1910

PRODUCT DATA SHEET

NOTE: The information in this publication is the result of careful testing in our laboratories, complemented by selected literature. It does not in any way constitute a guarantee, nor widely varying conditions of product use, which are beyond our control, it is strongly recommended that the product be tested for suit ability. Product typical this publication are current as of November 24, 2010.

Physical Properties

ENVIROMENTALLY FRIENDLY LUBRICANT

TERRA MULTI-TRAC THF

ENVIROMENTALLY FRIENDLY LUBRICANT

TERRA MULTI-TRAC THF

Viscosity @40°C, cSt @100°C, cSt	47.8 10.26
Brookfield Viscosity @-20°C @-35°C	1650 11,150
Viscosity Index	210
Flash Point, °F, (°C)	484 (251)
Stable Pour Point, °F, (°C)	-38 (-39)
Biodegradation Classification, ASTM D 5864	ultimate PW1