

LINCOLN

®

MODEL 1340 LEVER ACTION BARREL PUMP

**Extended pump body
improves top-of-barrel
clearance while providing
excellent flow per stroke**

- **Pumps non-corrosive automotive, agricultural and industrial fluids ***
- **Extended pump body for improved top-of-barrel clearance and excellent flow (14.0 fl oz. minimum per stroke)**
- **Removable non-drip spout allows for threaded hose connection**
- **Telescoping pick-up tube for 16- to 55-gallon drums**
- **Three-tier threaded bung fits standard 2" and 1.5" drums and plastic drums utilizing 56 x 4 mm buttress threads**

*** Not suitable for gasoline**



LINCOLN
®

Lincoln Industrial Corp.
One Lincoln Way
St. Louis, MO 63120-1578

Phone 314.679.4200
Fax 314.679.4359
www.lincolnindustrial.com

Form 444032 (2/08)
© Copyright 2008
Printed in U.S.A.

LINCOLN

®

MODEL 1162 FULLY AUTOMATIC PNEUMATIC GREASE GUN

The variable speed trigger provides excellent grease flow control while the advanced pump design eliminates traditional priming issues

- **Outstanding durability and dependability**
- **Fully automatic, continuous operation**
- **Variable-speed trigger**
- **Accessible check valve assembly**
- **Comfortable grip**
- **30" high-pressure hose with coupler and attachment clip**
- **Includes a combination filler nipple and bleeder valve**
- **Superior flow performance obtained through advanced design**



Pump Ratio:	40:1 at 150 psi
Max. Grease Pressure:	6,000 psi (414 bar)
Air Pressure Range:	40 - 150 psi (2.8 - 10.3 bar)
Weight:	5.375 lbs. (2.4 kg)

LINCOLN
®

Lincoln Industrial Corp.
One Lincoln Way
St. Louis, MO 63120-1578

Phone 314.679.4200
Fax 314.679.4359
www.lincolnindustrial.com

Form 444032 (2/08)
© Copyright 2008
Printed in U.S.A.