

CHEMCOAT, INC.

"Consistent Coatings . . . Superior Service"

P.O. BOX 188
MONTROUSEVILLE, PA 17754-0188

PH: (570) 368-8631 • FAX: (570) 368-8635

PRODUCT DATA SHEET

Product: *Gray W/B Primer*

Object Finished: *Cast Iron Objects & Pipe Fittings, and other ferrous substrates*

Formula Number: *41D-562*

Product Description

This product is designed for use as a protective coating on cast iron objects and pipe fittings and other ferrous substrates.

Advantages

- Exhibits quick dry
- Excellent block resistance
- Good corrosion resistance

Product Information

Weight per Gallon: 10.54 lbs +/- 1.0

Viscosity: 26-28" EZ3 Zahn

Weight Solids: 50.03% +/- 2.0


Volume Solids: 36.51%

VOC: 1.17 lbs/gal (minus water), 1.38 lbs VOC gallon solid

Packaging: 5-gallon pail, 50-gallon drum, 265-gallon tote

Appearance: Gray liquid

Storage: Protect from freeze



CHEMCOAT, INC.

"Consistent Coatings . . . Superior Service"

P.O. BOX 188
MONTGOMERYVILLE, PA 17754-0188

PH: (570) 368-8631 • FAX: (570) 368-8635

PRODUCT DATA SHEET

APPLICATION INFORMATION

For Dip or Spray Application: Adjust withdrawal rate to apply a smooth, continuous film.

Film Thickness: 2.5-3.0 mils wet, 1.0-1.3 mils dry

Bake Time and Temperature: Flash –5 minutes, Bake 15 minutes @ 150-175°F.

Coverage: 586 sq ft/gal @ 1 mil dry

Mixing: No dilution required, but it may be diluted with water if desired.

General Use: To ensure proper film formation and development of physical properties, do not use this paint when air, substrate or paint temperature are below 50°F. This product must be protected from freezing.

BASIS OF PRODUCT DATA

Results may vary depending on equipment, atmospheric conditions, mixing methods, etc.

OTHER RESTRICTIONS

See Legal Disclaimer

ENVIRONMENTAL, HEALTH AND SAFETY

Refer to the Safety Data Sheet

LEGAL DISCLAIMER

- **Keep container tightly closed**
- **Keep out of reach of children**
- **For industrial use only**
- **Not for internal consumption**
- **For professional use only**

Prior to each use of any product of Chemcoat, Inc., the user must always read and follow the warnings and instructions on the product's most current product label, Product Data Sheet and Safety Data Sheet; which are available upon request @

Customerservice@chemcoat.com