



Coastal®

Coastal Synthetic Blend SAE 75W-90 Gear Oil



Coastal Synthetic Blend SAE 75W-90 Gear Oil is a high performance Synthetic Blend sulfur/phosphorous gear lubricant designed for API Service Classification GL-5. It is formulated with additives to ensure extreme pressure characteristics, anti-wear, corrosion inhibition, rust prevention, low pour point, and anti-foaming performance. It may be used in limited slip differentials for top-off only.

Coastal Synthetic Blend SAE 75W-90 Gear Oil is recommended for use in passenger cars, light duty trucks and sport utility vehicles. Always check owner's manual for proper recommendation.

Benefits

- Excellent wear protection
- Shear resistant
- Oxidation and thermal stability for long life
- Excellent rust and corrosion protection
- Compatible with conventional gear lubricants



Warren Oil Company, Inc

Dunn, NC 28334: Benton, AL 36758: San Antonio, TX 78210:
Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72301



Coastal Synthetic Blend SAE 75W-90 Gear Oil

Typical Characteristics

SAE Viscosity Grade		75W-90
Pour Point Deg F.		-35
Flash Point, COC, °F		400
Viscosity		
@ 40°C, cSt		102.8
@ 100°C, cSt		15.9
Viscosity Index		166
Gravity, API		30.9
Rust Test, ASTM D665		Pass
Product Code #		
Bulk		158000
Drum		158019
Keg		158018
Pail		158017
12/1 Quart		158001



Warren Oil Company, Inc

Dunn, NC 28334: Benton, AL 36758: San Antonio, TX 78210:
Marion, IL 62959: Johnstown, PA 15909: West Memphis, AR 72301