



# SAFETY DATA SHEET

## 1. Identification

**Product identifier** Freeze-Off® Super Penetrant

**Other means of identification**

**Product code** 05002

**Recommended use** Penetrant

**Recommended restrictions** None known.

**Manufacturer/Importer/Supplier/Distributor information**

**Manufactured or sold by:**

**Company name** CRC Industries, Inc.  
**Address** 885 Louis Dr.  
Warminster, PA 18974 US

**Telephone**

**General Information** 215-674-4300

**Technical Assistance** 800-521-3168

**Customer Service** 800-272-4620

**24-Hour Emergency (CHEMTREC)** 800-424-9300 (US)

703-527-3887 (International)

**Website** www.crcindustries.com

## 2. Hazard(s) identification

<b>Physical hazards</b>	Flammable aerosols Gases under pressure	Category 1 Liquefied gas
<b>Health hazards</b>	Skin corrosion/irritation Serious eye damage/eye irritation Sensitization, skin Specific target organ toxicity, single exposure Specific target organ toxicity, repeated exposure Aspiration hazard	Category 2 Category 2A Category 1 Category 3 respiratory tract irritation Category 2 Category 1
<b>Environmental hazards</b>	Hazardous to the aquatic environment, long-term hazard	Category 3
<b>OSHA defined hazards</b>	Not classified.	

**Label elements**



**Signal word** Danger

**Hazard statement** Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause respiratory irritation. May cause damage to organs through prolonged or repeated exposure. Harmful to aquatic life with long lasting effects.

**Precautionary statement**

**Prevention** Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Do not apply while equipment is energized. Pressurized container: Do not pierce or burn, even after use. Extinguish all flames, pilot lights and heaters. Vapors will accumulate readily and may ignite. Use only with adequate ventilation; maintain ventilation during use and until all vapors are gone. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Do not breathe gas, mist or vapor. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves and eye/face protection. Wash hands thoroughly after handling. Avoid release to the environment.

<b>Response</b>	If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. If on skin: Wash with plenty of water. If skin irritation or rash occurs: Get medical attention. Take off contaminated clothing and wash before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
<b>Storage</b>	Store locked up. Store in a well-ventilated place. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Exposure to high temperature may cause can to burst.
<b>Disposal</b>	Dispose of contents/container in accordance with local/regional/national regulations.
<b>Hazard(s) not otherwise classified (HNOC)</b>	Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

**Supplemental information**

87.51% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

**3. Composition/information on ingredients**

**Mixtures**

Chemical name	Common name and synonyms	CAS number	%
1,1-Difluoroethane		75-37-6	40 - 50
Distillates (petroleum), hydrotreated middle		64742-46-7	20 - 30
Distillates (petroleum), hydrotreated light		64742-47-8	5 - 10
Turpentine, oil		8006-64-2	5 - 10
COzol® 306		Proprietary	4 - 6
Stoddard Solvent		8052-41-3	3 - 5
2-Butoxyethanol		111-76-2	1 - 3
4-Hydroxy-4-methylpentan-2-one (Diacetone alcohol)		123-42-2	1 - 3

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

**4. First-aid measures**

<b>Inhalation</b>	Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
<b>Skin contact</b>	Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.
<b>Eye contact</b>	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
<b>Ingestion</b>	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Aspiration may cause pulmonary edema and pneumonitis.
<b>Most important symptoms/effects, acute and delayed</b>	Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause an allergic skin reaction. Dermatitis. Rash. May cause redness and pain. Prolonged exposure may cause chronic effects.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
<b>General information</b>	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

**5. Fire-fighting measures**

<b>Suitable extinguishing media</b>	Water spray. Water fog. Foam. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire.
<b>Specific hazards arising from the chemical</b>	Contents under pressure. Pressurized container may explode when exposed to heat or flame. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. Static electricity accumulation may be significantly increased by the presence of small quantities of water or other contaminants. Material will float and may ignite on surface of water.
<b>Special protective equipment and precautions for firefighters</b>	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

**Fire-fighting equipment/instructions**

In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. If tank, rail car or tank truck is involved in a fire, ISOLATE for 800 meters (1/2 mile) in all directions; also consider initial evacuation for 800 meters (1/2 mile) in all directions. ALWAYS stay away from tanks engulfed in flame. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

**General fire hazards**

Extremely flammable aerosol.

**6. Accidental release measures**

**Personal precautions, protective equipment and emergency procedures**

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Remove all possible sources of ignition in the surrounding area. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Do not breathe gas, mist or vapor. Ventilate closed spaces before entering them. Use appropriate containment to avoid environmental contamination. Transfer by mechanical means such as vacuum truck to a salvage tank or other suitable container for recovery or safe disposal. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

**Methods and materials for containment and cleaning up**

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material.

Large Spills: Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Scoop up used absorbent into drums or other appropriate container. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

**Environmental precautions**

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground. Use appropriate containment to avoid environmental contamination.

**7. Handling and storage**

**Precautions for safe handling**

Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Handling operations that can promote accumulation of static charges include but are not limited to: mixing, filtering, pumping at high flow rates, splash filling, creating mists or sprays, tank and container filling, tank cleaning, sampling, gauging, switch loading, vacuum truck operations. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Do not re-use empty containers. Do not breathe mist or vapor. Do not breathe gas. Do not get this material in contact with skin. Avoid contact with eyes. Avoid prolonged exposure. Avoid contact with clothing. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices. Avoid release to the environment. Do not empty into drains. For product usage instructions, please see the product label.

**Conditions for safe storage, including any incompatibilities**

Level 3 Aerosol.

Store in a well-ventilated place. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Avoid spark promoters. These alone may be insufficient to remove static electricity. Store away from incompatible materials (see Section 10 of the SDS). Keep out of the reach of children.

**8. Exposure controls/personal protection**

**Occupational exposure limits**

**US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value	Form
2-Butoxyethanol (CAS 111-76-2)	PEL	240 mg/m <sup>3</sup>	
		50 ppm	

**US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)**

Components	Type	Value	Form
4-Hydroxy-4-methylpentan-2-one (Diacetone alcohol) (CAS 123-42-2)	PEL	240 mg/m3	
Distillates (petroleum), hydrotreated middle (CAS 64742-46-7)	PEL	50 ppm 5 mg/m3	Mist.
Stoddard Solvent (CAS 8052-41-3)	PEL	2900 mg/m3	
Turpentine, oil (CAS 8006-64-2)	PEL	500 ppm 560 mg/m3	
		100 ppm	

**US. ACGIH Threshold Limit Values**

Components	Type	Value	Form
2-Butoxyethanol (CAS 111-76-2)	TWA	20 ppm	
4-Hydroxy-4-methylpentan-2-one (Diacetone alcohol) (CAS 123-42-2)	TWA	50 ppm	
Distillates (petroleum), hydrotreated middle (CAS 64742-46-7)	TWA	5 mg/m3	Inhalable fraction.
Stoddard Solvent (CAS 8052-41-3)	TWA	100 ppm	
Turpentine, oil (CAS 8006-64-2)	TWA	20 ppm	

**US. NIOSH: Pocket Guide to Chemical Hazards**

Components	Type	Value	Form
2-Butoxyethanol (CAS 111-76-2)	TWA	24 mg/m3	
4-Hydroxy-4-methylpentan-2-one (Diacetone alcohol) (CAS 123-42-2)	TWA	5 ppm 240 mg/m3	
Distillates (petroleum), hydrotreated light (CAS 64742-47-8)	TWA	50 ppm 100 mg/m3	
Distillates (petroleum), hydrotreated middle (CAS 64742-46-7)	STEL	10 mg/m3	Mist.
Stoddard Solvent (CAS 8052-41-3)	TWA Ceiling	5 mg/m3 1800 mg/m3	Mist.
Turpentine, oil (CAS 8006-64-2)	TWA TWA	350 mg/m3 560 mg/m3	
		100 ppm	

**US. AIHA Workplace Environmental Exposure Level (WEEL) Guides**

Components	Type	Value
1,1-Difluoroethane (CAS 75-37-6)	TWA	2700 mg/m3 1000 ppm

**Biological limit values**

**ACGIH Biological Exposure Indices**

Components	Value	Determinant	Specimen	Sampling Time
2-Butoxyethanol (CAS 111-76-2)	200 mg/g	Butoxyacetic acid (BAA), with hydrolysis	Creatinine in urine	*

\* - For sampling details, please see the source document.

## Exposure guidelines

### US - California OELs: Skin designation

2-Butoxyethanol (CAS 111-76-2) Can be absorbed through the skin.

### US - Minnesota Haz Subs: Skin designation applies

2-Butoxyethanol (CAS 111-76-2) Skin designation applies.

### US - Tennessee OELs: Skin designation

2-Butoxyethanol (CAS 111-76-2) Can be absorbed through the skin.

### US NIOSH Pocket Guide to Chemical Hazards: Skin designation

2-Butoxyethanol (CAS 111-76-2) Can be absorbed through the skin.

### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

2-Butoxyethanol (CAS 111-76-2) Can be absorbed through the skin.

### Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

### Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

#### Skin protection

**Hand protection** Wear protective gloves: Nitrile. Rubber.

**Other** Wear appropriate chemical resistant clothing.

**Respiratory protection** Wear positive pressure self-contained breathing apparatus (SCBA). Air monitoring is needed to determine actual employee exposure levels.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

### General hygiene considerations

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

## 9. Physical and chemical properties

---

### Appearance

**Physical state** Liquid.

**Form** Aerosol.

**Color** Orange.

**Odor** Pine.

**Odor threshold** Not available.

**pH** Not available.

**Melting point/freezing point** -103 °F (-75 °C) estimated

**Initial boiling point and boiling range** 311 °F (155 °C) estimated

**Flash point** 126 °F (52.2 °C) Tag Closed Cup

**Evaporation rate** Slow.

**Flammability (solid, gas)** Not available.

### Upper/lower flammability or explosive limits

**Flammability limit - lower (%)** 0.6 % estimated

**Flammability limit - upper (%)** 10.6 % estimated

**Vapor pressure** 5273.9 hPa estimated

**Vapor density** > 1 (air = 1)

**Relative density** 0.88 estimated

**Solubility (water)** Not available.

**Partition coefficient (n-octanol/water)** Not available.

**Auto-ignition temperature** 446 °F (230 °C) estimated

**Decomposition temperature** Not available.

**Viscosity (kinematic)** Not available.

**Percent volatile** 100 % estimated

## 10. Stability and reactivity

<b>Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>Conditions to avoid</b>	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
<b>Incompatible materials</b>	Strong oxidizing agents. Chlorine.
<b>Hazardous decomposition products</b>	Carbon oxides.

## 11. Toxicological information

### Information on likely routes of exposure

<b>Ingestion</b>	May be fatal if swallowed and enters airways.
<b>Inhalation</b>	Prolonged inhalation may be harmful. May cause damage to organs by inhalation. May cause irritation to the respiratory system.
<b>Skin contact</b>	Causes skin irritation. May cause an allergic skin reaction.  2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.

**Eye contact** Causes serious eye irritation.

**Symptoms related to the physical, chemical and toxicological characteristics** Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May cause an allergic skin reaction. Skin irritation. May cause redness and pain. Dermatitis. Rash.

### Information on toxicological effects

**Acute toxicity** May be fatal if swallowed and enters airways. May cause an allergic skin reaction. May cause respiratory irritation.

Product	Species	Test Results
Freeze-Off® Super Penetrant		
<b>Acute</b>		
<i>Dermal</i>		
LD50	Rabbit	6287.9321 mg/kg estimated
<i>Inhalation</i>		
LC50	Rat	71729.7031 mg/l, 1 Hours estimated 17901.9043 ppm, 4 hours estimated
<i>Oral</i>		
LD50	Rat	6633.7905 mg/kg estimated
<b>Chronic</b>		
<i>Oral</i>		
LD50	Mouse	6324.7803 g/kg estimated

\* Estimates for product may be based on additional component data not shown.

**Skin corrosion/irritation** Causes skin irritation.

**Serious eye damage/eye irritation** Causes serious eye irritation.

### Respiratory or skin sensitization

#### ACGIH sensitization

Turpentine, oil (CAS 8006-64-2) Sensitiser.

**Respiratory sensitization** Not available.

**Skin sensitization** May cause an allergic skin reaction.

**Germ cell mutagenicity** No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

**Carcinogenicity** This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

#### IARC Monographs. Overall Evaluation of Carcinogenicity

2-Butoxyethanol (CAS 111-76-2) 3 Not classifiable as to carcinogenicity to humans.

**Reproductive toxicity** This product is not expected to cause reproductive or developmental effects.

**Specific target organ toxicity - single exposure** Respiratory tract irritation.

<b>Specific target organ toxicity - repeated exposure</b>	May cause damage to organs through prolonged or repeated exposure.
<b>Aspiration hazard</b>	May be fatal if swallowed and enters airways.
<b>Chronic effects</b>	Prolonged inhalation may be harmful. May be harmful if absorbed through skin.  2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.  May cause damage to organs through prolonged or repeated exposure.

## 12. Ecological information

**Ecotoxicity** Harmful to aquatic life with long lasting effects. Accumulation in aquatic organisms is expected.

Product	Species	Test Results
Freeze-Off® Super Penetrant		
Crustacea	EC50 Daphnia	22847.4102 mg/l, 48 hours estimated
Fish	LC50 Fish	1029.5527 mg/l, 96 hours estimated

Components	Species	Test Results
2-Butoxyethanol (CAS 111-76-2)		
<b>Aquatic</b>		
<i>Acute</i>		
Crustacea	EC50 Water flea (Daphnia magna)	1550 mg/l, 48 hours
Fish	LC50 Rainbow trout, donaldson trout (Oncorhynchus mykiss)	> 1000 mg/l, 96 hours
4-Hydroxy-4-methylpentan-2-one (Diacetone alcohol) (CAS 123-42-2)		
<b>Aquatic</b>		
Crustacea	EC50 Water flea (Daphnia magna)	8750 mg/l, 48 hours
Fish	LC50 Bluegill (Lepomis macrochirus) Goldfish (Carassius auratus)	420 mg/l, 96 hours > 5000 mg/l, 24 hours

\* Estimates for product may be based on additional component data not shown.

**Persistence and degradability** No data is available on the degradability of this product.

**Bioaccumulative potential** No data available.

**Partition coefficient n-octanol / water (log Kow)**

1,1-Difluoroethane	0.75
2-Butoxyethanol	0.81, log Pow
4-Hydroxy-4-methylpentan-2-one (Diacetone alcohol)	-0.098
Stoddard Solvent	3.16 - 7.15

**Mobility in soil** No data available.

**Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

## 13. Disposal considerations

**Disposal of waste from residues / unused products** This material and its container must be disposed of as hazardous waste. If discarded, this product is considered a RCRA ignitable waste, D001. Consult authorities before disposal. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national regulations.

**Hazardous waste code** D001: Waste Flammable material with a flash point <140 F

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

## 14. Transport information

### DOT

<b>UN number</b>	UN1950
<b>UN proper shipping name</b>	Aerosols, flammable, limited quantity
<b>Transport hazard class(es)</b>	
<b>Class</b>	2.1
<b>Subsidiary risk</b>	-
<b>Label(s)</b>	2.1
<b>Packing group</b>	Not applicable.
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.

<b>Special provisions</b>	N82
<b>Packaging exceptions</b>	306
<b>Packaging non bulk</b>	304
<b>Packaging bulk</b>	None

#### IATA

<b>UN number</b>	UN1950
<b>UN proper shipping name</b>	Aerosols, flammable, limited quantity
<b>Transport hazard class(es)</b>	
<b>Class</b>	2.1
<b>Subsidiary risk</b>	-
<b>Packing group</b>	Not applicable.
<b>Environmental hazards</b>	No.
<b>ERG Code</b>	10L
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.

#### Other information

**Passenger and cargo aircraft** Allowed.

**Cargo aircraft only** Allowed.

#### IMDG

<b>UN number</b>	UN1950
<b>UN proper shipping name</b>	AEROSOLS, LIMITED QUANTITY
<b>Transport hazard class(es)</b>	
<b>Class</b>	2
<b>Subsidiary risk</b>	-
<b>Packing group</b>	Not applicable.
<b>Environmental hazards</b>	
<b>Marine pollutant</b>	No.
<b>EmS</b>	F-D, S-U
<b>Special precautions for user</b>	Read safety instructions, SDS and emergency procedures before handling.

## 15. Regulatory information

---

**US federal regulations** This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

#### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

#### SARA 304 Emergency release notification

Not regulated.

#### US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

#### US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

2-Butoxyethanol (CAS 111-76-2)

#### CERCLA Hazardous Substance List (40 CFR 302.4)

2-Butoxyethanol (CAS 111-76-2)

#### CERCLA Hazardous Substances: Reportable quantity

Not listed.

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

1,1-Difluoroethane (CAS 75-37-6)

**Safe Drinking Water Act (SDWA)** Not regulated.

**Food and Drug Administration (FDA)** Not regulated.

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

**Section 311/312 Hazard categories**  
 Immediate Hazard - Yes  
 Delayed Hazard - Yes  
 Fire Hazard - Yes  
 Pressure Hazard - Yes  
 Reactivity Hazard - No



**SARA 302 Extremely hazardous substance** No

#### US state regulations

##### US. New Jersey RTK - Substances: Listed substance

1,1-Difluoroethane (CAS 75-37-6)  
2-Butoxyethanol (CAS 111-76-2)  
4-Hydroxy-4-methylpentan-2-one (Diacetone alcohol) (CAS 123-42-2)  
Stoddard Solvent (CAS 8052-41-3)  
Turpentine, oil (CAS 8006-64-2)

##### US. Massachusetts RTK - Substance List

1,1-Difluoroethane (CAS 75-37-6)  
2-Butoxyethanol (CAS 111-76-2)  
4-Hydroxy-4-methylpentan-2-one (Diacetone alcohol) (CAS 123-42-2)  
Stoddard Solvent (CAS 8052-41-3)  
Turpentine, oil (CAS 8006-64-2)

##### US. Pennsylvania RTK - Hazardous Substances

2-Butoxyethanol (CAS 111-76-2)  
4-Hydroxy-4-methylpentan-2-one (Diacetone alcohol) (CAS 123-42-2)  
Stoddard Solvent (CAS 8052-41-3)

##### US. Rhode Island RTK

1,1-Difluoroethane (CAS 75-37-6)  
2-Butoxyethanol (CAS 111-76-2)

##### US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

##### US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Cumene (CAS 98-82-8) Listed: April 6, 2010

#### Volatile organic compounds (VOC) regulations

##### EPA

**VOC content (40 CFR 51.100(s))** 50 %

**Consumer products (40 CFR 59, Subpt. C)** Not regulated

##### State

**Consumer products** This product is regulated as a Penetrant. This product is compliant for use in all 50 states.

**VOC content (CA)** 24.1 %

**VOC content (OTC)** 24.1 %

#### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

#### 16. Other information, including date of preparation or last revision

**Issue date** 11-01-2013  
**Prepared by** Allison Cho  
**Version #** 01  
**Further information** CRC # 447C

**HMIS® ratings**

Health: 2\*  
Flammability: 4  
Physical hazard: 0  
Personal protection: B

**NFPA ratings**

Health: 2  
Flammability: 4  
Instability: 0

**Disclaimer**

The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety professional, or CRC Industries.