

DINITROL 447

**Quick-drying body protection
with zinc additives**

DINITROL 447 is a stone chip protection with enhanced corrosion protection.

» **Permanently elastic**

» **Zn-enriched**

» **Flexible**

» **Can be coated**

» **Resistant to road salt**



Equipment

DINITROL Spray Tool HS 1-P
Art. No. 1700500

DINITROL Spray Tool UBS/HR GSI
Art. No. 1701900

DINITROL Pump unit for 20 L Pails
Art. No. 1705100

DINITROL Airless Pump 1:26
Art. No. 1705900

DINITROL 447

| Art. No. | Size | Package | Color |
|----------|--------|-----------|-------|
| 11012 | 500 ml | Spray can | Black |
| 11013 | 1 L | Can | Black |
| 11024 | 1 L | Can | Grey |
| 11052 | 208 L | Drum | Black |

a brand of



DINOL GmbH Pyrmonter Straße 76, D-32676 Lügde, Germany
Tel. +49 (0) 5281-98 2 98-0, Fax +49 (0) 5281-98 2 98-60, www.dinol.com

04.2023

All data and recommendations are the result of careful tests by our laboratory. They only can be considered as recommendation which corresponds to the level of experience of today. The data are given in good faith. However, in view of the multiplicity of possible application and working methods we are not in a position to assume any responsibility or obligations deriving from the misuse of our products. Therefore, a contractual legal relationship is not justified, and there are no secondary obligations arising from any purchase contracts.

DINITROL 447

Technical Details

Product descriptions

DINITROL 447 Protect Super is a fast-drying, rubber and resin based auto-body protection agent. Clearly higher rust protection is achieved through zinc additives. Zinc ions also prevent or delay rust formation in areas where the protective film is damaged. DINITROL 447 Protect Super contains no aggressive solvents such as chlorinated hydrocarbons (CFC/CHC), esters and ketones.

Applications

The product is particularly well-suited for after-treatment of autobodies. DINITROL 447 Protect Super does not attack PVC coatings, is asbestos- and bitumen-free, permanently elastic and resists stone impact and road salt. After thorough drying, DINITROL 447 Protect Super can be coated with all conventional paints.

Method of use

DINITROL 447 Protect Super is sprayed onto the dry, dust- and grease-free surface evenly and in criss-cross pattern, using 4 – 6 bar air pressure and a suitable gun for underbody protection. DINITROL 447 Protect Super can be painted over when thoroughly dry. Splashes can be removed with a white spirit-soaked cloth.

Pre-treatment Substrates

Surfaces shall be dry, clean and free from corrosion.

Over-Coating / 2-Layer-Application

DINITROL 447 Protect Super can be overpainted with the most common paints. It is recommended to make a test application to make sure it is working properly.

Storage

When stored cool and dry, the product has a shelf life of minimum 2 years in the unopened original packaging. For additional information please consult DINOL.

Safety precautions

Additional information can be found in the safety data sheet.

Transportation

Additional information can be found in the safety data sheet.

Technical Data

| | |
|--------------------------------|---|
| Colour | black, grey |
| Base | resin/rubber |
| Spec. weight | approx. 1 g/ml |
| Solids content | approx. 50% |
| Working temperature | 10 – 25°C |
| Water solubility | insoluble in water |
| Paintable | after thorough drying |
| Recommended film thickness wet | 1000 µm |
| Salt spray test DIN 50021 | over 400 h |
| Storage period | 24 months |
| Available in | 500 ml spray can / 1 L can / 208 L drum |

Spray - Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation
Aerosol 1; H222-H229; Skin Irrit. 2; H315; Eye Irrit. 2; H319;
Skin Sens. 1; H317; STOT SE 3; H336; STOT RE 2; H373;

Liter - Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation
Flam. Liq. 2; H225; Skin Irrit. 2; H315; Eye Irrit. 2; H319; Skin Sens. 1; H317;
STOT SE 3; H336; STOT RE 2; H373; Aquatic Chronic 2; H411

For all relevant safety advices please read the material safety data sheet or the packaging label.