

CASSIDA Product Information



LUBRITECH
Special Application Lubricants

CASSIDA FLUID GL Series

Synthetic gear lubricants for use in food manufacturing equipment



Gears – enclosed



Roller Bearings



NSF registered

Description

CASSIDA FLUID GL 150, 220, 320, 460 and 680 are high performance, anti-wear gear oils specially developed for the lubrication of enclosed gears in food and beverage processing machinery.

They are based on a careful blend of synthetic fluids and selected additives chosen for their ability to meet the stringent requirements of the food industry.

Certified by NSF for ISO 21469 and registered by NSF (Class H1) for use where there is potential for incidental food contact. Produced according to LUBRITECH Quality Standards, in facilities where HACCP audit and Good Manufacturing Practice have been implemented and form part of the quality and hygiene management systems ISO 9001 and ISO 21469.

Certifications and Specifications

- NSF H1
- NSF ISO 21469
- Kosher
- Halal
- DIN 51506 VBL (GL 150, 220), VCL (GL 150)
- ISO/DP 6743/6 L-CKD
- DIN 51517 CLP

Performance Features

- Resists the formation of harmful products of oxidation even at elevated temperatures
- Base oil has an ability to provide superior lubrication under all operating conditions
- Excellent EP properties make CASSIDA FLUID GL suitable for steel-on-steel and worm and phosphor-bronze wheel applications

CASSIDA Product Information



LUBRITECH
Special Application Lubricants

- Neutral odor and taste
- High viscosity index resulting in minimum variation of viscosity with change in temperature

Applications

- Lubrication of enclosed gearboxes used in the food industry
- Also intended for use in equipment manufacturing food packaging

Seal and paint compatibility

Compatible with the elastomers, gaskets, seals and paints normally used in food machinery lubrication systems.

Handling and storage

All food grade lubricants should be stored separately from other lubricants, chemical substances and foodstuffs and out of direct sunlight or other heat sources. Store between 0 °C and +40 °C. Provided that the product has been stored under these conditions we recommend to use the product within 5 years from the date of manufacture. Upon opening a pack, the product must be used within 2 years (or within 5 years of date of manufacture, whichever is the sooner).

Typical characteristics

Property	GL 150	GL 220	GL 320	GL 460	GL 680	Unit	Test Method
NSF Reg. No.	147331	147332	147333	147334	147335		
Colour	Colourless to Yellow	Colourless to Yellow	Colourless to Yellow	Colourless to Yellow	Colourless to Yellow		
Density at +15 °C	845	847	852	855	858	kg/m ³	ISO 12185
Flash Point	268 (514)	276 (528)	278 (532)	270 (518)	286 (546)	°C (°F)	ISO 2592
Pour Point	-54 (-65)	-48 (-54)	-45 (-49)	-45 (-49)	-39 (-38)	°C (°F)	ISO 3016
Kin. Visc. at +40 °C	150	220	320	460	680	mm ² /s	ISO 3104
Kin. Visc. at +100 °C	18.9	25.0	33.4	43.8	58.6	mm ² /s	ISO 3104
Viscosity Index	143	143	147	148	152		ISO 2909
FZG-Test A/8.3/90 Failure Load Stage	>12	>12	>12	>12	>12		ISO 14635-1

As far as we know these information reflect the current state of knowledge and our research. They cannot, however, be taken as an

CASSIDA Product Information



LUBRITECH
Special Application Lubricants

assurance about the properties nor as a guarantee of the suitability of the product for the individual case in point. Before using our products the purchaser must, therefore, check the suitability and be satisfied that the output will be satisfactory. Our products are continually being up-dated. We reserve the right, therefore, to alter the information of this product information at any time and without prior announcement. We are specialized in developing products for extreme tribological problems in cooperation with end users. FUCHS LUBRITECH provides service and individual advice. Please contact us! E-Mail: Lubritech-US@fuchs.com