

PRODUCT INFORMATION



LIQUID WRENCH® SUPER LUBRICANT AEROSOL

CODE: L212

PAGE: 1 of 1

DATE: 1/23/2008

FUNCTION AND APPLICATION: Lubricates, stops squeaks, loosens rusted and sticky parts, absorbs moisture.

OUTSTANDING PROPERTIES: Quickly cleans and lubricates typewriters, clocks, sewing machines, air conditioners, guns, fishing reels, fine instruments, hand and power tools, toys, zippers, sliding doors, casters and all moving parts. It frees rusted parts and helps stop corrosion on nuts, bolts, screws, fasteners, chains, cables and linkages, valves and fittings, lawn mowers and automobile engines. Displaces water from wet surfaces and leaves a rust inhibiting film. It dries out engines, spark plugs, coils, switches and wiring.

USE DIRECTIONS: Spray and watch it work. Harmless to fabrics, leather, rubber or paint.

PRECAUTIONS: Contains Aliphatic Petroleum Distillate (CAS# 8052-41-3), 2-Butoxy-1-Ethanol (CAS# 111-76-2), naphthenic Petroleum Oil Mixture (CAS# 64742-52-5), Corrosion Inhibitor (Mixture), Carbon Dioxide (CAS# 124-38-9). Combustible. Harmful or Fatal if Swallowed. Eye and Skin Irritant. Vapor Harmful. Contents under pressure.

FIRST AID: If swallowed DO NOT INDUCE VOMITING. Call Poison Control Center, Physician, or Hospital Emergency Room Immediately. For eye contact, flush with water for at least 15 minutes while lifting eyelid and get prompt medical attention. For skin contact, wash thoroughly with soap and water. If irritation persists, get prompt medical attention. If inhaled, move to fresh air. If breathing becomes difficult, get prompt medical attention.

STORAGE & HANDLING: Store in a dry, well-ventilated area below 120°F/49°C. Do not puncture, crush or incinerate (burn) can. **FIRE:** Use only in a well ventilated area away from heat, sparks and flame. Pilot lights of furnaces or hot water tanks can ignite vapors. Insure adequate ventilation in confined spaces such as: garages, basements, engine compartment. Vapors can collect in low-lying areas. Keep away from hot surfaces, direct sunlight, or contact with electrical current or connections such as battery terminals. Explosion or flash fire from vapors may cause serious injury or death. **CONTACT:** Avoid contact with eyes, skin or clothing. Remove contact lenses before use. **BREATHING:** Do not breathe vapors, gas or mist. Use only in well-ventilated area. Open doors and windows to prevent build up. **INHALING CONCENTRATED VAPORS, INTENTIONALLY OR OTHERWISE, CAN BE FATAL. KEEP AWAY FROM CHILDREN AND ANIMALS.**

Warning: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

DISPOSAL: Dispose of container, residue and excess product in accordance with all federal, state and local laws and regulations. Emptied containers contain product residue, so follow all warnings even after container is emptied.

CONTAINER DESCRIPTION: This product is available in an 11-oz aerosol container.



Radiator Specialty Company

600 RADIATOR ROAD, INDIAN TRAIL, N.C. 28079-5225 / 704-821-7643, 877-GO-4-GUNK

NOTICE: While this information is presented in good faith and believed to be accurate, Radiator Specialty Company does not guarantee satisfactory results from reliance thereon. The data is offered solely for your information and Radiator Specialty Company disclaims all liability for any loss or damage from its use. Thoroughly test any application according to the product directions and independently conclude satisfactory performance. Nothing contained herein is to be construed as a recommendation to use the product in violation of any patent.