

RE-ORDER THIS PRODUCT



petroleumservicecompany.com
(570) 822-1151



GT-1[®] Full Synthetic Motor Oil with Liquid Titanium[®]

Kendall[®] GT-1 Full Synthetic Motor Oil with Liquid Titanium protection additive is a premium quality, full-synthetic automotive engine oil designed to provide maximum engine protection for gasoline-fueled and flex-fuel passenger cars and light trucks under all operating conditions. It is particularly recommended for vehicles operating at extreme temperatures or under severe driving conditions, such as towing heavy loads.

GT-1 Full Synthetic with Liquid Titanium is formulated with synthetic base stocks and a performance additive package fortified with our exclusive Liquid Titanium protection additive for extra wear protection and improved fuel savings. The full-synthetic formulation, compared with conventional engine oils, provides improved protection against viscosity breakdown and deposit formation at high temperatures; lower volatility for reduced oil consumption; and faster oil circulation at low temperatures for easier starting and better protection during cold starts. The Liquid Titanium protection additive provides increased engine protection by forming a strongly bonded titanium shield on the surface of critical engine parts, which reduces friction and wear and can help extend engine life. Reduced friction also helps improve fuel economy performance beyond ILSAC GF-5 requirements.

GT-1 Full Synthetic with Liquid Titanium exceeds new car warranty requirements as defined by ILSAC GF-5. It meets or exceeds "Resource Conserving" requirements for fuel economy improvement, emission system and turbocharger protection, and protection of engines operating on ethanol-containing fuels up to E85. It is backward serviceable for use where API SM or earlier "S" category engine oils are recommended. The SAE 5W-30 grade also is OEM-approved for use in GM vehicles where dexos1[™] quality oil is specified.

Applications

- Gasoline-fueled and flex-fuel passenger cars, light trucks and sport utility vehicles, including gasoline-electric hybrids, especially when operating under severe conditions
- Four-stroke cycle gasoline engines in other mobile or stationary equipment

**Premium
Full-Synthetic
Passenger Car
Engine Oil;
Fortified With
Liquid Titanium[®]
Protection
Additive**



CONTACT INFORMATION

**Phillips66
Lubricants.com**

U.S. Customer
Service:
1-800-368-7128

Technical Hotline:
1-877-445-9198

International
Customer Service:
1-832-765-2500

E-mail address:
**kendallmotoroil@
p66.com**



GT-1 Full Synthetic with Liquid Titanium is licensed or OEM-certified for:

- ILSAC GF-5
- API Service SN with Resource Conserving
- GM dexos1™ (SAE 5W-30 only)

GT-1 Full Synthetic with Liquid Titanium meets or exceeds the requirements of:

- Chrysler MS-6395 (Rev. T) (SAE 5W-20, 5W-30, 10W-30)
- Ford WSS-M2C945-A (SAE 5W-20), WSS-M2C946-A (SAE 5W-30)
- GM4718M (SAE 5W-30 only), GM6094M (obsolete specifications)

Features/Benefits

- Exceeds ILSAC GF-5 requirements for new cars under warranty
- Enhanced performance benefits at extreme temperatures compared with conventional engine oils
- Exclusive Liquid Titanium® protection additive provides extra wear protection and improved fuel economy
- Outstanding resistance to viscosity and thermal breakdown at high temperatures
- Protects against sludge and varnish formation
- Protects against rust and bearing corrosion
- Low volatility for reduced oil consumption
- Excellent low-temperature pumpability for protection during cold starts
- Highly resistant to foaming
- Formulated to protect turbochargers and emission control system catalysts
- Formulated for use in vehicles operating on ethanol-containing fuels up to E85

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

© 2012 Phillips 66 Company. Kendall, the Two Finger logo, Liquid Titanium and their respective logos and products are trademarks of Phillips 66 Company in the U.S.A. and other countries.

GT-1® Full Synthetic Motor Oil with Liquid Titanium®
Typical Properties

SAE Grade	0W-20	5W-20	5W-30	10W-30
Specific Gravity @ 60°F	0.847	0.848	0.851	0.852
Density, lbs/gal @ 60°F	7.05	7.06	7.09	7.10
Color, ASTM D1500	3.0	3.0	3.0	3.0
Flash Point (COC), °C (°F)	229 (444)	229 (444)	235 (455)	232 (450)
Pour Point, °C (°F)	-43 (-45)	-41 (-42)	-40 (-40)	-39 (-38)
Viscosity, Kinematic				
cSt @ 40°C	43.9	45.4	61.2	63.2
cSt @ 100°C	8.4	8.4	10.9	10.4
Viscosity Index	171	164	171	153
Cold Cranking Viscosity, cP	5,000	6,650	4,900	3,750
@ (°C)	(-35)	(-30)	(-30)	(-25)
High Temp/High Shear Viscosity, cP @ 150°C	2.6	2.6	3.0	3.1
Sulfated Ash, ASTM D874, wt %	0.96	0.96	1.02	0.96
Total Base Number (TBN), ASTM D2896	8.0	8.0	8.6	8.0
Phosphorus, wt %	0.077	0.077	0.077	0.077
Titanium, wt %	0.010	0.010	0.010	0.010
Zinc, wt %	0.085	0.085	0.085	0.085

Health and Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet via <http://w3apps.phillips66.com/NetMSDS>.