

NEVASTANE® 6 SAFEGARD



FOOD INDUSTRY



TOTAL

Food Machinery Oil - SafeGard Spray.

APPLICATIONS

General Purpose Food Machinery Oil.

H1 Registered Food Grade Spray.



ADVANTAGES

- **NEVASTANE 6** is a general purpose food machinery oil, that makes it easy to save time and money with just the right amount of spray applied quickly and cleanly in the right places. It is formulated from USP white oils and additives which enable it to wet out on metal surfaces better than usual white oils providing better rust protection after washdown. It is resistant to acids and alkalis encountered during food processing and offers superior resistance to water and steam.
- **NEVASTANE 6** helps to assure long machine life while reducing contamination problems as required by the Hazard Analysis and Critical Control Point System (HACCP).
- **NEVASTANE 6** has been successfully used in applications such as conveyor lines, slides, guides, bearings, chains, and sanitary valves. Industries served include can making, pharmaceutical, bakeries, hospitals, breweries, textiles, fruit and vegetable packers, agriculture, poultry plants, and dairies.
- **NSF H1 Registered meets USDA 1998 H1 Guidelines for incidental contact with food.**
- The **SafeGard Spray System** is environmentally friendly because it uses no ozone depleting agents as propellants. A bladder system and air pressure forces the lubricant out delivering a fine continuous spray that can be sprayed upside down.

- Colorless and odorless.
- Multi-purpose lubricant and penetrant.
- Superior lubricity to white oils.
- Extends equipment life.
- Non-staining.
- Displaces moisture, resists steam and mild acids.

TYPICAL CHARACTERISTICS	METHODS	NEVASTANE 6
NSF Registration Number		127081
Appearance	Visual	Water White Liquid
Film Type		Oily
ISO Viscosity Grade		100
SAE Viscosity Grade		30
Rust Protection, hrs.	ASTM D 130	72
Flash Point, COC, °F(°C)	ASTM D 92	420(217)
Pour Point, °F(°C)	ASTM D 97	-10(-28)

Shelf Life: Use by 60 months or 5 years.

TOTAL Specialties USA, Inc.

Linden, NJ 07036
5 North Stiles Street
1-800-323-3198
www.totalspecialties.com

NEVASTANE 6-2016

This lubricant must be applied as recommended and used for the application for which it was designed. TOTAL Specialties USA, Inc. will have no responsibility for any injury to persons or property resulting from misuse or misapplication of the lubricant. A safety data sheet conforming to the OSHA Hazard Communication Standard 29 CFR Section 1910.1200 can be downloaded at www.totalspecialties.com. Copyright 2016 All rights reserved.