

# NEVASTANE SILICONE SAFEGARD



Food Industry

**Multipurpose Silicone Oil, suitable for incidental food contact.  
In aerosol (207 ml net) with Safeguard Spray System.**

## APPLICATIONS

- **NEVASTANE SILICONE SAFEGARD** contains a high viscosity silicone oil with excellent stability to provide maximum lubrication.
- **NEVASTANE SILICONE SAFEGARD** is multipurpose with a wide operating temperature range (-40°C to +200°C): small machines and chains subject to extreme temperatures, shrink oven chains, conveyors and rails...
- **NEVASTANE SILICONE SAFEGARD** is recommended for the lubrication of numerous applications in food processing industries.

## SPECIFICATIONS

- The formulation of **NEVASTANE SILICONE SAFEGARD** complies with the FDA, 21 CFR, 178.3570.
- **NEVASTANE SILICONE SAFEGARD** is **NSF H1** registered: No 123529.
- **NEVASTANE SILICONE SAFEGARD** is **Kosher** certified.
- **NEVASTANE SILICONE SAFEGARD** is a biostable product, it does not promote the development of bacteria and mould.

## ADVANTAGES

- **NEVASTANE SILICONE SAFEGARD** is recommended for use where incidental contact with food may occur. Using maintenance lubricants which have been registered H1 with NSF minimizes your critical control points as required by HACCP.
- Very good insulating, anti-rust and anti-corrosion properties.
- Very wide temperature range.
- Safeguard technology - spray without propellant gas: environmentally friendly.
- Can be sprayed upside down.

TYPICAL CHARACTERISTICS	METHODS	UNITS	NEVASTANE LUBE AEROSOL
Aspect	Visual	-	Slippery and transparent film
Color	Visual	-	Colorless
Temperature range of use	-	-	from -40°C to +200°C

Above characteristics are mean values given as an information.

### Recommendations:

- Shake well before use
- Hold upright and spray from a distance of about 20 cm
- Shelf life: 3 years from date of manufacture (unopened).

### Cautions:

- Store between 0°C and 50°C
- Do not spray on a naked flame or any incandescent material

TOTAL LUBRIFIANTS  
Industrie & Spécialités  
02-08-2010 (supersedes 16-12-2009)  
NEVASTANE SILICONE SAFEGARD  
1/1



This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.  
A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial adviser or down loaded from [www.quick-fds.com](http://www.quick-fds.com).