



## DESCRIPTION

PEAK Global® LifeTime® Antifreeze + Coolant features an advanced organic acid technology that provides guaranteed lifetime protection for as long as you own your vehicle!\* Its specially-engineered formula will provide maximum protection against damaging rust and corrosion in all automobiles and light/medium duty trucks worldwide, regardless of make, model, year or original antifreeze color.

## FEATURES & BENEFITS

- Provides guaranteed lifetime protection for as long as you own your vehicle when a complete cooling system flush and fill is performed and specified maintenance followed†
- Formulated for use in all American, Asian, and European automobiles
- Features a patented non 2-EH formula that is silicate-free
- Amber color will not change the current antifreeze color when used for topping off

## APPLICATIONS

Engineered for use in all passenger cars, SUVs, motorcycles and light/medium duty trucks, regardless of make, model, year or antifreeze/coolant in the system.

†Requires a complete cooling system flush and fill and regular manufacturer-specified maintenance.

## RECOMMENDED FOR ALL AUTOMOBILES AND LIGHT DUTY TRUCKS WITH THE FOLLOWING ANTIFREEZE SPECIFICATIONS:

- Chrysler MS7170
- Chrysler MS9769
- Chrysler MS12106
- Ford ESE M97B44-A
- Ford WSS-M97B44-D
- Ford WSS-M97B51-A1
- Ford WSS-M97B57-A1
- GM 1825M
- GMW3420
- Mercedes Benz DBL 7700
- ASTM D3306
- ASTM D4985
- ASTM D6210

## FREEZE/BOIL PROTECTION CHART

Coolant/Water Ratio	PROTECTION FROM	
	Freezing Down to	Boiling Up to*
50/50	-34°F (-36°C)	265°F (129°C)
60/40	-62°F (-52°C)	270°F (132°C)
70/30	-84°F (-64°C)	276°F (135°C)

\*At sea level atmospheric pressure with 15lb. pressure cap. The boiling point decreases about 2°F per 1,000 feet of altitude and increases about 2.5°F per pound developed in the system.



PROPERTIES	ASTM Method	TYPICAL VALUES		ASTM D3306 Limits
		CONCENTRATE	PREDILUTED (50/50)	
Appearance/Color	Visual	Amber	Amber	Distinctive
Specific gravity	ASTM D1122	1.113	1.077	1.110-1.145 <sup>1</sup> / 1.065 min <sup>2</sup>
Boiling point <sup>3</sup> , °F (°C), 50 vol %	ASTM D1120	325 (162.8)	229 (109)	226 (108) min.
pH, 50 vol %	ASTM D1287	8.3 <sup>2</sup>	8.3	7.5-11.0
Effect on Automotive Finish	ASTM D1882	No Effect	No Effect	No Effect
Total water, mass %	ASTM D1123	<5	50	5 max <sup>1</sup>
Ash content, mass %	ASTM D1119	<5	<2.5	5 max <sup>1</sup> /2.5 max <sup>2</sup>
Chloride, ppm	ASTM D3634	<25	<25	25 max
Shelf Life, years- unopened original container	--	3	5	--

<sup>1</sup>For concentrate product only, <sup>2</sup>Prediluted (50/50) only, <sup>3</sup>Unpressurized

## SHIPPING INFORMATION

CONCENTRATE



PXA0B1  
55 Gallon  
Concentrate Drum  
0-74804-03397-7

PXA0B3  
1 Gallon  
Concentrated Bottle  
0-74804-00407-6

50/50 PREDILUTED



PXAB51  
55 Gallon  
50/50 Drum  
0-74804-03351-9

PXAB53  
1 Gallon  
50/50 Bottle  
0-74804-00243-0

**To order, please call Old World Industries, LLC Customer Service at 1-800-323-8755.**

Part #	Unit	Pack/Size	Dimensions	Unit Wt (lbs)	Units per Pallet	Pallets per Truck	Pallet Weight**
PXA0B3	Case	6/1 gal	15.8" L x 12.6" W x 12.25" H	60	36	20	2,298
PXAB53	Case	6/1 gal	15.8" L x 12.6" W x 12.25" H	54	36	20	2,082
PXAB51	Drum	55 gal	23.5" dia. x 34.5"	520	4	20	2,277
PXA0B1	Drum	55 gal	23.5" dia. x 34.5"	495	4	20	2,177

\*\*Includes pallet weight of 50 lbs each

## ADDITIONAL INFORMATION

**Testing Requirements:** For proper freeze and boilover protection, use a traditional refractometer or hydrometer to measure the percentage of ethylene glycol by volume.

**Storage Recommendations:** PEAK Global Antifreeze/Coolant can be stored in original container at ambient temperature and limited periods of exposure to temperatures above 95°F (35°C) for 3-5 years, provided the container remains sealed. Product should be agitated before dilution or use.

**Safety and Environmental Guidance:** PEAK Global Antifreeze/Coolant is based on virgin ethylene glycol and should be kept away from children and animals to prevent exposure. A bittering agent is added to help reduce the potential for accidental ingestions of this product. More information with guidance on health, safety and disposal is available on the appropriate Safety Data Sheet, which can be obtained from [peakauto.com](http://peakauto.com). Always dispose of used coolant in accordance with local, state and Federal guidelines.

Old World Industries, LLC  
Northbrook, IL 60062 • 800-323-5440  
[Peakauto.com](http://Peakauto.com)



© 2019 Old World Industries, LLC. All Rights Reserved.  
PEAK, PEAK G Mountain graphic, PEAK GLOBAL and LIFETIME are trademarks of Old World Industries, LLC.  
NASCAR® is a registered trademark of the National Association for Stock Car Auto Racing, Inc.  
NHRA and the NHRA oval band logo are trademarks of National Hot Rod Association and are used with permission. All rights reserved.