



## Hydraulic/Tractor Fluid

76® Hydraulic/Tractor Fluid is a multifunctional fluid specially formulated for use in farm tractors and other off-highway equipment requiring one lubricant for the transmission, final drive, wet brakes and hydraulic systems. It meets the performance requirements of all major brands of farm tractors and other farm equipment that utilize a common fluid reservoir.

Hydraulic/Tractor Fluid is formulated to provide excellent oxidation resistance, excellent wear protection, protection against rust and corrosion, and resistance to foaming. It has carefully balanced frictional properties to ensure proper operation of wet brakes and transmission clutches.

Hydraulic/Tractor Fluid is available in two viscosity grades for use over a wide range of temperatures. The heavier viscosity grade is suitable for year-round use in most climates, whereas the “Low Viscosity” grade is recommended for use in cold climates where a John Deere J20D fluid is specified.

### **Applications**

Hydraulic/Tractor Fluid is recommended for use where the equipment manufacturer specifies:

- AGCO Power Fluid 821XL, Q-1826, Q-1802 (Type 55 Fluid), Q-1766B
- Case IH MS1210, MS1209, MS1207, MS1206
- Case New Holland (CNH) MAT3525 (134-D Fluid), MAT3506, MAT3505
- Caterpillar TO-2 (obsolete)
- Denison Hydraulics HF-0, HF-1, HF-2
- Ford ESN-M2C134-D, ESN-M2C86-C, ESN-M2C86-B, ESN-M2C41-B
- Ford-New Holland FNHA-2-C-201.00
- John Deere JDM J20C, J20D (“Low Viscosity” grade), J14C (Type 303 Fluid)
- Kubota UDT Fluid
- Landini Tractor II Hydraulic Fluid
- Massey Ferguson CMS M1145/M1143, M1141, M1135, M1129A
- Sundstrand Hydrostatic Transmission Fluid
- Vickers (Eaton) M-2950-S, I-286-S
- Volvo VME WB 101 (VCE 1273.03)
- ZF TE-ML 03E, 05F, 17E

**Multipurpose  
Hydraulic/  
Transmission/  
Final Drive Fluid  
For Farm Tractors**

### **CONTACT INFORMATION**

**Phillips66  
Lubricants.com**

U.S. Customer  
Service:  
**1-800-368-7128**

Technical Hotline:  
**1-877-445-9198**

International  
Customer Service:  
**1-832-765-2500**

E-mail address:  
**76lubricants@  
p66.com**

Hydraulic/Tractor Fluid also meets API GL-4 performance requirements.

### Features/Benefits

- Excellent oxidation resistance and thermal stability
- Excellent wear protection for clutches, gears and hydraulic pumps
- Prevents brake chatter and grabbing
- Protects against rust and corrosion
- Excellent seal compatibility
- Good foam resistance
- Two viscosity grades for use in most climates

### Hydraulic/Tractor Fluid

#### Typical Properties

Grade	—	Low Vis
Specific Gravity @ 60°F	0.868	0.864
Density, lbs/gal @ 60°F	7.23	7.19
Color, ASTM D1500	3.5	3.5
Flash Point (COC), °C (°F)	210 (410)	190 (374)
Pour Point, °C (°F)	-43 (-45)	-51 (-60)
Viscosity, Brookfield		
cP @ -20°C	2,800	—
cP @ -35°C	26,700	—
cP @ -40°C	—	11,500
Viscosity, Kinematic		
cSt @ 40°C	61.0	34.3
cSt @ 100°C	9.3	7.4
Viscosity Index	132	190
Ash, Sulfated, ASTM D874, wt %	1.41	1.41
Total Base Number, ASTM D2896	9.6	9.6
Zinc, wt %	0.149	0.149

### Health and Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet via <http://w3apps.phillips66.com/NetMSDS>.