



Megaplex® XD5

Megaplex XD5 is a high-performance, multipurpose, extreme-pressure (EP) lithium complex grease developed to satisfy the severe lubrication requirements of mining and off-road equipment manufactured by Caterpillar, Terex, Komatsu Dresser and others. It is particularly recommended for use in AC and DC electric-drive haul trucks, cranes, scrapers, shovels and drag lines operating in severe service under heavy or shock loads.

Megaplex XD5 is manufactured with high-quality base oils, a special polymer and a lithium complex soap thickener. It is fortified with extreme-pressure and antiwear additives, 5% molybdenum disulfide (moly), a tackifier, and rust and oxidation inhibitors to provide excellent wear protection as well as excellent corrosion protection and resistance to water washout in equipment operating under wet conditions and/or high temperatures and subject to heavy or shock loading.

Megaplex XD5 Grades No. 0 and No. 1W are formulated with lower-viscosity base oils than the other two grades for better pumpability at low ambient temperatures.

Applications

- Chassis parts and wheel bearings on mining and other off-highway equipment
- Hydraulic excavator mining shovels, such as Caterpillar 5100 & 5200 series
- Mine haul trucks
- Heavily loaded plain and rolling-element bearings in industrial and mobile equipment where the manufacturer specifies a high-temperature, extreme-pressure grease with 5% moly

Features/Benefits

- High dropping point (500°F)
- High load-carrying capacity
- Excellent wear protection
- Contains 5% moly for extra protection against galling and wear under shock loads
- Excellent resistance to water washout
- Excellent resistance to separation
- Protects against rust and corrosion

**Extreme-Pressure
Lithium Complex
Grease With
5% Moly For
Mining &
Off-Road
Equipment**

CONTACT INFORMATION

**Phillips66
Lubricants.com**

U.S. Customer
Service:
1-800-368-7128

Technical Hotline:
1-877-445-9198

International
Customer Service:
1-832-765-2500

E-mail address:
**lubricants@
p66.com**



Megaplex® XD5

Typical Properties

NLGI Grade	0	1W	1	2
Thickener	Lithium Complex	Lithium Complex	Lithium Complex	Lithium Complex
Color	Gray-Black	Gray-Black	Gray-Black	Gray-Black
Dropping Point, °C (°F)	260 (500)	260 (500)	260 (500)	260 (500)
Density, lbs/gal	7.92	7.92	7.96	7.99
Penetration, Worked (60 strokes),				
ASTM D217	355-385	310-340	310-340	265-295
Texture	Tacky	Tacky	Tacky	Tacky
Molybdenum Disulfide, wt %	5	5	5	5
Four-Ball EP, ASTM D2596, Weld Load, kgf	315	315	315	400
Four-Ball Wear, ASTM D2266,				
Scar Diameter, mm	0.50	0.65	0.50	0.50
Oxidation Stability, ASTM D942, 100 hrs,				
Pressure Drop, psi (kPa)	4 (28)	4 (28)	4 (28)	4 (28)
Rust Prevention, ASTM D1743	Pass	Pass	Pass	Pass
Timken OK Load, ASTM D2509, lb	55	50	55	55
Base Oil Properties:				
Viscosity (with polymer),				
cSt @ 40°C	180	140	245	470
cSt @ 100°C	13.7	13.0	19.0	30.0
SUS @ 100°F	962	739	1,304	2,526
SUS @ 210°F	75	72	97	147
Viscosity Index	60	83	86	92
Operating Temperature Range,				
°C	-34 to 149	-34 to 149	-29 to 177	-18 to 177
°F	-30 to 300	-30 to 300	-20 to 350	0 to 350

Health and Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet via <http://w3apps.phillips66.com/NetMSDS>.

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

© 2012 Phillips 66 Company, Phillips 66, 76, Conoco, Liquid Titanium and their respective logos and products are trademarks of Phillips 66 Company in the U.S.A. and other countries.