

RE-ORDER THIS PRODUCT



petroleumservicecompany.com  
(570) 822-1151



## Rock Drill Oil

Rock Drill Oil is an adhesive, extreme-pressure (EP) lubricant specially developed for the lubrication of air-powered tools such as rock drills, jackhammers, pavement breakers and drifters. It also is recommended for the lubrication of mining and industrial equipment operating in wet environments.

Rock Drill Oil is formulated with high-quality paraffinic base oils and a specially tailored additive package to provide excellent protection for pneumatic percussion tools. It has high load-carrying capacity to protect against wear and seizure of sliding metal surfaces under heavy or shock-load conditions. It has good adhesion to metal surfaces in the presence of moisture, and provides protection against rust and corrosion. It also has good oxidation resistance and thermal stability at high temperatures for long service life.

### **Applications**

- Pneumatic percussion tools such as jackhammers, pavement breakers and rock drills
- Mining equipment such as demolition hammers, chipping hammers and drifters
- Enclosed industrial gearboxes where leakage is a problem

### **Features/Benefits**

- Excellent extreme-pressure properties
- Protects against wear and seizure
- Good adhesion to metal surfaces in the presence of moisture
- Resists dripping and leakage
- Good oxidation resistance and thermal stability
- Protects against rust and corrosion
- Low odor
- Good foam resistance
- Seven viscosity grades for use over a wide range of temperatures

**Adhesive,  
Extreme-Pressure  
Air Tool Lubricant**

### **CONTACT INFORMATION**

**Phillips66  
Lubricants.com**

U.S. Customer  
Service:  
**1-800-368-7128**

Technical Hotline:  
**1-877-445-9198**

International  
Customer Service:  
**1-832-765-2500**

E-mail address:  
**lubricants@  
p66.com**



## Rock Drill Oil

### Typical Properties

ISO Grade	32	46	68	100	150	220	320
Specific Gravity @ 60°F	0.865	0.870	0.875	0.880	0.885	0.889	0.893
Density, lbs/gal @ 60°F	7.20	7.25	7.29	7.33	7.37	7.40	7.44
Color, ASTM D1500	1.5	1.5	2.0	2.5	3.0	3.5	4.0
Flash Point (COC),							
°C	198	215	218	222	228	234	243
°F	388	419	424	432	442	453	469
Pour Point,							
°C	-37	-37	-27	-27	-21	-18	-18
°F	-35	-35	-17	-17	-6	0	0
Viscosity,							
cSt @ 40°C	32.0	46.0	68.0	100	150	220	320
cSt @ 100°C	5.7	7.2	9.3	12.3	15.7	20.2	25.2
SUS @ 100°F	165	236	351	518	784	1,158	1,698
SUS @ 210°F	45.3	50.3	57.6	68.8	82.6	102	125
Viscosity Index	119	117	114	115	108	106	102
Acid Number, ASTM D664, mg KOH/g	0.68	0.68	0.68	0.68	0.68	0.68	0.68
Falex EP Load, ASTM D3233, lbf	2,250	2,250	2,250	2,250	2,250	2,250	2,250
Foam Test, ASTM D892	Pass	Pass	Pass	Pass	Pass	Pass	Pass
Four-Ball Wear, ASTM D4172,							
Scar Diameter, mm	0.37	0.37	0.37	0.37	0.37	0.37	0.37
Four-Ball Weld Load, ASTM D2783, kgf	300	300	300	300	300	300	300
Rust Test, ASTM D665 A	Pass	Pass	Pass	Pass	Pass	Pass	Pass
Timken OK Load, ASTM D2782, lb	60	60	60	60	60	60	60

### Health and Safety Information

For recommendations on safe handling and use of this product, please refer to the Material Safety Data Sheet via <http://w3apps.phillips66.com/NetMSDS>.

Typical properties are average values only and do not constitute a specification. Minor variations that do not affect product performance are to be expected during normal manufacture, and at different blending locations. Product formulations are subject to change without notification.

© 2012 Phillips 66 Company, Phillips 66, 76, Conoco, Liquid Titanium and their respective logos and products are trademarks of Phillips 66 Company in the U.S.A. and other countries.