

TITAN SINTOPOID FE SAE 75W-85

Premium Performance fuel-economy passenger car axle fluid offering increased gear-box efficiency in passenger cars due to low viscosity level. Reduces fuel consumption and offers best properties at low temperature. Suitable as fill for life fluid according to manufacturer.

Description

TITAN SINTOPOID FE SAE 75W-85 is being produced based on a modern, OEM-proven additive technology with multiple application profiles embedded into a nearly shear-free base oil matrix. Special Friction Modifiers reduce power losses in gears and bearings due to friction, by that increase the gearbox efficiency and in parallel ensure the performance of limited slip differentials. The operating temperature of the oil sump is being reduced significantly during constant operation. TITAN SINTOPOID FE SAE 75W-85 has been developed in cooperation with a leading automotive manufacturer and has been tested thoroughly.

Application

TITAN SINTOPOID FE SAE 75W-85 is miscible and compatible with conventional branded gear oils. However, mixing with other gear oils should be avoided in order to fully utilize the product's benefits. A complete oil change is recommended when converting to TITAN SINTOPOID FE SAE 75W-85. For information on product safety and proper disposal please refer to the latest Material Safety Data Sheet.

Advantages/Benefits

- Offers the benefit of fuel economy to customers.
- Rationalization of product diversity to one FE-MTF- product with several application opportunities, also for limited slip differentials (LS-Function).
- Offers reliable operation under high stress (without
- shear loss of viscosity) in rear axle gearboxes during the whole oil operation interval (Fill-for-life).
- Prevents reliably from wear, sludge formation, ag- glomeration and corrosion.
- Offers an outstanding viscosity temperature behaviour lying above the performance of many normal service gearbox lubricants, thus ensuring lubrication at very low as well as very high operation temperatures.
- Thermally highly stable and does not foam even under highest stress.
- Compatible with many elastomers and other sealant materials.
- Depending on OEM requirements also suitable for
- selected transmissions in hybrid and electric vehicles.

Specifications

- API GL-5

Approvals

- MB-APPROVAL 235.7
- MB-APPROVAL 235.74
- MB-APPROVAL 239.72
- ZF TE-ML 18 (ZF002195)

FUCHS Recommendations

See Page 2



FUCHS Recommendations

- MB 239.71
- VW TL 521 45-X (G 052 145 A1)
- VW TL 521 90 (G 052 190 A2/ G 055 190 A2)

TYPICAL CHARACTERISTICS

Density at 15 °C	DIN 51757	0.854 g/ml
SAE grade	SAE J306	75W-85
Kinematic Viscosity at 40°C	DIN 51562-1	78.0 mm ² /s
Kinematic Viscosity at 100°C	DIN 51562-1	12.0 mm ² /s
Viscosity Index	DIN ISO 2909	149
Pourpoint	DIN ISO 3016	-45 °C
Product dyeing	DIN 10964	none

Product Information



The information contained in this brochure is based on the experience and know-how of FUCHS LUBRICANTS CO. in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pre-treatment, possible external contamination, etc.

For this reason, universally-valid statements about the function of our products are not possible. The information given in this Product Information sheet represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application.

We therefore recommend you consult a FUCHS LUBRICANTS CO. Application Engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care.

Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our Product Information sheets at any time and without warning. With the publication of this Product Information sheet, all previous editions cease to be valid.

ANY FORM OF REPRODUCTIONS REQUIRES EXPRESS PRIOR WRITTEN PERMISSION FROM FUCHS LUBRICANTS CO.

© FUCHS LUBRICANTS CO. All rights reserved.