



SAFETY DATA SHEET

Revision Date 26-Sep-2018

Version 4

1. IDENTIFICATION

Product identifier

Product Name 135EA HEAVY DUTY RUBBERIZED UNDERCOATING 16OZ AE

Other means of identification

Product Code 81833

Recommended use of the chemical and restrictions on use

Recommended Use Undercoating - Aerosol

Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address

ITW Permatex
6875 Parkland Blvd.
Solon, OH 44139 USA

May Also Be Distributed by:

ITW Permatex Canada
101-2360 Bristol Circle
Oakville, ON Canada L6H 6M5
Telephone: (800) 924-6994

24-hour emergency phone number

Chem-Tel: 800-255-3924
International Emergency:
00+1+ 813-248-0585
Contract Number: MIS0003453

E-mail address: mail@permatex.com

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Skin corrosion/irritation	Category 2
Reproductive toxicity	Category 2
Specific target organ toxicity (repeated exposure)	Category 1
Aspiration toxicity	Category 1
Flammable aerosols	Category 1
Gases under pressure	Liquefied gas

Label elements

Emergency Overview

Signal word

Danger

Causes skin irritation
Suspected of damaging fertility or the unborn child
Causes damage to organs through prolonged or repeated exposure
May be fatal if swallowed and enters airways
Extremely flammable aerosol
Contains gas under pressure; may explode if heated



Appearance Black

Physical state Flammable Aerosol

Odor Solvent

Precautionary Statements - Prevention

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Use personal protective equipment as required
Wash face, hands and any exposed skin thoroughly after handling
Do not breathe dust/fume/gas/mist/vapors/spray
Do not eat, drink or smoke when using this product
Keep away from heat/sparks/open flames/hot surfaces. - No smoking
Do not spray on an open flame or other ignition source
Pressurized container: Do not pierce or burn, even after use

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention
IF ON SKIN: Wash with plenty of soap and water
If skin irritation occurs: Get medical advice/attention
Take off contaminated clothing and wash before reuse
IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
Do NOT induce vomiting

Precautionary Statements - Storage

Store locked up
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

- Not applicable

Unknown acute toxicity

26 % of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance(s)

Chemical Name	CAS No	Weight-%
PROPANE	74-98-6	10 - 30
TOLUENE	108-88-3	10 - 30
STODDARD SOLVENT	8052-41-3	3 - 7
BUTANE	106-97-8	3 - 7
ACETONE	67-64-1	3 - 7

4. FIRST AID MEASURES

Description of first aid measures

General advice	Get medical advice/attention if you feel unwell.
Eye contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Skin contact	IF ON SKIN: Wash skin with soap and water. If skin irritation persists, call a physician. Take off contaminated clothing and wash before reuse.
Inhalation	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If symptoms persist, call a physician.
Ingestion	IF SWALLOWED: Call a physician or poison control center immediately. Do NOT induce vomiting.
Self-protection of the first aider	Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves.

Most important symptoms and effects, both acute and delayed

Symptoms See section 2 for more information.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Carbon dioxide (CO₂), Dry chemical, Foam

Unsuitable extinguishing media

None

Specific hazards arising from the chemical

Extremely flammable. Heating causes rise in pressure with risk of bursting.

Explosion data

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Do not puncture or incinerate cans. Ensure adequate ventilation, especially in confined areas. Avoid contact with eyes and skin. Use personal protective equipment as required.

Other Information Ventilate the area.

Environmental precautions

Environmental precautions See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

- Methods for containment** Prevent further leakage or spillage if safe to do so.
- Methods for cleaning up** Eliminate all ignition sources if safe to do so. Ensure adequate ventilation. Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.
- Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Contents under pressure. Do not puncture or incinerate cans. Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapors or mists. Avoid contact with skin, eyes or clothing. Wash thoroughly after handling. Wash contaminated clothing before reuse. Use personal protective equipment as required.

Conditions for safe storage, including any incompatibilities

- Storage Conditions** Store locked up. Do not expose to temperatures exceeding 50 °C/122 °F.
- Incompatible materials** Nitrates, Fluorine, Chlorine, Strong oxidizing agents

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
PROPANE 74-98-6	: See Appendix F: Minimal Oxygen Content	TWA: 1000 ppm TWA: 1800 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1800 mg/m ³	IDLH: 2100 ppm TWA: 1000 ppm TWA: 1800 mg/m ³
TOLUENE 108-88-3	TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m ³ Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 560 mg/m ³
STODDARD SOLVENT 8052-41-3	TWA: 100 ppm	TWA: 500 ppm TWA: 2900 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 525 mg/m ³	IDLH: 20000 mg/m ³ Ceiling: 1800 mg/m ³ 15 min TWA: 350 mg/m ³
BUTANE 106-97-8	STEL: 1000 ppm	(vacated) TWA: 800 ppm (vacated) TWA: 1900 mg/m ³	TWA: 800 ppm TWA: 1900 mg/m ³
ACETONE 67-64-1	STEL: 500 ppm TWA: 250 ppm	TWA: 1000 ppm TWA: 2400 mg/m ³ (vacated) TWA: 750 ppm (vacated) TWA: 1800 mg/m ³ (vacated) STEL: 2400 mg/m ³ The acetone STEL does not apply to the cellulose acetate fiber industry. It is in effect for all other sectors (vacated) STEL: 1000 ppm	IDLH: 2500 ppm TWA: 250 ppm TWA: 590 mg/m ³

NIOSH IDLH *Immediately Dangerous to Life or Health*

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers
 Eyewash stations
 Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).
Skin and body protection Wear protective natural rubber, nitrile rubber, Neoprene™ or PVC gloves.
Respiratory protection Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as appropriate.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Flammable Aerosol
Appearance Black
Odor Solvent
Odor threshold No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No information available	
Melting point / freezing point	No information available	
Boiling point / boiling range	249 °C / 480 °F	
Flash point	-104 °C / -155 °F	Gives a flame projection at full valve opening or flashback at any degree of valve opening
Evaporation rate	No information available	
Flammability (solid, gas)	No information available	
Flammability Limit in Air		
Upper flammability limit:	8.8%	
Lower flammability limit:	1.6%	
Vapor pressure	70-80 psig @ 20°C (68°F)	
Vapor density	No information available	
Relative density	0.906	
Water solubility	No information available	
Solubility in other solvents	No information available	
Partition coefficient	No information available	
Autoignition temperature	480°C (896°F)	
Decomposition temperature	No information available	
Kinematic viscosity	No information available	
Dynamic viscosity	No information available	
Explosive properties	No information available	
Oxidizing properties	No information available	

Other Information

Softening point No information available
Molecular weight No information available
VOC Content (%) 39.5%
Density No information available
Bulk density No information available

10. STABILITY AND REACTIVITY

Reactivity
Stable under normal conditions

Chemical stability

Stable under recommended storage conditions

Possibility of Hazardous Reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

Incompatible materials

Nitrates, Fluorine, Chlorine, Strong oxidizing agents

Hazardous Decomposition Products

Carbon oxides

Oxides of sulfur

Hydrogen sulfide

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation	Causes damage to organs if inhaled.
Eye contact	Contact with eyes may cause irritation. May cause redness and tearing of the eyes.
Skin contact	May cause skin irritation and/or dermatitis.
Ingestion	Potential for aspiration if swallowed. Aspiration may cause pulmonary edema and pneumonitis.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
PROPANE 74-98-6	-	-	= 658 mg/L (Rat) 4 h
TOLUENE 108-88-3	= 2600 mg/kg (Rat)	= 12000 mg/kg (Rabbit)	= 12.5 mg/L (Rat) 4 h
BUTANE 106-97-8	-	-	= 658 g/m ³ (Rat) 4 h
ACETONE 67-64-1	= 5800 mg/kg (Rat)	-	= 50100 mg/m ³ (Rat) 8 h

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.
Germ cell mutagenicity No information available.
Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical Name	ACGIH	IARC	NTP	OSHA
TOLUENE 108-88-3	-	Group 3	-	-

*IARC (International Agency for Research on Cancer)
 Group 2A - Probably Carcinogenic to Humans
 Not classifiable as a human carcinogen
 Group 2B - Possibly Carcinogenic to Humans
 OSHA (Occupational Safety and Health Administration of the US Department of Labor)
 X - Present*

Chronic toxicity May cause adverse liver effects.
Target Organ Effects Central nervous system, Central Vascular System (CVS), Eyes, kidney, Liver, Respiratory system, Skin.

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral)	8194 mg/kg
ATEmix (dermal)	8629 mg/kg
ATEmix (inhalation-gas)	1178650 mg/l
ATEmix (inhalation-dust/mist)	78.1 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

68 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility

No information available.

Chemical Name	Partition coefficient
PROPANE 74-98-6	2.3
TOLUENE 108-88-3	2.7
BUTANE 106-97-8	2.89
ACETONE 67-64-1	-0.24

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes This material, as supplied, is a hazardous waste according to federal regulations (40 CFR 261).

Contaminated packaging Do not reuse container.

US EPA Waste Number D001

Chemical Name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
TOLUENE 108-88-3	-	-	Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying	-

			amounts and positions of chlorine substitution.	
--	--	--	---	--

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste Status
TOLUENE 108-88-3	Toxic Ignitable
ACETONE 67-64-1	Ignitable

14. TRANSPORT INFORMATION

DOT

UN/ID No 1950
 Proper shipping name: Aerosols, Limited Quantity (LQ)
 Hazard Class 2.1
 Emergency Response Guide Number 126

IATA

UN/ID No ID 8000
 Proper shipping name: Consumer commodity
 Hazard Class 9
 ERG Code 9L

IMDG

UN/ID No 1950
 Proper shipping name: Aerosols, Limited Quantity (LQ)
 Hazard Class 2
 EmS-No F-D, S-U

15. REGULATORY INFORMATION

International Inventories

TSCA Complies
 DSL/NDSL Complies
 EINECS/ELINCS Not determined
 ENCS Not determined
 IECSC Not determined
 KECL Not determined
 PICCS Not determined
 AICS Not determined

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
 DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
 EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
 ENCS - Japan Existing and New Chemical Substances
 IECSC - China Inventory of Existing Chemical Substances
 KECL - Korean Existing and Evaluated Chemical Substances
 PICCS - Philippines Inventory of Chemicals and Chemical Substances
 AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	SARA 313 - Threshold Values %
---------------	-------------------------------

TOLUENE - 108-88-3	1.0
--------------------	-----

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	Yes
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
TOLUENE 108-88-3	1000 lb	X	X	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
TOLUENE 108-88-3	1000 lb 1 lb	-	RQ 1000 lb final RQ RQ 454 kg final RQ 1 lb final RQ RQ 0.454 kg final RQ
ACETONE 67-64-1	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ

US State Regulations

California Proposition 65

WARNING: This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm

Chemical Name	California Proposition 65
TOLUENE - 108-88-3	Developmental

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
PROPANE 74-98-6	X	X	X
ASPHALT (PETROLEUM) 8052-42-4	X	X	X
TOLUENE 108-88-3	X	X	X
TALC 14807-96-6	X	X	X
ACETONE 67-64-1	X	X	X
KAOLIN 1332-58-7	X	X	X
BUTANE 106-97-8	X	X	X
STODDARD SOLVENT 8052-41-3	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

WHMIS Hazard Class

A Compressed gases, B5 - Flammable aerosol, D2B - Toxic materials

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA	Health hazards 2	Flammability 3	Instability 0	-
HMIS	Health hazards 2	Flammability 3	Physical hazards 0	Personal protection B

NFPA (National Fire Protection Association)
HMIS (Hazardous Material Information System)

Revision Date 26-Sep-2018

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet