


# Sunoco 260 GTX™

Sunoco 260 GTX™ is a great fuel choice for racing applications that need more detonation protection than pump gas provides, yet cannot use a leaded fuel. It has been shown to produce repeatable power levels in high horsepower small block V8 racing engines with compression ratios up to 12:1, and will tolerate more compression in engines with smaller or more efficient combustion chambers.

260 GTX is not a street legal fuel and is for off-road use only. It does not contain oxygenates or metallic additives and it will not harm oxygen sensors. It is an excellent choice where the use of oxygenates such as alcohols and ethers are restricted by the engine manufacturer or racing organization.

Sunoco 260 GTX contains additives to enhance shelf life and engine cleanliness. Like any gasoline, it should be stored in opaque, tightly sealed containers where the temperature is stable. Handled under such conditions, the shelf life of 260 GTX is in excess of 2 years.



<b>TYPICAL PROPERTIES</b>	
COLOR .....	<b>GREEN</b>
OCTANE NUMBER (R+M)/2 .....	<b>98</b>
RESEARCH OCTANE NUMBER (RON) .....	<b>103</b>
MOTOR OCTANE NUMBER (MON) .....	<b>93</b>
SPECIFIC GRAVITY .....	<b>0.762</b>
DENSITY (POUNDS/GALLON) .....	<b>6.3</b>
REID VAPOR PRESSURE (PSI) .....	<b>4.7</b>
ASTM D86 DISTILLATION (DEGREES F)	
10% EVAPORATED .....	<b>182</b>
50% EVAPORATED .....	<b>220</b>
90% EVAPORATED .....	<b>227</b>
STOICHIOMETRIC AIR/FUEL RATIO .....	<b>14.6</b>
OXYGEN (WEIGHT %) .....	<b>0.0</b>
H/C RATIO.....	<b>1.76</b>
LOWER HEATING VALUE (BTU/LB) .....	<b>18,240</b>
LOWER HEATING VALUE (BTU/GAL) .....	<b>115,800</b>
LEADED.....	<b>NO</b>

For off-road and racing applications only. Legal in California only for racing vehicles in sanctioned racing events.



**SUNOCO PERFORMANCE PRODUCTS**  
**PO BOX 1226 • LINWOOD, PA 19061**  
**WWW.SUNOCORACEFUELS.COM**  
**1.800.RACE.GAS**