


Sunoco 260 GT™

Sunoco 260 GT™ is an oxygenated, unleaded gasoline designed for high performance street cars, muscle cars, classics, street rods, and the like. It is street-legal in most states except California. With a 100 octane rating, Sunoco 260 GT will allow increased boost levels in supercharged or turbocharged applications compared to typical “pump” gas.

Sunoco 260 GT will not harm catalytic converters or oxygen sensors. 260 GT contains a comprehensive additive package for greater engine protection and reduced fuel system deposits. It is compatible with two-stroke synthetic and mineral-based engine oils. As with any gasoline, it should be stored in opaque, tightly sealed containers and kept where temperatures are stable. Properly stored, the shelf life of 260 GT is in excess of 1 year.



TYPICAL PROPERTIES	
COLOR	NOT DYED
OCTANE NUMBER (R+M)/2	100
RESEARCH OCTANE NUMBER (RON)	105
MOTOR OCTANE NUMBER (MON)	95
SPECIFIC GRAVITY	0.734
DENSITY (POUNDS/GALLON)	6.1
REID VAPOR PRESSURE (PSI)	6.4
DISTILLATION (DEGREES F)	
INITIAL BOILING POINT	112
10% EVAPORATED	145
50% EVAPORATED	211
90% EVAPORATED	216
FINAL BOILING POINT	236
STOICHIOMETRIC AIR/FUEL RATIO	14.1
OXYGEN (WEIGHT %)	3.7
ETHANOL (VOLUME %)	9.8
H/C RATIO	2.02
O/C RATIO	0.034
LOWER HEATING VALUE (BTU/LB)	17,900
LOWER HEATING VALUE (BTU/GAL)	109,200
LEADED	NO
STREET LEGAL	IN MOST STATES

Legal in California only for racing vehicles in sanctioned racing events.



SUNOCO PERFORMANCE PRODUCTS
PO BOX 1226 • LINWOOD, PA 19061
WWW.SUNOCORACEFUELS.COM
1.800.RACE.GAS