


Sunoco DXP™

Sunoco DXP was developed to exceed the needs of engines that push bore size, high compression ratios and extreme rpm levels. Sunoco DXP delivers extra protection against detonation during the best atmospheric conditions for improved performance within a demanding feature race or endurance events. This precision blends allows for greater durability and reduced wear in today's top level race engines.

Sunoco DXP is for off-road and racing use only. It contains additives to enhance stability and minimize oxidative effects. As with any gasoline, DXP should be stored in opaque, tightly sealed containers where temperatures are stable. Handled under such conditions, the shelf life of Sunoco DXP is 3 years or more.



TYPICAL PROPERTIES	
COLOR	GREEN
OCTANE NUMBER (R+M)/2	116
RESEARCH OCTANE NUMBER (RON)	119
MOTOR OCTANE NUMBER (MON)	113
SPECIFIC GRAVITY	0.735
DENSITY (POUNDS/GALLON)	6.1
REID VAPOR PRESSURE (PSI)	5.0
DISTILLATION (DEGREES F)	
10% EVAPORATED	178
50% EVAPORATED	216
90% EVAPORATED	225
STOICHIOMETRIC AIR/FUEL RATIO	14.9
OXYGEN (WEIGHT %)	0.0
H/C RATIO.....	2.07
LOWER HEATING VALUE (BTU/LB)	18,600
LOWER HEATING VALUE (BTU/GAL)	113,100
DIELECTRIC CONSTANT	0.2
LEADED.....	YES

For off-road and racing applications only. Legal in California only for racing vehicles in sanctioned racing events.



SUNOCO PERFORMANCE PRODUCTS
PO BOX 1226 • LINWOOD, PA 19061
WWW.SUNOCORACEFUELS.COM
1.800.RACE.GAS