



Lubricants
United States



SUNOCO ROCK DRILL OILS

Introduction

SUNOCO ROCK DRILL OILS are heavily compounded oils designed for the lubrication of pneumatic equipment exposed to excessive moisture or water spray. They are manufactured using premium quality mineral oils and special additive packages designed for heavy-duty rock drill applications. These additive systems employ excellent extreme pressure protection as well as rust and corrosion protection, tackiness, and antifoam properties.

Advantages

SUNOCO ROCK DRILL OILS provide good adhesion to metal surfaces in the presence of moisture, have excellent extreme-pressure properties and offer exceptional protection against wear, rust, corrosion, and foaming.

Applications

SUNOCO ROCK DRILL OILS are recommended for and meet the general requirements of major manufactures of jack hammers, rock drills and other makes of pneumatic percussion equipment manufactured by Gardner-Denver, Ingersoll-Rand, and most others.

Typical Properties

	PRODUCT CODES	6403	6223	6233	6243
	ISO GRADE	100	150	220	320
Viscosity, cSt @40 °C (D445)		100	150	220	320
Viscosity, cSt @100 °C (D445)		10.8	12.0	19.3	24.0
Viscosity Index (D2270)		98	93	96	95
Flash Point, COC °F (D92)		420	435	450	450
Corrosion, ASTM D130		1B	1B	1B	1B
Timken EP Test, lbs., ASTM D2782		60	60	60	60
Falex Load Test, lbs., ASTM D3233		2200	2200	2200	2200
Steam Emulsion No., ASTM D1935		1200+	1200+	1200+	1200+
Gravity, ° API		28.9	28.0	27.9	25.7

www.sunocolubes.com

Sales: sales@sunocolubes.com

Technical Questions: technical@sunocolubes.com

Customer Service & Sales: 800-660-0761 PO BOX 16270 Philadelphia, PA 19154