



Lubricants  
United States



## SUNOCO ULTRA dexos1/SN/GF Engine Oils



### Overview

SUNOCO ULTRA dexos1/SN/GF engine oils are specifically formulated for and licensed by General Motors to meet their new Global Engine Oil Specification. Offered in synthetic blend and full synthetic (5W-30 grade only) formulations, these engine oils utilize advanced additive technology which exceeds the requirements of General Motors' specification. SUNOCO ULTRA dexos1/SN/GF engine oils meet or exceeds the latest API SN and ILSAC GF-5 specifications as well as all previous service classifications API SM, SL and ILSAC GF-4 and GF-3

### Applications

SUNOCO ULTRA dexos1/SN/GF engine oils are scientifically proven to provide protection longer than conventional SN/GF-5 products. Their dedicated additive package ensures a more shear-stable product, a heightened resistance to high temperature burn-off, and excellent detergency. The use of the highest quality conventional and fully synthetic base stocks contributes to SUNOCO ULTRA dexos1/SN/GF engine oil's excellent oxidation stability and corrosion inhibition for long engine life.

### Features & Benefits

SUNOCO ULTRA dexos1/SN/GF engine oils are premium quality motor oils designed to meet the most demanding lubrication requirements of today's naturally aspirated, turbo-charged and super-charged gasoline fueled engines. These oils are specially formulated to provide excellent oxidation stability, increase wear protection, excellent low temperature flow properties, reduce oil consumption and enhance fuel economy. GM License Nos. RR1E0930113, RR1E0927113, & RR1E0929113.

### Specifications

5W-30: API SN, SM, SL, SJ • ACEA A1 • ILSAC GF-5, GF-4, GF-3 • GM 6094M, GM 4718M • Ford M2C946-A • Daimler Chrysler 10796, MS 6395M

5W-20: API SN, SM, SL, SJ • ACEA A1 • ILSAC GF-5, GF-4, GF-3 • GM 4718M • Ford M2C153H, M2C914-A, M2C945-A • Daimler Chrysler 10796, MS 6395M

### Typical Properties

Product Code	5793	5973	5933	5783
License No.	RR1E0923113	RR1E0930113	RR1E0927113	RR1E0929113
SAE Viscosity Grade	0W-20 Full Syn	5W-20 - Full Syn	5W-30 - Full Syn	5W-30 - Syn Blend
Viscosity, cSt @ 100 °C	8.2	8.71	11.0	11.3
Viscosity, cSt @ 40 °C	43	51.3	63	67
Viscosity, CCS, cP @ °C	5600 (-35)	4900 (-30)	4900 (-30)	5600 (-30)
Viscosity Index	170	148	165	162
NOACK, wt.%	12.5	12.0	11.0	12.6
HT/HS, Cp @150°C	2.6	2.6	3.1	3.1
Flash Point, °C	220	220	220	220
Pour Point, °C	-51	-45	-45	-43
Phosphorous, wt.%	0.074	0.074	0.074	0.074
Density	7.09	7.10	7.10	7.10
Zinc, wt%	0.084	0.084	0.084	0.084