



SUNOCO TH FLUID

OVERVIEW

SUNOCO TH FLUID is a premium, high quality universal tractor hydraulic fluid for use in transmissions, final drives and hydraulic systems of all major brands of tractors and other farm equipment using a common fluid reservoir. This fluid incorporates the latest additive chemistry to provide maximum protection for all systems requiring a universal fluid.

FEATURES & BENEFITS

SUNOCO TH FLUID has enhanced friction properties that optimize clutch and PTO performance, improves PTO chatter control and has excellent clutch and elastomers compatibility. It has a high viscosity index and is very shear stable while offering improved wet brakes control and excellent protection against rust, corrosion and yellow metal etching. SUNOCO TH FLUID has exceptional low temperature, anti-wear, and extreme pressure properties to protect key components.

APPLICATIONS

SUNOCO TH FLUID is designed for heavy duty transmissions, differentials, final drives, hydraulic systems, power steering systems, wet brakes, PTO's and hydrostatic drives. Suitable for top-up and re-fill of systems, SUNOCO TH FLUID is also used for certain commercial transmission applications requiring Type A (Suffix A) or Dexon fluids. Check your manual for your equipment's specific requirements. Do not use in passenger car automatic transmissions.

SPECIFICATIONS

API GL-4 • Allison Type C-4 • AGCO Power Fluid 821 XL • Case IH MS1210, MS1209, MS1207, MS1206, MS 1204-07/09 • Case New Holland (CNH) MAT-3509, 3525, 3506, 3505 • Caterpillar TO-2 • Dennison HF-0, HF-1, HF-2 • Fendt • Ford ESN M2C134-A/B/C/D, FNHA-2C-201.00, FNHA-2-C-200.00, M2C86-B/C, M2C41-B, M2C48-A/B • International Harvester B-6 Hy-Tran • John Deere J14B/C, J20A/B, J20C (Hygard), J21A • Kubota UDT Fluid • Massey Ferguson M1110, M1127B, M1129A, M1143, M1141 (Permatran III) • Minneapolis-Moline 35154, 35202, 35301 • Sauer-Sundstrand Hydrostatic Transmission Fluid • VALTRA G2-08 • VCE (Volvo) WB 101 • Vickers M-2950-S, I-286-S, 35VQ25 • White Farm Equipment Q-1705, Q-1722, Q-1766B, Q-1802 (Type 55 Fluid), Q-1826 (HTF) • ZF TE-ML 03E/05F/06E/06F/06K/17E/21F

TYPICAL PROPERTIES

Product Code	4413
Viscosity, cSt @ 40 °C	57.5
Viscosity, cSt @ 100 °C	9.20
Viscosity Index	155
Brookfield Viscosity, cP @-20°C	2,600
Brookfield Viscosity, cP @-35°C	20,500
Flash Point, °C	200
Pour Point, °C	-40
Zinc, wt%	0.150