



## SUNOCO ULTRA FULL SYNTHETIC SAE 0W-16 SP/GF-6B ENGINE OIL

### OVERVIEW

**SUNOCO ULTRA FULL SYNTHETIC SAE 0W-16 SP/GF-6B ENGINE OIL** is a specially formulated product designed for superior fuel economy. It is produced using pure synthetic base oils and high-performance additive packages for superior performance benefits and fuel efficiency over other conventional and synthetic engine oils.

### APPLICATIONS

**SUNOCO ULTRA FULL SYNTHETIC SAE 0W-16 SP/GF-6B ENGINE OIL** meets the most demanding lubrication requirements of today's naturally aspirated, turbocharged, direct-injected, gasoline-fueled and flex-fueled engines. This oil is certified against the newest ILSAC category, **GF-6B and is not backwards compatible to GF-5** or earlier certifications. It been engineered to for protection from LSPI events and is API "Resource Conserving" for impressive fuel economy gains.

### FEATURES & BENEFITS

**SUNOCO ULTRA FULL SYNTHETIC SAE 0W-16 SP/GF-6B ENGINE OIL** has excellent oxidation stability for long lubricant life, low-temperature protection to prevent cold start wear, low volatility for reduced oil consumption, and increased resistance to viscosity breakdown. It specifically designed to inhibit incidents of LSPI (low-speed pre-ignition), a combustion event that can cause premature wear or catastrophic failure and to promote fuel economy savings and emissions reductions. **SUNOCO ULTRA FULL SYNTHETIC SAE 0W-16 SP/GF-6B ENGINE OIL** protects against engine deposits, valve train wear, and help extend engine life longer then convention motor oils.

### SPECIFICATIONS

**API SP, SN, SN PLUS • ILSAC GF-6B**

### TYPICAL PROPERTIES

<b>PRODUCT CODE</b>	<b>7433</b>
SAE Viscosity Grade	0W-16
Viscosity, cSt @ 100°C	7.4
Viscosity, cSt @ 40°C	38.3
Viscosity, CCS, cP @ °C	4,500 (-40)
Viscosity Index	164
Flash Point, COC, °C, min	200
Pour Point, °C, max	-47