

Super S[®] Non-Detergent Motor Oil

TECHNICAL PRODUCT INFORMATION



Super S Non-Detergent Motor Oil

Super S Non-Detergent Motor Oil are blended from well refined petroleum base oils and may be used in older, worn engines with high oil consumption

FEATURES/ BENEFITS

- Well refined mineral oils with no added additives
- Available in 5 viscosity grades
- Mono grade formulations

APPLICATIONS

- Engines calling for API SA or SB performance level engine oils
- API GL-1 Gear Applications
- Older engines
- Engines with high oil consumption
- Non critical low pressure hydraulic systems
- Drip oilers, spindle lubrication, once thru applications
- Light duty compressors

RECOMMENDATIONS/SPECIFICATIONS

Recommended for applications calling for
API SA, SB
API GL-1

SPECIAL HANDLING, NOTICES OR WARNINGS

CAUTION: This oil is rated API SA, SB and is not suitable for use in most gasoline powered automotive engines built after 1951, use in more modern engines may cause unsatisfactory performance or harm of equipment. Use the same care and handling that you would use with petroleum products.

TYPICAL CHARACTERISTICS

Super S® Non-Detergent Motor Oil						
Property	Test Method ASTM -D	SAE Viscosity Grade				
SAE Viscosity Grade		10	20	30	40	50
Viscosity @ 100°C	D445	4.5	8	10	13.5	19
VI	2270	>50	>50	>50	>50	>50

Typical test data are average values only.
 Minor variations which do not affect product performance are to be expected during normal manufacturing.

PRODUCT NUMBERS

SAE 10

- SUS 84-3 3/1 gallon bottles
- SUS 84-1 6/1 gallon bottles
- SUS 7 5 gallon pail

SAE 20

- SUS 85 12/1 quart bottles
- SUS 85-55 55 gallon drum

SAE 30

- SUS 41 12/1 quart bottles
- SUS 10 5 gallon pail
- SUS 16 55 gallon drum
- SUS 41 Bulk

SAE 40

- SUS 45 12/1 quart bottles
- SUS 5405 6/5 quart bottles
- SUS 45-3 3/1 gallon bottles
- SUS 45-1 6/1 gallon bottles
- SUS 11 5 gallon pail
- SUS 11-55 55 gallon drum
- SUS 45Bulk Bulk

SAE 50

- SUS 86 12/1 quart bottles
- SUS 8605 6/5 quart bottles
- SUS 86-3 3/1 gallon bottles
- SUS 86-1 6/1 gallon bottles
- SUS 86-5 5 gallon pail
- SUS 86-55 55 gallon drum
- SUS 86Bulk Bulk