



Super S[®] Power Steering Fluid

Super S[®] Power Steering Fluid is a general purpose fluid for power steering systems. Formulated with paraffinic basestocks with an effective anti-wear and anti-foam additive to provide year round protection in pumps requiring use of a hydraulic based power steering fluid.

APPLICATIONS

Year round use in power steering systems in:

- Automobiles
- Light Trucks
- Farm Equipment
- Applications calling for a hydraulic power steering fluid

FEATURES/ BENEFITS

- Formulated with wax-free base oils and a balanced additive package
- Maintains system efficiency
- Controls leaks and squeals
- Resists oxidation, corrosion, and wear
- Non-foaming

SPECIAL HANDLING, NOTICES OR WARNINGS

Handle as you would any petroleum product.

TYPICAL CHARACTERISTICS

Super S [®] Power Steering Fluid		
Properties	Test Method ASTM D-	Data
Gravity, °API	1298	23.2
Flash Point °C/°F,	92	171/340
Density (lb/gal)	1298	7.47
Color	1500	1.5
Viscosity	445	
cSt @ 40°C		30.75
cSt @ 100°C		7.05

Typical test data are average values only.

Minor variations which do not affect product performance are to be expected during normal manufacturing.

PRODUCT NUMBERS

SUS 29L	12/12 oz. bottles
SUS 29-24	24/12 oz. bottles
SUS 30	12/1 quart bottles
SUS 129-3	3/1 gallon bottles
SUS 129-6	6/1 gallon bottles
SUS 29Bulk	Bulk