

Super S TC-W3 Premium Outboard Oil



TECHNICAL PRODUCT INFORMATION

Super S TC-W3 Premium Outboard Oil

Super S TC-W3 Premium Outboard Oil is a high performance lubricant for the superior protection of all two-stroke gasoline outboard motors. It is formulated from base stocks incorporated with a select ashless additive package and high flash point diluents designed to meet the most critical requirements of high performance, water and air cooled two stroke cycle engines. Super S TC-W3 Premium Outboard Oil is a self-mixing oil. It is blended to the correct viscosity for use in oil injection systems fitted to two-stroke gasoline outboard motors.

FEATURES/ BENEFITS

- Provides efficient protection against ring sticking and cylinder wall scuffing.
- High flash point diluents allow easy mixing with gasoline.
- Protects engines against rust, wear, corrosion and exhaust port plugging.
- Reduces spark plug fouling and surface ignition.

RECOMMENDATIONS

Super S TC-W3 Premium Outboard Oil meets or exceeds the requirements for use where the following specifications are recommended:

- NMMA (National Maritime Manufacturers' Association) for service TC-W3 at the manufacturer's recommended fuel/oil ratio.

APPLICATIONS

All two-stroke gasoline outboard motors with or without separate oil tanks.

SPECIAL HANDLING, NOTICES OR WARNINGS

Super S TC-W3 Premium Outboard Oil is unlikely to present any significant health or safety hazard when properly used in the recommended application. Avoid contact with skin. After skin contact, wash immediately with soap and water.

TYPICAL CHARACTERISTICS

Super S TC-W3 Premium Outboard Oil		
<i>Properties</i>	<i>Test Method</i>	<i>Data</i>
Density @ 15C (kg/m ³)	ASTM D4052	31.4
Kinematic Viscosity cSt @ 40C cSt @ 100C	ASTM D445	37.0 - 49.0 6.9 - 7.3
Pour Point °C	ASTM D97	-30
Flash Point °C	ASTM D92	95
Sulphated Ash % wt	ASTM D874	0

PRODUCT NUMBERS

SUS 175	24/16oz
SUS 176	12/1qt
SUS 177	6/1gal
SUS 179	55gal