

Super S[®] Universal 2 Cycle Oil

TECHNICAL PRODUCT INFORMATION



Super S Universal 2 Cycle Oil

Super S Universal 2 Cycle Oil is formulated for use in air cooled 2 cycle engines.

FEATURES/ BENEFITS

- Provides easy starts
- Provides anti scuff and anti wear protection
- Protects against rust and corrosion
- Minimizes deposits
- Controls plug fouling

APPLICATIONS

- Air cooled 2 cycle engines
- Engines calling for API TC performance level oil
- Super S Universal 2-Cycle Engine Oil is suitable for use in the following 2-cycle engines:
 - Homelite
 - Husqvarna
 - Poulan
 - Pioneer
 - Stihl
 - McCulloch

Check owners manual for the correct fluid recommendation

SPECIAL HANDLING, NOTICES OR WARNINGS

Use the same care and handling as for any petroleum product.

TYPICAL CHARACTERISTICS

Super S [®] Universal 2 Cycle Oil		
Properties	Test Method ASTM D-	Data
SAE Grade		30
Gravity, °API	1298	23
Flash Point °C/°F,	92	207/405
Pour Point °C/°F,	97	-18/0
Color	1500	3.5
Viscosity	445	
cSt @ 40°C		52.8
cSt @ 100°C		8.5

Typical test data are average values only.

Minor variations which do not affect product performance are to be expected during normal manufacturing.

PRODUCT NUMBERS

SUS 81	48/3.2 oz. bottles
SUS 18	24/8 oz. bottles
SUS 18-16	24/16 oz. bottles
SUS 300bulk	Bulk