Revision Date 01-23-2017 Revision Number 13



### SECTION 1 Identification of the substance/mixture and of the company/undertaking

Product identification used on label

Product identifier 3319

Details of the supplier of the safety

data sheet

TECTYL® 185GW GRAY Daubert Chemical Company 4700 S. Central Avenue Chicago, IL 60638

708-496-7350

Emergency telephone number Relevant identified uses of the substance or mixture and uses

advised against

Chemtrec: (800) 424-9300 Corrosion Preventive Compound

#### **SECTION 2 Hazards identification**

Classification of the chemical in accordance with paragraph (d) of §1910.1200;

GHS Hazard Symbols





GHS Skin Corrosion/Irritation Category 2

Classification Serious Eye Damage/Eye Irritation Category 2B

Flammable Liquid Category 3

Specific Target Organ Systemic Toxicity (STOT) - Single Exposure Category 3

Signal Word Warning

Hazard Flammable liquid and vapor
Statements Causes skin and eye irritation
May cause respiratory irritation

May cause drowsiness or dizziness

Unclassified None Identified

Hazards (HNOC):
Precautionary
Statements

**Prevention** Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof equipment. Use only non-sparking tools.

Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapours/spray.

Revision Date 01-23-2017 Revision Number 13

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

**Response** IF ON SKIN: Wash with plenty of soap and water.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse

skin with water/shower.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable

for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

Call a POISON CENTER or doctor/physician if you feel unwell.

Specific treatment: None known

If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention.

Use dry chemical, water fog, CO2, foam or sand/earth for extinction.

Storage Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Disposal Dispose of contents/container in accordance with

local/regional/national/international regulation for hazardous wastes.

### **SECTION 3 Composition/information on ingredients**

Chemical Name	CAS#	%
Hydrotreated light distillate (Petroleum)	64742-47-8	30 - 50

Note: Specific chemical identities and/or exact percentages have been withheld as a trade secret.

### **SECTION 4 First aid measures**

Inhalation	If symptoms are	e experienced remove so	urce of contamination of	or move victim to fresh air
	ii by iiip to iiib tai t	emperiemeed remove so	aree or communication of	or move victim to mean an

and obtain medical advice.

**Eyes** Flush eyes with plenty of water for at least 20 minutes retracting eyelids often. Tilt the head

to prevent chemical from transferring to the uncontaminated eye. Get immediate medical

attention.

**Skin Contact** Wash with soap and water. Get medical attention if irritation develops or persists.

Do not induce vomiting and seek medical attention immediately. Provide medical care

provider with this SDS. If vomiting occurs, lean victim forward to reduce risk of aspiration

into lungs.

Most important symptoms/effects, acute and delayed

Ingestion

See Section 11

Indication of immediate medical attention and special treatment needed Treat symptomatically.

Revision Date 01-23-2017 **Revision Number 13** 

Suitable extinguishing media: Use alcohol resistant foam, carbon dioxide, dry chemical, or water spray

when fighting fires. Water or foam may cause frothing if liquid is burning but it still may be a useful extinguishing agent if carefully

applied to the fire.

**Unsuitable extinguishing media:** 

Fire and/or Explosion Hazards

Do not use water jet as an extinguisher, as this will spread the fire. Vapors may be ignited by sparks, flames or other sources of ignition if material is above the flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition and flash back.Empty containers that retain product residue (liquid, solid/sludge,

or vapor) can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition. Any of these actions can potentially cause

an explosion that may lead to injury or death.

Use process enclosures to control the level of dust in the air.

Fire Fighting Methods and Protection Do not enter fire area without proper protection including self-contained

> breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous vapors and decomposition products. Use appropriate methods for the

surrounding fire.

**Hazardous Combustion Products** Carbon dioxide, Carbon monoxide, Hydrocarbons, Sulfur oxides

#### **SECTION 6 Accidental release measures**

Personal precautions, protective equipment and emergency procedures No health effects expected from the clean-up of this material, if contact can be avoided. Follow personal protective equipment recommendations found in Section VIII of this SDS

Methods and materials for containment and cleaning up

Absorb or cover with dry earth, sand or other non-combustible material and transfer to appropriate waste containers. Use clean, non-sparking tools to collect absorbed material. Collect and discard in accordance with local, state and national regulations.

#### **SECTION 7 Handling and storage**

Precautions for safe handling

Mildly irritating material. Avoid unnecessary exposure. As with all chemicals, good industrial hygiene practices should be followed when handling this material. Wash thoroughly after handling. Do not get in eyes, on skin and clothing. Ground and bond containers when transferring material. "Empty" containers retain product residue (liquid and/or

vapor) and can be dangerous.

Conditions for safe storage, including any

incompatibilities

Store in a cool dry place. Isolate from incompatible

materials. Keep container closed when not in use. Keep away from heat, sparks, and flame.

Strong oxidizing agents

**Incompatible materials** 

Revision Date 01-23-2017 Revision Number 13

#### **SECTION 8 Exposure controls/personal protection**

**Control parameters** 

<u>Chemical Name</u> <u>ACGIH TLV</u> <u>ACGIH STEL</u> <u>OSHA PEL</u>

Hydrotreated light distillate (Petroleum) 200 mg/m3

**Engineering Measures** Local exhaust ventilation or other engineering controls are normally required when

handling or using this product to avoid overexposure. Engineering controls must be designed to meet the OSHA chemical specific standard in 29 CFR 1910. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne

levels below recommended exposure limits

**Respiratory Protection** Proper ventilation (at a minimum) will be required when handling this product. Use

respirators (NIOSH approved) only if ventilation cannot be used to eliminate symptoms or reduce the exposure to below acceptable levels. Follow a respiratory protection program that meets 29 CFR 1910.134 and ANSI Z88.2 requirements whenever work

place conditions warrant the use of a respirator.

**Eye Protection** Wear chemically resistant safety glasses with side shields when handling this product.

Do not wear contact lenses.

**Skin Protection** Wear protective gloves. Inspect gloves for chemical break-through and replace at

regular intervals. Clean protective equipment regularly. Wash hands and other exposed

areas with mild soap and water before eating, drinking, and when leaving work.

Gloves Chemically resistant gloves

#### **SECTION 9 Physical and chemical properties (Typical, not specification)**

Physical State Thixotropic liquid

Color Grev

Odor
Odor Threshold
Petroleum Type
No data available

range, °C

Flash Point  $105 \, ^{\circ}\text{F}(41 \, ^{\circ}\text{C})$ 

Evaporation Rate <1 (n-Butyl Acetate=1)
Flammability (Solid, Gas) No data available
Lower Flammable/Explosive Limit, No data available

% in air

Upper Flammable/Explosive Limit, No data available

% in air

Vapor Pressure2 mmHgVapor Density>1 (Air=1)Specific Gravity @ 25°C1.02

Solubility in WaterNegligible; 0-1%Octanol/Water Partition CoefficientNo data availableAutoignition TemperatureNo data availableDecomposition TemperatureNo data available

Revision Date 01-23-2017 Revision Number 13

Viscosity16000 cPVolatiles, % by weight37VOC, Material, lb/gal3.4VOC, Material, grams/liter407.8VOC minus exempt solvents & water,3.4

lb/gal

### **SECTION 10 Stability and reactivity**

**Reactivity** No data available

Chemical stability Stable under normal conditions. Hazardous polymerization

will not occur.

**Possibility of hazardous reactions** Under normal conditions of storage and use, hazardous

reactions will not occur.

**Conditions to avoid**Contamination. Elevated temperatures.

Incompatible materials Strong oxidizing agents

**Hazardous decomposition products**Under normal conditions of use & storage, decomposition and

hazardous decomposition products are unlikely.

### **SECTION 11 Toxicological information**

**Likely Routes of Entry**Inhalation, Skin contact, Eye contact

Target Organs Potentially Affected by Exposure Central Nervous System

**Chemical Interactions That Change Toxicity**No chemical interaction known to affect toxicity.

Medical Conditions Aggravated Skin contact may aggravate existing skin disease, Respiratory

disease including asthma and bronchitis

**Immediate (Acute) Health Effects by Route of Exposure** 

**Inhalation Irritation** Can cause moderate respiratory irritation, dizziness, weakness, fatigue, nausea and

headache. Other possible symptoms include; wheezing and coughing due to pulmonary

edema (fluid build-up in lungs).

**Skin Contact** Can cause minor skin irritation, defatting, and dermatitis.

**Eye Contact** Can cause moderate irritation, tearing and reddening, but not likely to permanently injure

eve tissue.

**Injection Irritation** Irritating to mouth, throat, and stomach. Can cause abdominal discomfort, nausea,

vomiting and diarrhea. Aspiration of material into the lungs can cause chemical

pneumonitis which can be fatal.

**Ingestion Toxicity** Harmful if swallowed.

**Long-Term (Chronic) Health Effects** 

**Carcinogenicity** There are no carcinogenic ingredients present at or over 0.1%.

**Inhalation** Upon prolonged and/or repeated exposure, can cause severe respiratory irritation,

dizziness, weakness, fatigue, nausea, headache and possible unconsciousness.

**Skin Contact** Upon prolonged or repeated contact, can cause minor skin irritation, defatting, and

dermatitis.

**Ingestion** Under normal industrial usage conditions, ingestion is highly unlikely.

Revision Date 01-23-2017 Revision Number 13

**Component Toxicology Data** 

Chemical Name CAS Number LD50/LC50

Hydrotreated light distillate 64742-47-8 Dermal LD50 Rabbit > 2000 mg/kg Oral LD50 Rat > 5000 mg/kg

(Petroleum) Inhalation LC50 (4h) Rat > 20 mg/L

**SECTION 12 Ecological information** 

Overview No ecological information available

MobilityNo dataPersistenceNo dataBioaccumulationNo dataDegradabilityNo data

**Ecotoxicity Data** 

Chemical Name CAS Number Aquatic EC50 Aquatic ERC50 Aquatic LC50

Crustacea Algae Fish

No data available

**SECTION 13 Disposal considerations** 

**Waste Description for Spent Product** Spent or discarded material may be a hazardous waste.

**Disposal Methods** Dispose of by incineration following Federal, State, Local, or Provincial

regulations.

Waste Disposal Code(s) D001

**SECTION 14 Transport information** 

Full shipping name for UN1268, PETROLEUM DISTILLATES, N.O.S., (Naphtha Solvent), 3, PG III,

Export, Air, Sea (any quantity unless flash pt. >150°F) or vessels of 119 GL or more

**Domestic Ground in vessels** < Non-Regulated

119 gal.

**SECTION 15 Regulatory information** 

Status of formula components on selected national regulatory inventories:

LIST STATUS

**TSCA** All components in this product are on the TSCA Inventory or exempt.

**Canadian DSL** All chemical substances in this material are included on or exempted from listing on the

Canadian DSL.

Chemical Name CAS # Regulation Percent

No CERCLA-listed chemicals in this CERCLA

product.

No 313-listed chemicals in this SARA 313

product.

No SARA 302 EHS-listed chemicals in SARA EHS

this product.

Revision Date 01-23-2017 Revision Number 13

### **SECTION 16 Other information**

**Revision** 01-23-2017

Date

**Disclaimer** Although the information contained herein is believed to be reliable, it is furnished without warranty

of any kind. This information is not intended to be all-inclusive as to the manner and conditions of

use, handling, and storage.

Version Reviewed

Comments Approved: M. Longo