

# TERRA MULTI-TRAC THF



## GENERAL DESCRIPTION

TERRA MULTI-TRAC THF is an environmentally responsible, biodegradable universal lubricant for farm equipment, off-highway machinery, and industrial tractors. This multifunctional, bio-based fluid is designed for equipment requiring one lubricant for the transmission, final drive, wet brakes and hydraulic systems. It meets or exceeds the performance requirements of all major brands of farm tractors and other farm equipment that utilize a common fluid reservoir. TERRA MULTI-TRAC THF is formulated with special friction modifiers to ensure proper operation of wet brakes and transmission clutch packs. The vegetable based formulation provides superior oxidation resistance, excellent wear protection, protects against rust and corrosion, and has exceptional anti-foam characteristics. TERRA MULTI-TRAC THF is classified as ultimately biodegradable (Pw1) and non-toxic, It is ideal for equipment operating in environmentally sensitive areas.

## APPLICATION

TERRA MULTI-TRAC THF meets or exceeds the requirements for ATD Allison C-4, Caterpillar TO-2 and is recommended for use where the equipment manufacturer specifies the following:

CASE INTERNATIONAL JIC-145/MS-1210, JIC-185/MS-1204MS-1205, MS-1127, MS1129-A, M1135, M1141  
DEUTZ-ALLIS  
FIAT-HESSTON  
FORD M2C134-DM2C86-C, M2C86-B, M2C41-B, M2C48-B, M2C53-A, M2C134-A, M2C134-B, M2C134-C  
JOHN DEERE J20C, J14AQuatrol, J20DHyard  
KUBOTA  
LANDINI  
MASSEY-FERGUSON MS-1205, MS-1127, MS1129-A, M1135, M1141  
STEIGER  
VERSATILE  
WHITE FARM Q-1826, Q-1705, Q-1766, Q-1802

August 22, 2012

454 South Main Street, Wilkes-Barre, PA 18703 | P: (570) 822-1151 | F: (570) 823-1910

**PRODUCT DATA SHEET**

August 22, 2012

454 South Main Street, Wilkes-Barre, PA 18703 | P: (570) 822-1151 | F: (570) 823-1910

# PRODUCT DATA SHEET

NOTE: The information in this publication is the result of careful testing in our laboratories, complemented by selected literature. It does not in any way constitute a guarantee, nor widely varying conditions of product use, which are beyond our control, it is strongly recommended that the product be tested for suit ability. Product typical this publication are current as of November 24, 2010.

## Physical Properties

### ENVIROMENTALLY FRIENDLY LUBRICANT

#### TERRA MULTI-TRAC THF

Viscosity @40°C, cSt @100°C, cSt	47.8 10.26
Brookfield Viscosity @-20°C @-35°C	1650 11,150
Viscosity Index	210
Flash Point, °F, (°C)	484 (251)
Stable Pour Point, °F, (°C)	-38 (-39)
Biodegradation Classification, ASTM D 5864	ultimate PW1

ENVIROMENTALLY FRIENDLY LUBRICANT

## TERRA MULTI-TRAC THF