

**Stock Number:** 3286005 **Revision Date:** 09-23-2024 **Replaces:** 09-07-2021

### TECTYL® 891D CLASS II

### 1. Identification

Product identifier used on the label: TECTYL® 891D CLASS II

Stock Number: 3286005

Other means of identification:

Synonyms: None
Chemical family: Mixture

Recommended use of the chemical and restrictions on use:

**Recommended use:** Corrosion Preventative Coating

**Restrictions on use:** Uses other than those described above

Name, address, and telephone number

of the chemical manufacturer,

Daubert Chemical Company

importer, or other responsible party:

4700 S. Central Avenue

Chicago, IL 60638

**Telephone number:** 1-708-496-7350 **E-mail address:** SDS@Daubert.com

Emergency phone number: Chemtrec: (800) 424-9300 - in USA and Canada

+1-703-527-3887 - outside USA and Canada

### 2. Hazard(s) identification

Classification of the chemical in accordance with paragraph (d) of §1910.1200:

GHS Hazard Symbols:





GHS Classification: Flammable Liquid Category 3; Specific Target Organ Systemic Toxicity

(STOT) - Single Exposure Category 3

Signal Word: Warning

Hazard Statements: Flammable liquid and vapor

May cause respiratory irritation

Unclassified Hazards (HNOC): None Identified

**Precautionary Statements:** 

**Prevention:** Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Product identifier used on the label: TECTYL® 891D CLASS II

Stock Number: 3286005 Revision Date: 09-23-2024 Replaces: 09-07-2021

Avoid breathing fume/gas/mist/ vapors/spray.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face

protection.

**Response:** If on skin (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower.

If inhaled: Remove person to fresh air and keep comfortable for

breathing.

Call a poison center/doctor if you feel unwell.

In case of fire: Use appropriate media to extinguish.

**Store** in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

**Disposal:** Dispose of contents/container to a suitable disposal site in accordance

with local/national/international regulations.

**Hazards not otherwise classified:**No data available

### 3. Composition/information on ingredients

Chemical Name	Common name and synonyms	CAS#	%
Distillates (petroleum), hydrotreated light	None	64742-47-8	30 - 60
Light aromatic solvent naphtha	None	64742-95-6	1-5
Sulfonic acids, petroleum, sodium salts	None	68608-26-4	1 - 5
Benzenesulfonic acid, mono- C16-24-alkyl derivs., calcium salts	None	70024-69-0	0.1 - 1

Specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

### 4. First-aid measures

Description of necessary measures, subdivided according to the different routes of exposure, i.e., inhalation, skin and eye contact, and ingestion:

**Inhalation:** If symptoms are experienced remove source of contamination or move

victim to fresh air and obtain medical advice.

Product identifier used on the label: TECTYL® 891D CLASS II

Stock Number: 3286005 Revision Date: 09-23-2024 Replaces: 09-07-2021

**Eye Contact:** Immediately flush eyes with plenty of water for at least 20 minutes

retracting eyelids often. Tilt the head to prevent chemical from transferring to the uncontaminated eye. Get immediate medical attention and monitor the eye daily as advised by your physician.

**Skin Contact:** Wash with soap and water. Get medical attention if irritation develops or

persists.

**Ingestion:** Do not induce vomiting and seek medical attention immediately. Provide

medical care provider with this SDS.

Most important symptoms/effects,

acute and delayed:

May cause respiratory irritation

Indication of immediate medical attention and special treatment

needed, if necessary:

Consult a physician. Treat symptomatically.

### 5. Fire-fighting measures

### Suitable (and unsuitable) extinguishing media:

**Suitable extinguishing media:** Use alcohol resistant foam, carbon dioxide, or dry chemical extinguishing

agents. Water may be ineffective but water spray can be used to extinguish a fire if swept across the base of the flames. Water can absorb

heat and keep exposed material from being damaged by fire.

**Unsuitable extinguishing media:** Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the

chemical:

Vapors may be ignited by sparks, flames or other sources of ignition if material is above the flash point giving rise to a fire (Class B). Vapors are heavier than air and may travel to a source of ignition and flash back. Empty containers that retain product residue (liquid, solid/sludge, or vapor) can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose container to heat, flame, sparks, static electricity, or other sources of ignition. Any of these actions can potentially cause an explosion that may lead to injury or death.

**Hazardous combustion products:** Oxides of carbon, Smoke, Sulfur oxides, Hydrogen sulfide, Incomplete

combustion products, Fume, Wax and Oil fumes

Special protective equipment and precautions for fire-fighters:

Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Fight fire from a safe distance and a protected location due to the potential of hazardous

vapors and decomposition products.

Product identifier used on the label: TECTYL® 891D CLASS II

Stock Number: 3286005 Revision Date: 09-23-2024 Replaces: 09-07-2021

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures:

No health effects expected from the clean-up of this material if contact can be avoided. Follow personal protective equipment recommendations

found in Section VIII of this SDS

Methods and materials for containment and cleaning up:

Absorb or cover with dry earth, sand or other non-combustible material and transfer to appropriate waste containers. Use clean, non-sparking tools to collect absorbed material. Collect and discard in accordance with local, state and national regulations.

### 7. Handling and storage

Precautions for safe handling:

Mildly irritating material. Avoid unnecessary exposure. Ground and bond containers when transferring material. Avoid contact with material, avoid breathing dusts or fumes, use only in a well-ventilated area. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. Do not get in eyes, on skin and clothing. Wash thoroughly after handling. As with all chemicals, good industrial hygiene practices should be followed when handling this material. Prevent small spills and leakage to avoid slip hazard.

Conditions for safe storage, including

any incompatibilities:

Safe storage conditions:

Store in a cool dry place. Isolate from incompatible materials. Keep away

from heat, sparks, and flame. Keep container closed when not in use.

Materials to Avoid/Chemical

Incompatibility:

Strong oxidizing agents, Strong acids

### 8. Exposure controls/personal protection

OSHA permissible exposure limit (PEL), American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Value (TLV), and any other exposure limit used or recommended by the chemical manufacturer, importer, or employer preparing the safety data sheet, where available:

Chemical component	OSHA PEL	ACGIH TLV	ACGIH STEL	IDLH
Distillates (petroleum), hydrotreated light		200 mg/m3		No data available
Light aromatic solvent naphtha	400 mg/m3			No data available

Product identifier used on the label: TECTYL® 891D CLASS II

Stock Number: 3286005 Revision Date: 09-23-2024 Replaces: 09-07-2021

Appropriate engineering controls:

Local exhaust ventilation or other engineering controls are normally required when handling or using this product to avoid overexposure.

Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits

Engineering controls must be designed to meet the OSHA chemical

specific standard in 29 CFR 1910.

Individual protection measures, such as personal protective equipment:

**Respiratory Protection:** Proper ventilation (at a minimum) will be required when handling this

product. Use respirators (NIOSH approved) only if ventilation cannot be used to eliminate symptoms or reduce the exposure to below acceptable levels. Follow a respiratory protection program that meets 29 CFR 1910.134 and ANSI Z88.2 requirements whenever work place conditions

warrant the use of a respirator.

**Respirator Type(s):** NIOSH approved air purifying respirator with organic vapor cartridge.

Eye protection: Wear chemically resistant safety glasses with side shields when handling

this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Do not wear contact

lenses. Have an eye wash station available.

When handling material that is heated, wear chemically resistant safety

glasses with side shields and a face shield.

**Skin protection:** Wear protective gloves. Inspect gloves for chemical break-through and

replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating,

drinking, and when leaving work.

Gloves: Impervious rubber

Other protective equipment: Wear chemically resistant safety glasses with side shields when handling

this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Do not wear contact

lenses. Have an eye wash station available.

Wear protective gloves. Inspect gloves for chemical break-through and replace at regular intervals. Clean protective equipment regularly. Wash hands and other exposed areas with mild soap and water before eating,

drinking, and when leaving work.

When handling material that is heated, wear chemically resistant safety

glasses with side shields and a face shield.

**General hygiene conditions:** Follow all protective equipment recommendations provided in Section 8.

Use bonding and grounding when transferring quantities of material. Use

Product identifier used on the label: TECTYL® 891D CLASS II

Stock Number: 3286005 Revision Date: 09-23-2024 Replaces: 09-07-2021

spark-proof tools and explosion-proof equipment. Ground and bond containers when transferring material. Avoid contact with material, avoid breathing dusts or fumes, use only in a well-ventilated area. Prevent small spills and leakage to avoid slip hazard. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. Do not get in eyes, on skin and clothing. Wash thoroughly after handling. As with all chemicals, good industrial hygiene practices should be followed when handling this material.

### 9. Physical and chemical properties

Appearance (physical state, color etc.):

Physical state: Viscous Liquid

Color: Black

Odor: Petroleum Type
Odor Threshold: No data available
pH: No data available

Melting point/freezing point (°C):

Melting Point (°C):

Freezing point (°C):

Initial boiling point and boiling range (°C):

Flash Point:

Evaporation Rate:

No data available

Upper/lower flammability or explosive

limits:

Upper flammability or explosive limits:

Lower flammability or explosive limits:

No data available

No data available

No data available

Vapor density:

No data available

Relative density: 0.918

Solubility(ies):Negligible; 0-1%Partition coefficient: n-octanol/water:No data availableAuto-ignition temperature (°C):No data availableDecomposition Temperature (°C):No data available

Viscosity: < 2300 cP Volatiles, % by weight: 34.42

Product identifier used on the label: TECTYL® 891D CLASS II

Stock Number: 3286005 Revision Date: 09-23-2024 Replaces: 09-07-2021

VOC, Material, lb/gal 2.63

VOC, Material, grams/liter 315.7

VOC minus exempt solvents & water, g/L 315.8

10. Stability and reactivity

**Reactivity:** Not expected to be reactive

**Chemical stability:** Stable under normal conditions.

Possibility of hazardous reactions: Under normal conditions of storage and use, hazardous reactions will not

occur.

Conditions to avoid (e.g., static

**discharge, shock, or vibration):** Elevated temperatures. Contamination.

Incompatible materials: Strong oxidizing agents, Strong acids

Hazardous decomposition products: Under normal conditions of use & storage, decomposition and hazardous

decomposition products are unlikely.

11. Toxicological information

Description of the various toxicological (health) effects and the available data used to identify those effects:

Information on the likely routes of exposure (inhalation, ingestion, skin

and eye contact):

Eye contact, Skin contact, Inhalation

Symptoms related to the physical,

chemical and toxicological

characteristics:

May cause respiratory irritation

Delayed and immediate effects and also chronic effects from short- and long-term exposure:

**Ingestion Toxicity:** Not believed to have any significant toxicity.

**Skin Contact:** Can cause minor skin irritation, defatting, and dermatitis.

**Inhalation Toxicity:** May cause respiratory irritation

**Eye Contact:** Contact with the eyes may cause moderate to severe eye injury. Eye

contact may result in tearing and reddening, but not likely to

permanently injure eye tissue. Temporary vision impairment (cloudy or

Sparks, open flame, other ignition sources, and elevated temperatures.

blurred vision) is possible.

Sensitization: None known

Mutagenicity: No data

Product identifier used on the label: TECTYL® 891D CLASS II

Stock Number: 3286005 Revision Date: 09-23-2024 Replaces: 09-07-2021

**Reproductive and Developmental** 

No data available

**Toxicity:** 

**Carcinogenicity:** There are no carcinogenic ingredients present at or over 0.1%.

STOT-single exposure: Classification has been based on toxicological information of the

components in Section 3.

STOT-repeated exposure: Based on available data, the classification criteria are not met.

Aspiration hazard: Based on available data, the classification criteria are not met.

### Numerical measures of toxicity (such as acute toxicity estimates):

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Distillates (petroleum), hydrotreated light			Inhalation LC50 (4h) Rat > 20 mg/L
Light aromatic solvent naphtha			Inhalation LC50 (4h) Rat 61 mg/L

Is the hazardous chemical listed in the National Toxicology Program (NTP) Report on Carcinogens (latest edition) or has it been found to be a potential carcinogen in the International Agency for Research on Cancer (IARC) Monographs (latest edition), or by OSHA?:

Chemical Name	OSHA Carcinogen	IARC Carcinogen	NTP Carcinogen
No component of this			
product present at levels			
greater than or equal to			
0.1% is identified as a			
known or anticipated			
carcinogen.			

### 12. Ecological information

#### **Ecological Toxicity Data:**

Chemical Name	CAS#	Aquatic EC50	Aquatic ERC50	Aquatic LC50 Fish
		Crustacea	Algae	
Light aromatic solvent	64742-95-6	EC50(48 HR)	No data available	LC50(96 HR)
naphtha		WATER FLEA 2.7 -		RAINBOW TROUT
		5.1 mg/L		8.8 mg/L

Persistence and degradability: No data

Bioaccumulative potential:No data availableMobility in soil:No data availableOther adverse effects (such asNo data available

hazardous to the ozone layer):

Product identifier used on the label: TECTYL® 891D CLASS II

Stock Number: 3286005 Revision Date: 09-23-2024 Replaces: 09-07-2021

### 13. Disposal considerations

Description of waste residues and information on their safe handling and methods of disposal, including the disposal of any contaminated

Spent or discarded material is a hazardous waste.

Dispose of by incineration following Federal, State, Local, or Provincial

regulations.

packaging:

Waste codes / waste designations: D001

### 14. Transport information

Domestic Ground in containers <= 119 GL	Corrosion preventive/Non-Regulated
Domestic Ground in containers > 119 GL	UN1268, PETROLEUM DISTILLATES, N.O.S.,(Naphtha Solvent), Combustible liquid, PG III
Shipping name for Export, Air (IATA)	UN1268, PETROLEUM DISTILLATES, N.O.S.,(Naphtha Solvent),3, PG
Shipping name for Export, Sea (IMDG)	UN1268, PETROLEUM DISTILLATES, N.O.S.,(Naphtha Solvent),3, PG
Marine Pollutant?	No

### 15. Regulatory information

### **International Inventory**

Country(s) or region		On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes

Product identifier used on the label: TECTYL® 891D CLASS II

Stock Number: 3286005 Revision Date: 09-23-2024 Replaces: 09-07-2021

Europe	European List of Notified Chemical	No
	Substances (ELINCS)	
Japan	Inventory of Existing and New	Yes
	Chemical Substances (ENCS)	
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippines Inventory of Chemicals	Yes
	and Chemical Substances (PICCS)	
Taiwan	Taiwan Inventory	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA)	Yes
	Inventory	

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or are unknown from listing on the inventory administered by the governing country(s).

Chemical Name	CAS#	Regulation	Percent
Naphthalene	91-20-3	Prop. 65 - Cancer	TRACE
Benzene	71-43-2	Prop. 65 - Cancer	TRACE
Ethylbenzene	100-41-4	Prop. 65 - Cancer	TRACE
Cumene	98-82-8	Prop. 65 - Cancer	<0.1
Benzene	71-43-2	Prop. 65 - Developmental and/or Reproductive	TRACE
Toluene	108-88-3	Prop. 65 - Developmental and/or Reproductive	TRACE
Xylene	1330-20-7	CERCLA	<0.1
			RQ = 100 lbs.

Product identifier used on the label: TECTYL® 891D CLASS II

Stock Number: 3286005 Revision Date: 09-23-2024 Replaces: 09-07-2021

	•		
Cumene	98-82-8	CERCLA	<0.1
			RQ = 5000 lbs.
Toluene	108-88-3	CERCLA	TRACE
			RQ = 1000 lbs
Sodium hydroxide	1310-73-2	CERCLA	TRACE
			RQ = 1000 lbs.
Naphthalene	91-20-3	CERCLA	TRACE
			RQ = 100 lbs.
Benzene	71-43-2	CERCLA	TRACE
			RQ = 10 lbs.
Ethylbenzene	100-41-4	CERCLA	TRACE
			RQ = 1000 lbs.
Naphthalene	91-20-3	SARA 313	TRACE
Benzene	71-43-2	SARA 313	TRACE
Ethylbenzene	100-41-4	SARA 313	TRACE
Toluene	108-88-3	SARA 313	TRACE
Cumene	98-82-8	SARA 313	<0.1
Xylene	1330-20-7	SARA 313	<0.1
1,2,4-Trimethylbenzene	95-63-6	SARA 313	0.5 - 1.5
No SARA 302 EHS-listed chemicals in this product.		SARA EHS	

Product identifier used on the label: TECTYL® 891D CLASS II

Stock Number: 3286005 Revision Date: 09-23-2024 Replaces: 09-07-2021

### 16. Other information, including date of preparation or last revision.

SDS Prepared by: REGULATORY

**Revision Date:** 09-23-2024

Revision Number: 28

Reason for revision: Revised

Approved: K. Slegel

**Disclaimer:** Although the information contained herein is believed to be reliable, it is

furnished without warranty of any kind. This information is not intended to be all-inclusive as to the manner and conditions of use, handling, and

storage.