

SAFETY DATA SHEET

According to the Hazard Communication Standard, 29 CFR 1910.1200

VULSOL 5000

SDS #: 088088

Section 1. Identification

GHS product identifier : VULSOL 5000

Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Cutting fluid Metalworking fluid

Supplier's details

: TotalEnergies Marketing USA, Inc. 1201 Louisiana St. Suite 1800

Houston, TX 77002 Phone: 713-483-5000

ProductSafety@totalenergies.com

Emergency telephone number (with hours of operation)

1-866-928-0789 (For Emergencies, call CARECHEM 24/7 Domestic) 1-215-207-0061 (For Emergencies, call CARECHEM 24/7 International)

Section 2. Hazards identification

OSHA/HCS status

: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture

: CORROSIVE TO METALS - Category 1 SKIN CORROSION - Category 1B SERIOUS EYE DAMAGE - Category 1

GHS label elements

Hazard pictograms



Signal word

: Danger

Hazard statements

: May be corrosive to metals.

Causes severe skin burns and eye damage.

Precautionary statements

Prevention

: Wear protective gloves, protective clothing and eye or face protection. Keep only in original packaging. Wash thoroughly after handling.

Response

: Absorb spillage to prevent material damage. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or doctor. IF SWALLOWED: Immediately call a POISON CENTER or doctor. Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. Immediately call a POISON CENTER or doctor. Wash contaminated clothing before reuse. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Storage

: Store locked up. Store in a corrosion resistant container with a resistant inner liner.

Date of revision : 2023/06/01 1 USA ENGLISH 1/14



SDS #: 088088

Disposal

: Dispose of contents and container in accordance with all local, regional, national and international regulations.

Supplemental label elements

: Keep container tightly closed. Do not breathe vapor or spray. Use only with adequate ventilation.

Hazards not otherwise classified

: Causes respiratory tract burns.

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Ingredient name	% (w/w)	CAS number
2-(2-aminoethoxy)ethanol	≥10 - ≤25	929-06-6
Nitric acid, reaction products with cyclododecanol and cyclododecanone, by-products from, high-boiling fraction	≤5	72162-23-3
octanoic acid	≤3	124-07-2

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

Additional information

: Aqueous solution The product is made from synthetic base oils

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact

: Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.

Inhalation

: Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Skin contact

: Get medical attention immediately. Call a poison center or physician. Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.

Ingestion

: Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in

Date of revision : 2023/06/01 1 USA ENGLISH 2/14



SDS#: 088088

recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : Causes serious eye damage.

Inhalation : Corrosive to the respiratory system.

Skin contact : Causes severe burns.

Ingestion : May cause burns to mouth, throat and stomach.

Over-exposure signs/symptoms

Eye contact : Adverse symptoms may include the following:

> watering redness

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

coughing

Skin contact : Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur

Ingestion : Adverse symptoms may include the following:

stomach pains

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Specific treatments : No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. If it is

suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water

before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing : Use dry chemical, CO2, water spray (fog) or foam.

Unsuitable extinguishing : Do not use water jet.

media

media

Specific hazards arising from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst.

USA **ENGLISH** Date of revision : 2023/06/01 1 3/14



SDS #: 088088

Hazardous thermal decomposition products

: carbon oxides (CO, CO₂)

Mercaptans
Hydrogen sulfide
sulfur oxides
Sodium oxides
hydrogen chloride
nitrogen oxides

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders:

: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Absorb spillage to prevent material damage. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Absorb spillage to prevent material damage. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

: Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container. Absorb spillage to prevent material damage.

Date of revision : 2023/06/01 1 USA ENGLISH 4/14



SDS #: 088088

Advice on general occupational hygiene

: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store in a corrosion resistant container with a resistant inner liner. Store locked up. Keep away from metals. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

Ingredient name	Exposure limits
2-(2-aminoethoxy)ethanol	None.
Nitric acid, reaction products with cyclododecanol and cyclododecanone,	None.
by-products from, high-boiling fraction	
octanoic acid	None.

Advisory OEL

: No known significant effects or critical hazards.

Appropriate engineering controls

: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/ or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

Skin protection Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.

Date of revision : 2023/06/01 1 USA ENGLISH 5/14



SDS#: 088088

Hydrocarbon-proof gloves

Impermeable butyl rubber gloves

Neoprene gloves. Fluorinated rubber nitrile rubber

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and

the contact time.

: Personal protective equipment for the body should be selected based on the task being **Body protection**

performed and the risks involved and should be approved by a specialist before

handling this product.

: Appropriate footwear and any additional skin protection measures should be selected Other skin protection

based on the task being performed and the risks involved and should be approved by a

specialist before handling this product.

Respiratory protection Ensure adequate ventilation and check that a safe, breathable atmosphere is present

before entry into confined spaces. In case of insufficient ventilation, wear suitable respiratory equipment. The use of breathing apparatus must comply strictly with the manufacturer's instructions and the regulations governing their choices and uses.

Section 9. Physical and chemical properties

The conditions of measurement of all properties are at standard temperature (20°C / 68°F) and pressure (1013 hPa) unless otherwise indicated

Appearance

Physical state : Liquid. [limpid] Color : Not available. Odor : Characteristic. **Odor threshold** : Not available.

: 9.7 [Conc. (% w/w): 5%]

Melting point/freezing point : Not available. **Boiling point** : Not available.

Flash point : Open cup: Not applicable.

: Not available. **Evaporation rate** Flammability (solid, gas) : Not available. Lower and upper explosive : Not available.

(flammable) limits

Vapor pressure : Not available. Vapor density : Not available.

Relative density : 0.842 [ASTM D 1298] **Density** : 0.842 g/cm³ [15°C]

Solubility(ies)

Media	Result
water	Soluble

Miscible with water : Forms an emulsion

Partition coefficient: n-

octanol/water

: Not applicable.

Auto-ignition temperature : Not available. : Not available. **Decomposition temperature**

Date of revision 1 USA **ENGLISH** : 2023/06/01 6/14



SDS #: 088088

Viscosity

: Kinematic (40°C (104°F)): Not applicable.

Flow time (ISO 2431)

: Not available.

Particle characteristics

Median particle size : Not applicable.

Section 10. Stability and reactivity

Reactivity: No specific test data related to reactivity available for this product or its ingredients.

Chemical stability : Stable under recommended storage and handling conditions (see Section 7).

Possibility of hazardous

reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : No specific data.

Incompatible materials: Reactive or incompatible with the following materials:

metals

Hazardous decomposition

products

: carbon oxides (CO, CO₂)

Mercaptans
Hydrogen sulfide
sulfur oxides
Sodium oxides
hydrogen chloride
nitrogen oxides

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/substance	Result	Species	Dose	Exposure	Test
2-(2-aminoethoxy)ethanol	LC50 Inhalation Vapor	Rat	>8.7 mg/m ³	8 hours	-
	LD50 Dermal	Rabbit	>3000 mg/kg	-	OECD 402
					Acute Dermal
	LD50 Oral	Rat - Female	3000 mg/kg		Toxicity OECD 401
	LD30 Oral	Rat - Female	3000 Hig/kg	-	Acute Oral
					Toxicity
Nitric acid, reaction products	LC50 Inhalation Dusts	Rat	5.1 mg/l	4 hours	-
with cyclododecanol and	and mists				
cyclododecanone, by-					
products from, high-boiling fraction					
Tradition .	LC50 Inhalation Vapor	Rat	80.4 mg/l	1 hours	_
	LC50 Inhalation Vapor	Rat	20.1 mg/l	4 hours	-
	LD50 Dermal	Rabbit	2500 mg/kg	-	-
	LD50 Oral	Rat	>5000 mg/kg	-	-
octanoic acid	LC50 Inhalation Dusts and mists	Rat	5.1 mg/l	4 hours	OECD 403
	LC50 Inhalation Vapor	Rat	40.2 mg/l	1 hours	_
	LC50 Inhalation Vapor	Rat	20.1 mg/l	4 hours	_
	LD50 Dermal	Rabbit	>5000 mg/kg	-	-
	LD50 Oral	Rat	10080 mg/kg	-	-

Date of revision : 2023/06/01 1 USA ENGLISH 7/14



SDS#:

088088

LD50 Oral Rat 2000 mg/kg **OECD 401**

Conclusion/Summary : Based on available data, the classification criteria are not met.

Irritation/Corrosion

Product/substance	Result	Species	Score	Exposure	Test
2-(2-aminoethoxy)ethanol Nitric acid, reaction products	Eyes - Cornea opacity Skin - Visible necrosis Eyes - Moderate irritant	Rabbit Rabbit Rabbit	2 -	- 4 hours 0.01 g	- OECD 404
with cyclododecanol and cyclododecanone, by-products from, high-boiling fraction	Lyes - Moderate IIIItalit	INADDIL		0.01 g	
	Skin - Moderate irritant	Rabbit	-	0.5 g	-

Skin : Based on available data, the classification criteria are met. : Based on available data, the classification criteria are met. **Eyes** Based on available data, the classification criteria are not met. Respiratory

Sensitization

Skin : Based on available data, the classification criteria are not met. Respiratory : Based on available data, the classification criteria are not met.

Mutagenicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Carcinogenicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Reproductive toxicity

: Based on available data, the classification criteria are not met. **Conclusion/Summary**

Teratogenicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Conclusion/Summary : Based on available data, the classification criteria are not met.

Specific target organ toxicity (repeated exposure)

Conclusion/Summary : Based on available data, the classification criteria are not met.

Aspiration hazard

: Based on available data, the classification criteria are not met. **Conclusion/Summary**

Information on the likely

routes of exposure

: Not available.

Potential acute health effects

Eye contact : Causes serious eye damage.

Inhalation : Corrosive to the respiratory system.

: Causes severe burns. Skin contact

Ingestion : May cause burns to mouth, throat and stomach.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:

> watering redness

Date of revision : 2023/06/01 1 USA **ENGLISH** 8/14



lotalEnergies sps #: 088088

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

coughing

Skin contact: Adverse symptoms may include the following:

pain or irritation

redness

blistering may occur

Ingestion : Adverse symptoms may include the following:

stomach pains

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Long term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Product/substance	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	(vapors)	Inhalation (dusts and mists) (mg/ I)
VULSOL 5000 2-(2-aminoethoxy)ethanol Nitric acid, reaction products with cyclododecanol and cyclododecanone, by-products from, high-boiling	27744.4 3000 N/A	16542 2500 N/A	N/A N/A N/A	N/A N/A 20.1	N/A N/A 5.1
fraction octanoic acid	10080	N/A	N/A	20.1	5.1

Other information :

Not available.

Date of revision : 2023/06/01 1 USA ENGLISH 9/14



SDS #: 088088

Section 12. Ecological information

Toxicity

Product/substance	Result	Species	Exposure	Test
2-(2-aminoethoxy)ethanol	Acute EC50 202 mg/l	Algae	72 hours	-
	Acute EC50 189 mg/l	Daphnia - Daphnia magna	48 hours	-
	Acute LC50 460 mg/l	Fish	96 hours	-
	Acute NOEC 62.5 mg/l	Algae	72 hours	-
Nitric acid, reaction products with cyclododecanol and cyclododecanone, by- products from, high-boiling fraction	Acute EC50 120 mg/l	Daphnia - Daphnia magna	48 hours	-
octanoic acid	Acute EC50 23.28 mg/l	Algae - Pseudokirchnerella subcapitata	72 hours	OECD 201
	Acute EC50 20 mg/l Acute LC50 22 mg/l Chronic NOEC 0.2 mg/l	Daphnia - Daphnia Magna Fish Daphnia - Daphnia Magna	48 hours 96 hours 21 days	OECD 202 - OECD 211

Persistence and degradability

Product/substance	Aquatic half-life	Photolysis	Biodegradability
2-(2-aminoethoxy)ethanol Nitric acid, reaction products with cyclododecanol and cyclododecanone, by- products from, high-boiling fraction	-	-	Readily Not readily

Bioaccumulative potential

Product/substance	LogK _{ow}	BCF	Potential
2-(2-aminoethoxy)ethanol octanoic acid	-1.89 3.05	-	low low

Mobility in soil

Soil/water partition coefficient (Koc)

Mobility in soil

: Not available.

: Given its physical and chemical characteristics, the product is generally mobile in the ground It may contaminate ground water. the product may evaporate Soluble in water

Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues.

Date of revision : 2023/06/01 1 USA ENGLISH 10/14



SDS#: 088088

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	DOT Classification	IMDG	ICAO/IATA
UN/ID No	UN1760	UN1760	UN1760
UN proper shipping name	Corrosive liquids, n.o.s. (2-(2-aminoethoxy) ethanol)	CORROSIVE LIQUID, N.O.S. (2-(2-aminoethoxy) ethanol)	Corrosive liquid, n.o.s. (2-(2-aminoethoxy) ethanol)
Transport hazard class(es)	8 CORROSAR	8	8
Packing group	III	III	III
Environmental hazards	No.	No.	No.

Additional information

DOT Classification : Limited quantity Yes.

> Packaging instruction Exceptions: 154. Non-bulk: 203. Bulk: 241. **Quantity limitation** Passenger aircraft/rail: 5 L. Cargo aircraft: 60 L.

Special provisions IB3, T7, TP1, TP28

: Emergency schedules F-A, S-B **IMDG**

Special provisions 223, 274

ICAO/IATA Quantity limitation Passenger and Cargo Aircraft: 5 L. Packaging instructions: 852.

Cargo Aircraft Only: 60 L. Packaging instructions: 856. Limited Quantities - Passenger

Aircraft: 1 L. Packaging instructions: Y841.

Special provisions A3, A803

Special precautions for user : Transport within user's premises: always transport in closed containers that are

upright and secure. Ensure that persons transporting the product know what to do in the

event of an accident or spillage.

Transport in bulk according : Not available.

to IMO instruments

Section 15. Regulatory information

U.S. Federal regulations

: TSCA 4(a) proposed test rules: benzotriazole

TSCA 8(a) PAIR: 2-(2-aminoethoxy)ethanol

TSCA 8(a) CDR Exempt/Partial exemption: Not determined Commerce control list precursor: 2,2',2"-nitrilotriethanol

Clean Air Act Section 112 : Listed

(b) Hazardous Air **Pollutants (HAPs)**

Clean Air Act Section 602

Class I Substances

: Not listed

Clean Air Act Section 602

Class II Substances

: Not listed

Date of revision : 2023/06/01 USA **ENGLISH** 1 11/14



SDS#: 088088

DEA List I Chemicals

(Precursor Chemicals)

: Not listed

DEA List II Chemicals (Essential Chemicals) : Not listed

SARA 302/304

Composition/information on ingredients

No products were found.

SARA 304 RQ : Not applicable.

SARA 311/312

Classification : CORROSIVE TO METALS - Category 1

> SKIN CORROSION - Category 1B SERIOUS EYE DAMAGE - Category 1 HNOC - Corrosive to respiratory tract

Composition/information on ingredients

Name	%	Classification
2-(2-aminoethoxy)ethanol	≥10 - ≤25	CORROSIVE TO METALS - Category 1 SKIN CORROSION - Category 1B SERIOUS EYE DAMAGE - Category 1 HNOC - Corrosive to respiratory tract
Nitric acid, reaction products with cyclododecanol and cyclododecanone, by-products from, high-boiling fraction	≤5	EYE IRRITATION - Category 2A
octanoic acid	≤3	SKIN CORROSION - Category 1B SERIOUS EYE DAMAGE - Category 1

State regulations

Massachusetts : The following components are listed: 2-ETHANOL,(2-AMINOETHOXY);

TRIETHANOLAMINE

New York : None of the components are listed.

New Jersey : The following components are listed: 2-(2-AMINOETHOXY)ETHANOL;

TRIETHANOLAMINE

Pennsylvania : The following components are listed: ETHANOL, 2,2',2"-NITRILOTRIS-

California Prop. 65

⚠ WARNING: This product can expose you to Ethylene Glycol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

International regulations

Chemical Weapon Convention List Schedules I, II & III Chemicals

Ingredient name	List name	Status
Triethanolamine	Schedule III	Listed

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Date of revision : 2023/06/01 1 USA **ENGLISH** 12/14



SDS #: 088088

Not listed.

Inventory list

Vietnam inventory

Australia inventory (AIIC) : Not determined.

Canada inventory (DSL/NDSL) : Not determined.

China inventory (IECSC) : Not determined.

Europe inventory (EC) : At least one component is not listed.

Japan inventory : Japan inventory (CSCL): Not determined.

Japan inventory (ISHL): Not determined.

New Zealand Inventory of Chemicals (NZIoC) : At least one component is not listed.

Philippines inventory (PICCS) : Not determined.

Korea inventory (KECI) : Not determined.

Taiwan Chemical Substances Inventory (TCSI) : Not determined.

Thailand inventory : Not determined.

Turkey inventory : Not determined.

United States inventory (TSCA 8b) : Not determined.

The information stated in this section relates solely to the conformity of the chemical product with the countries Inventories. The information used to confirm the inventory status of this product may be based on additional data to the chemical composition shown in Section 3. Other regulations may apply for importation or marketing authorizations.

: Not determined.

Section 16. Other information

Hazardous Material Information System (U.S.A.)



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings and the associated label are not required on SDSs or products leaving a facility under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered trademark and service mark of the American Coatings Association, Inc.

The customer is responsible for determining the PPE code for this material. For more information on HMIS® Personal Protective Equipment (PPE) codes, consult the HMIS® Implementation Manual.

National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Date of revision : 2023/06/01 1 USA ENGLISH 13/14



SDS #: 088088

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

Procedure used to derive the classification

Classification	Justification
SKIN CORROSION - Category 1B	Expert judgment Calculation method Calculation method

History

Date of revision : 2023/06/01

previous revision date : No previous validation

Version : 1

Key to abbreviations : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973

as modified by the Protocol of 1978. ("Marpol" = marine pollution)

N/A = Not available

SGG = Segregation Group

UN = United Nations

References : Not available.

✓ Indicates information that has changed from previously issued version.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Date of revision : 2023/06/01 1 USA ENGLISH 14/14