

Valvoline™ DAILY PROTECTION SAE 5W-20 Motor Oil

Version: 1.11 Revision Date: 02/07/2023 Print Date: 04/10/2023

SECTION 1. IDENTIFICATION

Product name : Valvoline™ DAILY PROTECTION SAE 5W-20

Motor Oil

Product code : 797974

Manufacturer or supplier's details

Company name of supplier : Valvoline LLC

Address : 100 Valvoline Way

Lexington, KY 40509

United States of America (USA)

Telephone : 1-800-TEAMVAL (1-800-832-6825)

E-mail address : SDS@valvoline.com

Emergency telephone

number

: +1-800-VALVOLINE (+1-800-825-8654)

Recommended use of the chemical and restrictions on use

Recommended use : Motor Oil

SECTION 2. HAZARDS IDENTIFICATION

GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture



Valvoline™ DAILY PROTECTION SAE 5W-20 Motor Oil

Version: 1.11 Revision Date: 02/07/2023 Print Date: 04/10/2023

Components

Chemical name	CAS-No.	Concentration (% w/w)
Distillates, petroleum, solvent-refined	64741-88-4	>= 50 - < 60
heavy paraffinic		
DISTILLATES (PETROLEUM),	64742-54-7	>= 30 - < 40
HYDROTREATED HEAVY		
PARAFFINIC		
DISTILLATES (PETROLEUM),	64742-54-7	>= 1.5 - < 5
HYDROTREATED HEAVY		
PARAFFINIC		
HYDROTREATED LIGHT	64742-55-8	>= 1 - < 1.5
PARAFFINIC DISTILLATE		

Actual concentration is withheld as a trade secret

SECTION 4. FIRST AID MEASURES

General advice : Do not leave the victim unattended.

If inhaled : If unconscious, place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of eye contact : Remove contact lenses.

Protect unharmed eye.

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.

Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

delayed

: No symptoms known or expected.

Notes to physician : Treat symptomatically.

No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Hazardous combustion

products

: carbon dioxide and carbon monoxide

Valvoline...

SAFETY DATA SHEET

Valvoline™ DAILY PROTECTION SAE 5W-20 Motor Oil

Revision Date: 02/07/2023 Version: 1.11 Print Date: 04/10/2023

Further information Standard procedure for chemical fires.

Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Special protective equipment:

for firefighters

Wear self-contained breathing apparatus for firefighting if

necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Environmental precautions If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for

containment and cleaning up

Wipe up with absorbent material (e.g. cloth, fleece). Keep in suitable, closed containers for disposal.

SECTION 7. HANDLING AND STORAGE

Advice on protection against :

fire and explosion

Normal measures for preventive fire protection.

Advice on safe handling For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Conditions for safe storage Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid No materials to be especially mentioned.

Further information on

storage stability

: No decomposition if stored and applied as directed.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates, petroleum, solvent- refined heavy paraffinic	64741-88-4	TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
		TWA (Mist)	5 mg/m3	OSHA Z-1



Valvoline™ DAILY PROTECTION SAE 5W-20 Motor Oil

Version: 1.11 Revision Date: 02/07/2023 Print Date: 04/10/2023

		TWA (Mist)	5 mg/m3	OSHA P0
		TWA (Mist)	5 mg/m3	NIOSH REL
		ST (Mist)	10 mg/m3	NIOSH REL
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable particulate matter)	5 mg/m3	ACGIH

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally

required.

Hand protection

Material : neoprene, nitrile rubber

Break through time : >= 240 min Glove thickness : >= 0.35 mm

Directive : Equipment should conform to EN 374

Remarks : The selected protective gloves have to satisfy the

specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time. The data about break through time/strength of material are standard values! The exact break through time/strength of material has to be obtained from the producer of the

protective glove.

Eye protection : Safety glasses



Valvoline™ DAILY PROTECTION SAE 5W-20 Motor Oil

Version: 1.11 Revision Date: 02/07/2023 Print Date: 04/10/2023

Skin and body protection : Protective suit

Hygiene measures : General industrial hygiene practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Odour : No data available

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Boiling point/boiling range : No data available

Flash point : $> 390 \, ^{\circ}\text{F} / > 199 \, ^{\circ}\text{C}$

Method: Cleveland open cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Self-ignition : No data available

Upper explosion limit / Upper

flammability limit

6 %(V)

Calculated Explosive Limit

Lower explosion limit / Lower :

flammability limit

1 %(V)

Calculated Explosive Limit

Vapour pressure : 0.0012 hPa (68 °F / 20 °C)

Calculated Vapor Pressure

Relative vapour density : No data available

Relative density : No data available

Density : 0.8620 g/cm3 (60.01 °F / 15.56 °C)

Solubility(ies)

Water solubility : No data available

SAFETY DATA SHEET

Valvoline™ DAILY PROTECTION SAE 5W-20 Motor Oil

Version: 1.11 Revision Date: 02/07/2023 Print Date: 04/10/2023

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : 50 mm2/s (104 °F / 40 °C)

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : No decomposition if stored and applied as directed.

Possibility of hazardous

reactions

Stable under recommended storage conditions.

No hazards to be specially mentioned.

Conditions to avoid : excessive heat

Incompatible materials : Strong oxidizing agents

Hazardous decomposition

products

No hazardous decomposition products are known.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Not classified based on available information.

Components:

Distillates, petroleum, solvent-refined heavy paraffinic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.58 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: The substance or mixture has no acute

inhalation toxicity

Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Remarks: No mortality observed at this dose.

SAFETY DATA SHEET

Valvoline™ DAILY PROTECTION SAE 5W-20 Motor Oil

Version: 1.11 Revision Date: 02/07/2023 Print Date: 04/10/2023

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Acute oral toxicity : LD50 (Rat): > 15 g/kg

Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

Skin corrosion/irritation

Not classified based on available information.

Components:

Distillates, petroleum, solvent-refined heavy paraffinic:

Species : Rabbit

Result : No skin irritation

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Assessment : Slight, transient irritation Result : Slight, transient irritation

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Assessment : Slight, transient irritation Result : Slight, transient irritation

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Assessment : Slight, transient irritation Result : Slight, transient irritation

Serious eye damage/eye irritation

Not classified based on available information.

Components:

Distillates, petroleum, solvent-refined heavy paraffinic:

Species : Rabbit

Result : No eye irritation

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Result : No eye irritation
Assessment : No eye irritation



Valvoline™ DAILY PROTECTION SAE 5W-20 Motor Oil

Version: 1.11 Revision Date: 02/07/2023 Print Date: 04/10/2023

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Result : No eye irritation
Assessment : No eye irritation

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Result : Slight, transient irritation
Assessment : Slight, transient irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.

Components:

Distillates, petroleum, solvent-refined heavy paraffinic:

Test Type : Buehler Test Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Components:

Distillates, petroleum, solvent-refined heavy paraffinic:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation

Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation

Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation

Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Carcinogenicity - : Classified based on DMSO extract content < 3% (Regulation

Assessment (EC) 1272/2008, Annex VI, Part 3, Note L)

SAFETY DATA SHEET

Valvoline™ DAILY PROTECTION SAE 5W-20 Motor Oil

Version: 1.11 Revision Date: 02/07/2023 Print Date: 04/10/2023

IARC No component of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

OSHANo component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

NTP No component of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

No aspiration toxicity classification

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks : No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

Components:

Distillates, petroleum, solvent-refined heavy paraffinic:

Valvoline, which is a second s

SAFETY DATA SHEET

Valvoline™ DAILY PROTECTION SAE 5W-20 Motor Oil

Version: 1.11 Revision Date: 02/07/2023 Print Date: 04/10/2023 04/10/2023

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h Test Type: static test Test substance: WAF

Method: OECD Test Guideline 203

Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): > 10,000 mg/l

Exposure time: 48 h Test Type: static test Test substance: WAF

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

NOEL (Pseudokirchneriella subcapitata (green algae)): >=

100 mg/l

End point: Growth inhibition

Exposure time: 72 h Test Type: static test Test substance: WAF

Method: OECD Test Guideline 201

Toxicity to fish (Chronic

toxicity)

NOELR (Oncorhynchus mykiss (rainbow trout)): Calculated >=

1,000 mg/l

Exposure time: 14 d

Toxicity to daphnia and other :

aquatic invertebrates (Chronic toxicity)

NOEL (Daphnia (water flea)): 10 mg/l

Exposure time: 21 d Test substance: WAF

Method: OECD Test Guideline 211

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Toxicity to fish : LL50 (Fish): > 100 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Aquatic invertebrates): > 10,000 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

EL50 (Algae, algal mat (Algae)): > 100 mg/l

Exposure time: 72 h

Toxicity to fish (Chronic

toxicity)

NOEC (Fish): 10 mg/l

Toxicity to daphnia and other : NOEC (Aquatic invertebrates): 10 mg/l

Valvoline, TM

SAFETY DATA SHEET

Valvoline™ DAILY PROTECTION SAE 5W-20 Motor Oil

Version: 1.11 Revision Date: 02/07/2023 Print Date: 04/10/2023

aquatic invertebrates (Chronic toxicity)

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

Persistence and degradability

Components:

Distillates, petroleum, solvent-refined heavy paraffinic:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 2 - 4 % Exposure time: 28 d

Method: OECD Test Guideline 301B

Bioaccumulative potential

Components:

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Partition coefficient: n-

octanol/water

: log Pow: Expected > 7

Mobility in soil

No data available

Other adverse effects

Product:

Ozone-Depletion Potential : Regulation: 40 CFR Protection of Environment; Part 82



Valvoline™ DAILY PROTECTION SAE 5W-20 Motor Oil

Version: 1.11 Revision Date: 02/07/2023 Print Date: 04/10/2023

Protection of Stratospheric Ozone - CAA Section 602 Class I

Substances

Remarks: This product neither contains, nor was

manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A +

B).

Additional ecological information

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Contaminated packaging : Empty containers should be taken to an approved waste

handling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

49 CFR

Not regulated as a dangerous good

Special precautions for user

Not applicable

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

CERCLA Reportable Quantity

This material does not contain any components with a CERCLA RQ.



Valvoline™ DAILY PROTECTION SAE 5W-20 Motor Oil

Version: 1.11 Revision Date: 02/07/2023 Print Date: 04/10/2023

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : No SARA Hazards

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

Clean Air Act

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 112 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489).

Clean Water Act

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. CleanWater Act, Section 311, Table 117.3.

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

This product does not contain any priority pollutants related to the U.S. Clean Water Act

US State Regulations

Massachusetts Right To Know

Distillates, petroleum, solvent-refined heavy paraffinic	64741-88-4
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8

Pennsylvania Right To Know

Distillates, petroleum, solvent-refined heavy paraffinic DISTILLATES (PETROLEUM), HYDROTREATED HEAVY	64741-88-4 64742-54-7
PARAFFINIC PROPRIETARY SUBSTANCE OF LUBRIZOL PV1510	Not Assigned
000000280302	Not Assigned
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY	64742-54-7
PARAFFINIC	
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED	64742-65-0
HEAVY PARAFFINIC (<3 % DMSO EXTRACT)	

Maine Chemicals of High Concern

SAFETY DATA SHEET

Valvoline™ DAILY PROTECTION SAE 5W-20 Motor Oil

Version: 1.11 Revision Date: 02/07/2023 Print Date: 04/10/2023 04/10/2023

Lubricating oils (petroleum), hydrotreated 64742-58-1
PROPRIETARY OF LUBRIZOL 7065C Not Assigned
Lubricating oils (petroleum), C15-30, hydrotreated neutral oilbased 72623-86-0

Vermont Chemicals of High Concern

Lubricating oils (petroleum), hydrotreated 64742-58-1
PROPRIETARY OF LUBRIZOL 7065C Not Assigned
Lubricating oils (petroleum), C15-30, hydrotreated neutral oilbased 72623-86-0

Washington Chemicals of High Concern

Lubricating oils (petroleum), hydrotreated 64742-58-1
PROPRIETARY OF LUBRIZOL 7065C Not Assigned
Lubricating oils (petroleum), C15-30, hydrotreated neutral oilbased 72623-86-0

California List of Hazardous Substances

Distillates, petroleum, solvent-refined heavy paraffinic
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY
PARAFFINIC
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY
PARAFFINIC
HYDROTREATED LIGHT PARAFFINIC DISTILLATE
64742-55-8

California Permissible Exposure Limits for Chemical Contaminants

Distillates, petroleum, solvent-refined heavy paraffinic
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY
PARAFFINIC
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY
PARAFFINIC
64741-88-4
64742-54-7

The components of this product are reported in the following inventories:

TCSI : On the inventory, or in compliance with the inventory

TSCA : All substances listed as active on the TSCA inventory

AIIC : Not in compliance with the inventory

DSL : All components of this product are on the Canadian DSL

ENCS : Not in compliance with the inventory

ISHL : Not in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : Not in compliance with the inventory

IECSC : Not in compliance with the inventory

SAFETY DATA SHEET

Valvoline™ DAILY PROTECTION SAE 5W-20 Motor Oil

Version: 1.11 Revision Date: 02/07/2023 Print Date: 04/10/2023

NZIoC : On the inventory, or in compliance with the inventory

TECI: Not in compliance with the inventory

TSCA list

No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.


Inventories

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

NFPA 704:



Special hazard

HMIS® IV:

HEALTH	1	0
FLAMMABILITY		1
PHYSICAL HAZARD		0

HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
NIOSH REL : USA. NIOSH Recommended Exposure Limits

OSHA P0 : USA. Table Z-1-A Limits for Air Contaminants (1989 vacated

values)

OSHA Z-1 : USA. Occupational Exposure Limits (OSHA) - Table Z-1

Limits for Air Contaminants

ACGIH / TWA : 8-hour, time-weighted average



Valvoline™ DAILY PROTECTION SAE 5W-20 Motor Oil

Version: 1.11 Revision Date: 02/07/2023 Print Date: 04/10/2023

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-hour

workday during a 40-hour workweek

NIOSH REL / ST : STEL - 15-minute TWA exposure that should not be exceeded

at any time during a workday

OSHA P0 / TWA : 8-hour time weighted average OSHA Z-1 / TWA : 8-hour time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL -Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS -Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 -Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA -National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD -Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS -Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations: UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Revision Date : 02/07/2023

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the



Valvoline™ DAILY PROTECTION SAE 5W-20 Motor Oil

Version: 1.11 Revision Date: 02/07/2023 Print Date: 04/10/2023

specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

US / EN

Internal information: R0366793