

This Safety Data Sheet (SDS) has been prepared in accordance with the requirements of the OSHA Hazard Communication Standard (CFR 29 1910.1200).US

Section 1. Identification

GHS product identifier **Z Guard™ 8000 Black**

Synonyms Black Undercoating

Material uses Coating to Protect Semi-Trailers



Updated June 8, 2015

Supplier's details Z Technologies Corp.
26500 Capitol Ave.
Redford, MI 48239 USA
www.ztechprotection.com

Emergency telephone number 800-424-9300 Medical Emergency

For chemical emergency, spill, leak, fire, exposure or accident: call CHEMTREC day or night.
DOMESTIC NORTH AMERICA 800-424-9300;
INTERNATIONAL, CALL
703-527-3887 (collect calls accepted)
CHEMTREC Customer # CCN649135

Section 2. Hazards identification

OSHA/HCS status This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the Substance or mixture FLAMMABLE LIQUIDS - Category 3
ACUTE TOXICITY: INHALATION - Category 4
SKIN CORROSION/IRRITATION - Category 2
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A
SPECIFIC TARGET ORGAN TOXICITY (SINGLE EXPOSURE) [Narcotic effects] - Category 3
SPECIFIC TARGET ORGAN TOXICITY (REPEATED EXPOSURE) [central nervous system (CNS)] - Category 2
ASPIRATION HAZARD - Category 1

GHS label elements

Hazard pictograms



Signal word

Danger

Hazard statements

Flammable liquid and vapor.
Harmful if inhaled.
Causes serious eye irritation. Causes skin irritation.
May be fatal if swallowed and enters airways. May cause drowsiness and dizziness.
May cause damage to organs through prolonged or repeated exposure. (central nervous system (CNS))

Precautionary statements

Section 2. Hazards identification

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Wear protective gloves. Wear eye or face protection. Keep away from heat, sparks, open flames and hot surfaces. - No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Use only outdoors or in a well-ventilated area. Do not breathe vapor. Wash hands thoroughly after handling.

Response

Get medical attention if you feel unwell. IF exposed or concerned: Get medical attention. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or physician if you feel unwell. IF SWALLOWED: Immediately call a POISON CENTER or physician. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing. If skin irritation occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

Storage

Store locked up. Store in a well-ventilated place. Keep cool.

Disposal

Dispose of contents and container in accordance with all local, regional, national and international regulations.

Hazards not otherwise classified

SKIN INJECTION HAZARD

Spray from an airless spray tip, airless hose leaks or ruptured airless components can inject fluid into your body and cause extremely serious injury, including the need for amputation. Fluid injected into the skin might look like just a cut, but it is a serious injury. Get immediate surgical attention.

Section 3. Composition/Information on ingredients

Substance/mixture

STODDARD SOLVENT (Mineral Spirits)

Other means of identification

Low boiling point naphtha - unspecified; Low aromatic hydrocarbon solvents - medium flashpoint.; Petroleum distillates; mineral spirits; White spirits; Stoddard Solvent; Solvent Naphthas; Petroleum hydrocarbon solvent;

CAS number/other identifiers

CAS number 8052-41-3 21% by weight in coating

Ingredient name	%	CAS number
C9-C15 Cycloalkanes	13	**
C9-C15 Alkanes	6	**
C9-C15 Aromatics	2	**

* - Various ** - Mixture *** - Proprietary

Any concentration shown as a range is due to process variation.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact

Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband

Section 4. First aid measures

Skin contact	Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Continue to rinse for at least 10 minutes. Get medical attention. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute

Potential acute health effects

Eye contact	Causes serious eye irritation.
Inhalation	Harmful if inhaled. Can cause central nervous system (CNS) depression. May cause drowsiness and dizziness.
Skin contact	Causes skin irritation.
Ingestion	Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways. Irritating to mouth, throat and stomach.

Over-exposure signs/symptoms

Eye contact	Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	Adverse symptoms may include the following: nausea or vomiting headache drowsiness/fatigue dizziness/vertigo unconsciousness
Skin contact	Adverse symptoms may include the following: irritation redness
Ingestion	Adverse symptoms may include the following: nausea or vomiting

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician	If ingested, this material presents a significant aspiration and chemical pneumonitis hazard. Induction of emesis is not recommended. Consider activated charcoal and/or gastric lavage. If patient is obtunded, protect the airway by cuffed endotracheal intubation or by placement of the body in a Trendelenburg and left lateral decubitus position.
Specific treatments	Treat symptomatically and supportively.
Protection of first-aiders	No action shall be taken involving any personal risk or without suitable training. If it is suspected that gas or vapor is still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Specific hazards arising from the chemical

Flammable liquid and vapor. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. The vapor/gas is heavier than air and will spread along the ground. Vapors may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back. Runoff to sewer may create fire or explosion hazard.

Extinguishing media

Suitable extinguishing media

Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media

Do not use water jet.

Hazardous thermal decomposition products

Decomposition products may include the following materials:
carbon dioxide
carbon monoxide

Special protective actions for fire-fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency Personnel

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel"

Environmental Precautions

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill

Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

large spill

Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see Section 8). Avoid exposure - obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not swallow. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous: and can fatally explode if welded! Non equilibrium conditions may increase the fire hazard associated with this product.

Always bond receiving containers to the fill pipe before and during loading. Always confirm that receiving container is properly grounded. Bonding and grounding alone may be inadequate to eliminate fire and explosion hazards. Carefully review operations that may increase the risks such as tank and container filling, tank cleaning, sampling, gauging, loading, filtering, mixing, agitation, etc. In addition to bonding and grounding, efforts to mitigate the hazards may include, but are not limited to, ventilation, inerting and/or reduction of transfer velocities.

Always keep nozzle in contact with the container throughout the loading process. Do NOT fill any portable container in or on a vehicle.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

Bulk Storage Conditions: Maintain all storage tanks in accordance with applicable regulations. Use necessary controls to monitor tank inventories. Inspect all storage tanks on a periodic basis. Test tanks and associated piping for tightness. Maintain the automatic leak detection devices to assure proper working condition.

Section 8. Exposure controls/personal protection

Control parameters Occupational exposure limits

Ingredient name	Exposure limits
C9-C15 Cycloalkanes	ACGIH TIV (United States). TWA: 400 ppm 8 hours. Form: Methylcyclohexane
C9-C15 Aromatics	ACGIH TIV (United States). TWA: 400 ppm 8 hours. Form: (Methylcyclohexane)
Nonane, all isomer	ACGIH TIV (United States, 4/2014). TWA: 200 ppm 8 hours. TWA: 1050 mg/m3 8 hours.

Appropriate engineering Controls

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Section 8. Exposure controls/personal protection

Environmental exposure Controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, vapor controls, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Hygiene measures

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

Safety glasses equipped with side shields are recommended as minimum protection in industrial settings. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: Splash goggles. Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. chemical splash goggles. If inhalation hazards exist, a full-face respirator may be required instead.

Skin protection

Hand protection

Chemical-resistant gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers.

Body protection

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Other skin protection

Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory Protection

Use a properly fitted, air-purifying or supplied-air respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Section 9. Physical and chemical properties

Physical state	Liquid. [Syrupy liquid.]
Color	Black.
Odor	Characteristic hydrocarbon solvent odor. alcohol, present < 0.5%, can be smelled.
Boiling point/boiling range	157 to 218°C (314.6 to 424.4°F)
Flash point	Closed cup: 42°C (107.6°F) [Tagliabue (ASTM D-56)]
Evaporation rate	0.16 (n-butyl acetate. - 1)
Lower and upper explosive (flammable) limits	Lower: 0.6% Upper: 8%
Vapor pressure	0.029 kPa (0.22 mm Hg) [room temperature]
Vapor density	4.5 to 5 [Air - 1]
Density lbs/gal	11.5 lbs/gal
Solubility	Very slightly soluble in the following materials: cold water.
Auto-ignition temperature	230 to 240°C (446 to 464°F)

Section 10. Stability and reactivity

VOC	2.4 pounds per gallon
Reactivity	Not expected to be Explosive, Self-Reactive, Self-Heating, or an Organic Peroxide under US GHS Definition(s).
Chemical stability	The product is stable.
Possibility of hazardous reactions	Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition. Fatal explosion can occur upon welding empty container! Do not allow vapor to accumulate in low or confined areas.
Incompatible materials	Reactive or incompatible with the following materials: oxidizing materials
Hazardous decomposition products	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Nonane, all isomers	LC50 Inhalation Gas.	Rat	3200 ppm	4 hours

Conclusion/Summary

C9-C15 Alkanes: In animal studies utilizing mineral spirits containing up to 22% aromatics indicated that the acute central nervous system effects are reversible. Based on existing animal studies, the potential for persistent effects is not clear.

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
C9-C15 Aromatics	Skin - Mild irritant	Rabbit	-	24 hours 500 microliters	-
Nonane, all isomers	Skin - Mild irritant	Pig	-	24 hours 250 microliters	-
	Skin - Moderate irritant	Rat	-	96 hours 300 microliters	-

Skin **C9-C15 Alkanes:** Primary dermal irritation studies (four hour exposure) in rabbits utilizing mineral spirits containing less than 2% aromatics resulted in slight to moderate skin irritation. In humans, mineral spirits have produced slight to moderate skin irritation particularly with evaporation from the skin is prevented.

Eyes No additional information.

Respiratory **C9-C15 Alkanes:** Animal studies have demonstrated that mineral spirits produced mild respiratory tract irritation at elevated concentrations. Also, sensory respiratory tract irritation was evident by reduced breathing rates in the test animals in certain studies.

Section 11. Toxicological information

Sensitization

Skin

C9-C15 Alkanes: In animal studies utilizing mineral spirits containing up to 18%, aromatics skin sensitization is not evident.

Respiratory

No additional information.

Mutagenicity

Conclusion/Summary

C9-C15 Alkanes: In vivo and in vitro studies on mineral spirits containing up to 22 % aromatics indicate that these products are not genotoxic

Carcinogenicity

Conclusion/Summary

C9-C15 Alkanes: The National Toxicology Program (NTP) conducted two-year carcinogenicity studies in rats and mice with Stoddard Solvent IIC (less than 2% aromatics). The studies indicated that there was some evidence of carcinogenic activity in male rats (adrenal medulla neoplasms and renal tubule adenoma) but no evidence of carcinogenic activity in female rats. Further, there was equivocal evidence of carcinogenic activity in female mice (hepatocellular adenoma) but no evidence of carcinogenic activity in male mice. A low carcinogenic potential is suggested by a lack of genotoxic potential identified in in vivo and in vitro genetic toxicity tests (with and without metabolic activation).

Classification Reproductive toxicity

Conclusion/Summary

C9-C15 Alkanes: There were no treatment-related effects on pregnancy rate, mortality or gross Post mortem observations in animals studies utilizing mineral spirits containing less than 2% Aromatics.

Teratogenicity

Conclusion/Summary

C9-C15 Alkanes: There were no treatment-related effects on pregnancy rate, mortality or gross post mortem observations in animal studies utilizing mineral spirits containing less than 2% aromatics.

Specific target organ toxicity (single exposure)

Name	Category	Route of exposure	Target organs
C9-C15 Cycloalkanes	Category 3	Not applicable.	Narcotic effects
C9-C15 Alkanes	Category 3	Not applicable.	Narcotic effects
C9-C15 Aromatics	Category 3	Not applicable.	Narcotic effects
Nonane, all isomers	Category 3	Not applicable.	Narcotic effects

Aspiration hazard

Name	Result
C9-C15 Cycloalkanes	ASPIRATION HAZARD - Category 1
C9-C15 Alkanes	ASPIRATION HAZARD - Category 1
C9-C15 Aromatics	ASPIRATION HAZARD - Category 1
Nonane, all isomers	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure

Routes of entry anticipated: Oral, Dermal, Inhalation.

Potential acute health effects

Eye contact

Causes serious eye irritation.

Inhalation

Harmful if inhaled. Can cause central nervous system (CNS) depression. May cause drowsiness and dizziness.

Skin contact

Causes skin irritation.

Ingestion

Can cause central nervous system (CNS) depression. May be fatal if swallowed and enters airways. Irritating to mouth, throat and stomach.

Section 11. Toxicological information

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact Adverse symptoms may include the following:
pain or irritation
watering
redness

Inhalation Adverse symptoms may include the following:
nausea or vomiting
headache
drowsiness/fatigue
dizziness/vertigo
unconsciousness

Skin contact Adverse symptoms may include the following:
irritation
redness

Ingestion Adverse symptoms may include the following:
nausea or
vomiting

Potential chronic health effects

General May cause damage to organs through prolonged or repeated exposure.

Carcinogenicity Some aromatic impurities at concentrations below threshold of reporting are suspected of causing cancer. Risk of cancer depends on duration and level of exposure.

Mutagenicity No known significant effects or critical hazards.

Teratogenicity No known significant effects or critical hazards.

Developmental effects No known significant effects or critical hazards.

Fertility effects No known significant effects or critical hazards.

Section 12. Ecological information

Toxicity Not available

Conclusion/Summary Not available.

Persistence and degradability

Conclusion/Summary Not available.

Bioaccumulative potential

Product/ingredient name	logP _{ow}	BCF	Potential
C9-C15 Aromatics	2.8 to 6.5	99 to 5780	high
Nonane, all isomers	5.65	105	low

Mobility in soil

Soil/water partition \ coefficient (KOC) Not available

Other adverse effects No known significant effects or critical hazards.

Section 13. Disposal considerations





Disposal methods

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. **Do not cut, weld or grind used container: it can cause fatal explosion!** Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

RCRA classification

D001, D018

Section 14. Transport information

	DOT Classification	IMDG	IATA
UN number	UN1268	UN1268	UN1268
UN proper shipping name	UN1268, Petroleum Distillates, n.o.s. (Stoddard Solvent), 3, PG III	UN1268, Petroleum Distillates, n.o.s. (Stoddard Solvent), 3, PG III	UN1268, Petroleum Distillates, n.o.s. (Stoddard Solvent), 3, PG III
Transport hazard class(es)	3 	3  	3 
Packing group	III	III	III
Environmental hazards	No	Yes	No
Additional information	No additional remark		

Special precautions for user

Transport within user's premises always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Section 15. Regulatory information

U.S. Federal regulations

TSCA 12(b) one-time export: **Nonane, all isomers**

United States inventory (TSCA 8b): All components are listed or exempted.

Clean Water Act (CWA) 307: Naphthalene

Clean Water Act (CWA) 311: Naphthalene;

This material is classified as an oil under Section 311 of the Clean Water Act (CWA) and the Oil Pollution Act of 1990 (OPA). Discharges or spills which produce a visible sheen on waters of the United States, their adjoining shorelines, or into conduits leading to surface waters must be reported to the EPA's National Response Center at (800) 424-8802.

SARA 302/304

Composition/information on ingredients

SARA 304 RQ

Not applicable.

Section 15. Regulatory information

SARA 311/312

Classification

Fire hazard

Immediate (acute) health hazard

Delayed (chronic) health hazard

Composition/information on ingredients

Name	Fire hazard	Sudden release of pressure	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard
C9-C15 Cycloalkanes	Yes.	No.	No.	Yes.	No.
C9-C15 Alkanes	Yes.	No.	No.	Yes.	No.
C9-C15 Aromatics	Yes.	No.	No.	Yes.	No.
Nonane, all isomers	Yes.	No.	No.	Yes.	No.

SARA 313

	Product name	CAS number	%
Form R - Reporting requirements	None present in regulated quantities		
Supplier notification			

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts

The following components are listed: STODDARD SOLVENT

New Jersey

The following components are listed: STODDARD SOLVENT

Pennsylvania

The following components are listed: STODDARD SOLVENT

International regulations

International lists

Australia inventory (AICS): All components are listed or exempted.

China inventory (IECSC): All components are listed or exempted.

Japan inventory: All components are listed or exempted.

Korea inventory: All components are listed or exempted.

Malaysia Inventory (EHS Register): All components are listed or exempted.

New Zealand Inventory of Chemicals (NZIoC): All components are listed or exempted.

Philippines inventory (PICCS): All components are listed or exempted.

Taiwan inventory (CSNN): Not determined.

Canada inventory

All components are listed or exempted.

EU Inventory

All components are listed or exempted.

WHMIS (Canada)

Class B-3: Combustible liquid with a flash point between 37.8°C (100°F) and 93.3°C (200°F).
Class D-2B: Material causing other toxic effects (Toxic).

Section 16. Other information

Hazardous Material Information System (U.S.A.)

HEALTH	*	2
Flammability		2
Physical hazards		1
PERSONAL PROTECTION		

The PPE (Personal Protection Equipment) designation in the HMIS is provided for use by employees at supplier sites only. Other users of this product are encouraged to evaluate the hazards of the product and assign PPE that is applicable to their specific situations.

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program.

HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

History

Date of issue/Date of revision May 31, 2015

Key to abbreviations

Acute Toxicity Estimate
 BCF - Bioconcentration Factor
 GHS - Globally Harmonized System of Classification and Labelling of Chemicals
 IATA - International Air Transport Association
 IBC - Intermediate Bulk Container
 IMDG - International Maritime Dangerous Goods
 LogPow - logarithm of the octanol/water partition coefficient
 MARPOL 73/78 - International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" - marine pollution)
 UN - United Nations\

Z GUARD™ IS A REGISTERED TRADEMARK OF Z TECHNOLOGIES CORPORATION.

Z Technologies Corporation Inc. Safety Data Sheet

For Additional Information contact MSDS Coordinator during business hours, EST time:(313) 9370710

Notice

Z Technologies Corporation Inc. ("Z Tech") expressly disclaims all express or implied warranties of merchantability and fitness for a particular purpose, with respect to the product or information provided herein, and shall under no circumstances be liable for incidental or consequential damages.

All information appearing herein is based upon data obtained from the manufacturers and/or recognized technical sources. While the information is believed to be accurate, Z Technologies makes no representations as to its accuracy or sufficiency. Conditions of use are beyond Z Tech's control and therefore users are responsible to verify this data under their own operating conditions to determine whether the product is suitable for their particular purposes and they assume all risks of their use, handling, and disposal of the product, or from the publication or use of, or reliance upon, information contained herein.

This information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.

END OF SDS