



Transmax ATF +4

ATF+4 Type Automatic Transmission Fluid

Description

Castrol Transmax ATF+4® Automatic Transmission Fluid is for use in Fiat Chrysler vehicles.

Advantages

Full Synthetic formula exceeds ATF+3® requirements

Certified and approved for all Chrysler cars and trucks that require ATF+4®, Mopar ATF+3®, ATF+2®, ATF+2 Type 7176®, or ATF+®

Technologically advanced, full synthetic formulation provides superior transmission life

Engineered with superior base oils to ensure superb low and high temperature performance

Product Performance Claims

Meets or Exceeds Fiat Chrysler ATF+4® requirements.

ATF+4® approved and licensed by Fiat Chrysler(License Number 40630033).

Typical Characteristics

Name	Method	Units	Typical Results
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	33.24
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	7.51
Viscosity Index	ASTM D2270	None	204
Viscosity, Brookfield @ -40C (75W)	ASTM D2983	mPa.s (cP)	8380
Pour Point	ASTM D97	°C	-51
Flash Point, COC	ASTM D92	°C	198
Specific Gravity, 60 F	ASTM D1298		0.85
Pounds Per Gallon	ASTM D287		7.08

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Transmax ATF +4
20 Apr 2017

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Lubricants USA Inc., 1500 Valley Road, Wayne, NJ 07470
Telephone: 1,800.462.0835
www.castrol.com/us Email: contactus@bp.com