



# Castrol Transmax CVT

CVT Fluid

## Description

Castrol Transmax CVT, formulated with *Smooth Drive Technology*<sup>TM</sup> and premium full-synthetic base oil, is designed for most continuously variable transmissions. Its superior technology enables longer transmission life. It is suitable for use in most passenger cars fitted with push belt transmissions. Ensuring peace of mind across a wide range of vehicles.

## Advantages

- Enhanced friction durability for a smoother drive for longer transmission life.
- Enhanced wear protection for longer transmission life.
- Superior high temperature protection to effectively resist oxidation.
- Superior variator torque capacity that can prevent belt or chain slippage.

## Typical Characteristics

Name	Method	Units	Transmax CVT
Density @ 15C, Relative	ASTM D4052	g/ml	0.850
Viscosity, Kinematic 40C	ASTM D445	mm <sup>2</sup> /s	35
Viscosity, Kinematic 100C	ASTM D445	mm <sup>2</sup> /s	7.25
Viscosity Index	ASTM D2270	None	178
Pour Point	ASTM D97	°C	-51
Viscosity, Brookfield @ -40C	ASTM D2983	mPa.s (cP)	11100
Flash Point, COC	ASTM D92	°C	218

## Product Performance Claims

Suitable for use where:

Toyota CVT Fluid TC

Toyota CVT Fluid FE

Nissan CVT Fluid NS-1

Nissan CVT Fluid NS-2

Nissan CVT Fluid NS-3

MMC DIAQUEEN ATF SP-III

MMC DIAQUEEN CVT Fluid J1

MMC DIAQUEEN CVT Fluid J4

MMC DIAQUEEN CVT Fluid J4+

Mazda CVTF 3320

Subaru i-CVT Fluid

Subaru i-CVT FG

Subaru Lineartronic High Torque Chain CVTF

Daihatsu AMMIX CVT Fluid DC

Daihatsu AMMIX CVT Fluid DFE

Suzuki CVT Fluid 3320

Suzuki CVT Fluid Green 1

Suzuki CVT Fluid Green 2

Suzuki CVTF TC

Suzuki NS-2

Honda HCF-2 \*

Hyundai/Kia SP-III

Chrysler NS-2

Chrysler CVTF+4

Mini Cooper EZL799

Ford CVT23

MB 236.20

\* Transmax CVT is suitable for use in all of Honda CVTs except 2001-2007 Model Honda Fit/Jazz which are equipped with Starting Clutch

Castrol Transmax CVT

01 Nov 2018

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Lubricants USA Inc., 1500 Valley Road, Wayne, NJ 07470

Telephone: 1,800.462.0835

[www.castrol.com/us](http://www.castrol.com/us) Email: [contactus@bp.com](mailto:contactus@bp.com)