



## Castrol Transmax Dex/Merc

Automatic Transmission Fluid

### Description

Castrol Transmax™ DEX/MERC Domestic Multi-Vehicle Transmission Fluid is for use in older Ford and General Motors vehicles.

### Advantages

- Enhanced friction durability for smooth transmission performance
- Meets DEXRON®-IIIH requirements. Also satisfies requirements of DEXRON®, DEXRON®-III, IIE and II. Do not use this ATF in applications calling for DEXRON®-VI. Use Castrol Transmax™ Type F ATF in applications calling for Type F.
- Meets MERCON® requirements. May also be used in power steering applications where MERCON® is required. Do not use this ATF in applications calling for MERCON® V or MERCON® SP.

### Warranty and Protection Requirements

Exceeds all passenger car and light truck manufacturer's warranty requirements for vehicles, transmissions or power steering service where a DEXRON®-IIIH or MERCON® type ATF is specified

### Industry Specifications and OEM Approvals

Meets or Exceeds General Motors DEXRON®-IIIH Requirements

- Meets or Exceeds Ford MERCON® Requirements

### Typical Characteristics

Test	Method	Typical Results
Viscosity at 40°C, cSt	ASTM D-445	32
Viscosity at 100°C, cSt	ASTM D-445	7.2
Viscosity Index	ASTM D-2270	200
Color, Typical	ASTM D-1500	7
Appearance		Red
Brookfield Viscosity at -40 C, cP	ASTM D-2983	17,000
Pour Point, °C (°F)	ASTM D-97	-43(-45)
Flash Point, °C (°F)	ASTM D-92	177(350)
Specific Gravity, 60°F	ASTM D-1298	0.863
Pounds per Gallon	ASTM D-287	7.19

## Typical Physical Characteristics

Test	Method	Typical Results
Viscosity at 40°C, cSt	ASTM D-445	32
Viscosity at 100°C, cSt	ASTM D-445	7.2
Viscosity Index	ASTM D-2270	200
Color, Typical	ASTM D-1500	7
Appearance		Red
Brookfield Viscosity at -40 C, cP	ASTM D-2983	17,000
Pour Point, °C (°F)	ASTM D-97	-43(-45)
Flash Point, °C (°F)	ASTM D-92	177(350)
Specific Gravity, 60°F	ASTM D-1298	0.863
Pounds per Gallon	ASTM D-287	7.19

## Product Performance Claims

Meets MERCON®  
DEXRON® IIIH  
Suitable for use as power steering fluid

## Additional Information

### Part Numbers and UPCs

#### Packaged Goods

<b>Case Size</b>	6/1 QT	3/1 GA
<b>Case Part No.</b>	06820	03520
<b>Bottle/ Unit UPC</b>	0-79191-00462-3	0-79191-33520-8
<b>Case UPC</b>	0-79191-06820-5	0-79191-03520-7

#### Bulk/Drum

<b>Unit Size</b>	16 GA KEG	55 GA DRUM	BULK
<b>Part No.</b>	0463	0464	0460

Castrol Transmax Dex/Merc  
20 Jun 2017  
Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

BP Lubricants USA Inc., 1500 Valley Road, Wayne, NJ 07470  
Telephone: 1,800.462.0835  
www.castrol.com/us Email: contactus@bp.com