



Castrol Transmax Mercon V

Automatic Transmission Fluid

Description

Castrol Transmax™ MERCON® V Transmission Fluid is for use in most Ford vehicles.

Advantages

- Enhanced friction durability provides superior transmission life and promotes smooth shifting
- Exceptional thermal protection guards against transmission wear
- Certified and approved by Ford for all cars and trucks that require MERCON® or MERCON® V
- Do not use this ATF in applications calling for MERCON® SP or Type F

Warranty and Protection Requirements

- Exceeds all passenger car and light truck manufacturer's warranty requirements for vehicles, transmissions or power steering service where a MERCON® or MERCON® V type ATF is specified

Industry Specifications and OEM Approvals

- Meets or exceeds Ford MERCON® V and Ford MERCON® Requirements
- MERCON® V Approved and Licensed by Ford Motor Company

Typical Physical Characteristics

Test	Method	Typical Results
Viscosity at 40°C, cSt	ASTM D-445	35
Viscosity at 100°C, cSt	ASTM D-445	7.4
Viscosity Index	ASTM D-2270	186
Color, Typical	ASTM D-1500	7
Appearance		Red
Brookfield Viscosity at -40 C, cP	ASTM D-2983	9,800
Pour Point, °C (°F)	ASTM D-97	-35(-31)
Flash Point, °C (°F)	ASTM D-92	180(356)
Specific Gravity, 60°F	ASTM D-1298	0.862
Pounds per Gallon	ASTM D-287	7.17

* Due to continual product research and development, the information contained herein is based on products purchased in the U.S. and subject to change without notification. Typical properties may vary slightly.

Additional Information

Part Numbers and UPCs

Packaged Goods

Case Size	6/1 Qt
Case Part No.	06068
Bottle/ Unit UPC	0-79191-00068-7
Case UPC	0-79191-06068-1

Bulk/Drum

Unit Size	55 Gal Drum
Part No.	55176

Castrol Transmax Mercon V
12 Mar 2012

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com