



Transmax Type F

Automatic Transmission Fluid

Description

Castrol Transmax Type F is designed for use in older ford vehicles (pre 1982) requiring the unique friction characteristics of a type F transmission fluid.

NB: Do not use in transmissions where a Mercon or Dexron type fluid is required

Advantages

- Excellent lubrication to gears and bushings allowing optimized transmission operation.
- Good thermal and oxidation stability prolonging component life.

Typical Characteristics

Name	Method	Units	Transmax Type F
Density @ 15C, Relative	ASTM D4052	g/ml	0.865
Appearance	Visual	-	Clear & Bright
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	38
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	7.4
Viscosity Index	ASTM D2270	None	165
Viscosity, Brookfield @ -40C	ASTM D2983	mPa.s (cP)	30900
Pour Point	ASTM D97	°C	-45
Flash Point, COC	ASTM D92	°C	210

Product Performance Claims

Meets Ford ESW-M2C-33F, ESW-M2C-33G

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Transmax Type F

07 Sep 2015

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com