



Hydraulic Oils

	Description	Application	Viscosities	Available Size
Anti-Wear Hydraulic Oil	Contains an anti-wear additive to prevent pump wear.	Industrial, Marine, and Offroad systems that have Vane, Piston, or Gear type Pumps.	ISO VG 22 through ISO VG 150	Qts, Gals, 5 Gal Pail, 55 Gal Drum
Cold Weather Hydraulic Oil	Maintains consistent viscosity in all temperatures. Reduce Wear and Extend Service Intervals.	Hydraulic Systems operating in extreme cold or arctic conditions.	ISO VG 15 through ISO VG 100	Qts, Gals, 5 Gal Pail, 55 Gal Drum
Zinc Free/ Biodegradable Hydraulic Oil	Meets or Exceeds environmental regulations set by the U.S. Fish and Wildlife Service & EPA.	Systems requiring zinc free hydraulic fluid and systems operating in environmentally sensitive areas.	ISO VG 15 through ISO VG 100	5 Gal Pail, 55 Gal Drum
High Viscosity Index (HVI) Hydraulic Oil	Extreme duty hydraulic fluid specifically designed for equipment operating in adverse environments.	Industrial/Construction Equipment, Farm Equipment. Common reservoir applications for Transmissions and Wet Brakes.	ISO VG 32/SAE 10W, ISO VG 46, ISO VG 69/ SAE 20W	1 Gal, 5 Gal Pail, 55 Gal Drum
Food Grade Hydraulic Oil	Meets USDA and/or FDA Guidelines for incidental food contact.	Equipment used in the food processing and packaging industry.	ISO VG 32 through ISO VG 68	5 Gal Pail, 55 Gal Drum
Off-Road Equipment Hydraulic Oil	Maintains viscosity over a wide temperature range. High dielectric strength.	Bucket Trucks, Cherry Pickers and other hydraulic equipment requiring an HVI type fluid.	ISO VG 15 through ISO VG 100	5 Gal Pail, 55 Gal Drums
MIL-H-5606 Hydraulic Oil	Highly Refined, mineral based hydraulic fluid.	Aviation missile systems, landing gear, and autopilot. Land based equipment requiring MIL Spec 5606.	ISO VG 15	Qts, Gal, 5 Gal Pail, 55 Gal Drum